

- AUDIO
- VIDEO
- LIGHTS
- MUSIC
- ACCESSORIES



FBT JOLLY SERIES COMPACT SPEAKERS

These are lightweight and compact 2-way speakers in black polypropylene enclosures and come in passive and active models, some of which are bi-amped. They feature 5"-15" woofers and dome tweeters. Models listed with Neutrik Combi (XLR and 1/4") input jacks also have mic/line inputs. The 2 active subwoofer models feature birch enclosures. The Red Series offers slightly less powerful, less expensive alternatives. The JOLLY5B is also available in a transformer tap version for use in 70V/100V systems.



ITEM	DESCRIPTION	PRICE
Blue Series		
JOLLY5B	5" passive speaker, 80W, 16ohms, 1/4" & terminal inputs	155.00
JOLLY8B	8" passive speaker, 100W, 8ohms, 2 Neutrik NL4 inputs	255.00
JOLLY12B	12" passive speaker, 200W, 8ohms, 2 Neutrik NL4 inputs	389.00
JOLLY15B	15" passive speaker, 350W, 8ohms, 2 Neutrik NL4 inputs	439.00
JOLLY5BA	5" active bi-amped spkr, 80/20W, Neutrik combi-jack input	319.00
JOLLY8BA	8" active bi-amped spkr, 150/50W, Neutrik combi-jack input	479.00
JOLLY12BA	12" active bi-amped spkr, 250/50W, Neutrik combi-jack input	679.00
JOLLY15BA	15" active bi-amped spkr, 300/50W, Neutrik combi-jack input	749.00
Red Series		
JOLLY5RA	5" active speaker, 60W, Neutrik combi-jack input	235.00
JOLLY8RA	8" active bi-amped speaker, 80/20W, Neutrik combi-jack input	365.00
Subwoofers		
JOLLYSUB10A	10" active subwoofer, 300W	889.00
JOLLYSUB12A	12" active subwoofer, 300W	1069.00
70V/100V Model		
JOLLY5BT	5" passive speaker w/transformer, 80W, terminal strip I/O only	199.00



FENDER 1270 SERIES FLOOR MONITORS These two-way floor monitors are made of molded ABS plastic and won't take up much space on stage. Both versions feature a 10" woofer with 2" Voice Coil and 1 1/2" Coaxial Ceramic Compression Driver. The powered version is bi-amped at 100W while the passive version will handle 200W continuous at 8ohms.



ITEM	DESCRIPTION	PRICE
1270	Passive floor monitor, 10", 8ohms	159.99
1270P	Active floor monitor, 10", 100W	259.99



GALAXY AUDIO HOTSPOT MINI SPEAKERS

The PA6S is a compact PA 2-way system featuring a 6.5" LF neodymium woofer and a 1.5" HF neodymium tweeter. It has a built-in compressor/limiter and an XLR pass thru on channels 1 and 2. The HOT-SPOT-VC-7 (HS7) is engineered for near-field vocal monitoring and has two Neolite 5" drivers and an 18dB stepped attenuator volume control. Both models include an integrated handle and mounting point for a mic boom.



ITEM	DESCRIPTION	PRICE
PA6S	2-way powered PA, 170W @ 4ohms, 80Hz-18kHz	299.99
HOT-SPOT-VC-7	Vocal monitor, passive, 200W, 150Hz-18kHz	139.99

GALAXY AUDIO MSPA/MSPADC POWERED MICRO SPOT MONITOR

Weighing only 4.82lbs and smaller than a football, it delivers 30W to its internal 4.5" speaker, up to 99dB SPL. Includes XLR and 1/4" inputs, a 2-band EQ and built-in compressor/limiter. Mount to a wall or ceiling, or atop a mic stand with the included mounting hardware.



ITEM	DESCRIPTION	PRICE
MSPA	Power: 90-250VAC, 50/60Hz, 30W	199.99
MSPADC	Power: 90-250VAC, 50/60Hz, 30W, 12VDC, 3A	229.99



JBL CONTROL 1 PRO/CONTROL 5 SPEAKERS

Perfect for applications where tight corners and tough angles are all too common, the Control Series features a wide variety of available mounting systems allowing enclosures to be easily positioned. The Control 1 Pro features an updated crossover network design providing steeper crossover slopes for exceptional sonic performance and improved consistency throughout the listening area. A wall-mount bracket is included. The molded enclosure houses magnetically shielded transducers, making the Control 1 Pro well-suited for use near video monitors. Input connections are via spring-loaded terminals. The Control 5 features a 6 1/2" woofer and 1" titanium tweeter, and is also magnetically shielded for use near computer monitors. Both models priced as each, but sold in pairs.

ITEM	DESCRIPTION	PRICE
CONTROL-1-PRO	5.25" 2-way speaker, 80Hz-20kHz, 150W, 4ohms	78.00
CONTROL-1-PRO-WH	White version of above speaker	78.00
CONTROL-5	6.5" monitor loudspeaker, 75Hz-20kHz, 175W, 4ohms, black	160.00
CONTROL-5-WHITE	6.5" monitor loudspeaker, 75Hz-20kHz, 175W, 4 ohms, white	160.00
5-0100	Ultra-duty mount bracket for Control-1-Pro	70.00
MTC51	Wall-mount bracket, ball/clamp design for Control 5	110.00
MTC52	Ceiling-mount bracket, ball/clamp design for Control 5	95.00

JBL CONTROL 30 A 10" 3-way speaker featuring a 5-1/4" mid-range and compression driver HF and 120x110 deg coverage. Power handling is 250W pink noise, 500W program and 1000W peak, and has an integral 70V transformer, a weather-resistant finish, and Sonic Guard overpower protection. It has excellent natural sound reproduction. 8-ohm nominal load, plus integral 70V transformer terminal strip wire mounts, 42lbs.



ITEM	DESCRIPTION	PRICE
CONTROL-30	10" 3-way speaker, black	649.00
CONTROL-30-WHITE	10" 3-way speaker, white	649.00

JBL CONTROL 29AV-1 An upgraded version of the Control 29AV loudspeaker, featuring re-voicing advancements in the crossover network. Developed in conjunction with Walt Disney Imagineering, the re-voicing provides a flatter frequency response with more natural midrange sound character, while extending the bass response. The result is improved clarity on speech and vocals with a more natural sound and wider frequency response for music.



ITEM	DESCRIPTION	PRICE
C29AV-1	8" 2-way speaker, 300W program	369.00

CERTIFIED REPAIR BY EXPERIENCED TECHNICIANS

FULL COMPASS IS A FACTORY-AUTHORIZED REPAIR CENTER FOR MANY OF THE MAJOR BRANDS WE CARRY.



NEED A REPLACEMENT PART? NO PROBLEM!

IF WE DON'T HAVE THE PART YOU NEED IN STOCK, WE'LL GET IT FOR YOU!

VIEW OUR PARTS CATALOG ONLINE!



JBL EON 300 & 500 SERIES POWERED SPEAKERS The EON-305 is a 15" 2-way passive loudspeaker that features 2 parallel-linked Speakon/ 1/4" combo jacks. The EON-315's input is a balanced XLR/1/4" combo that is mic-line switchable and features 1 XLR output for signal loop-through. The EON 500 Series features one XLR out (selectable), one XLR/ 1/4" input, additional 1/4" ins, and Differential Drive® woofers. The EON-510 has a 10" woofer, the EON-515XT has a 15" woofer and the EON- 518S has an 18" woofer. The EON-515XT also features Crown® Class "D" technology. The EON-518S features level control, dual inputs, a stereo crossover network, a pole-mount cup for sub/satellite applications, a polarity reverse switch, peak limiter and a speaker level input.

ITEM	DESCRIPTION	PRICE
EON-30515" 2-way, passive, 250W, 100°x60°, 50Hz-18kHz, 33lbs	379.00
EON-31515" 2-way, active, 220W/LF, 60W/HF, 100°x60°, 50Hz-18kHz, 35lbs	499.00
EON-51010" 2-way, active, 220W/LF, 60W/HF, 100°x60°, 70Hz-17kHz, 17lbs	599.00
EON-515XT15" 2-way, active, 525W/LF, 100W/HF, 100°x60°, 42Hz-18kHz, 32.5lbs	699.00
EON-518S18" subwoofer, active, 500W, 42Hz-100Hz, 65lbs	899.00

JBL JRX JRX100 delivers the performance and prestige JBL is known for an affordable price point. Features include 90x40 Progressive Transition Waveguide for best horn performance, beefy all steel handles and 18 gauge steel grill, SonicGuard protection, 3/4" MDF wood construction and dual-angle pole socket for better coverage. Connections are both Neutrik Speakon and 1/4" phone sockets. Install versions have no handles, feet or pole sockets but have M10 eyebolts.



ITEM	DESCRIPTION	PRICE
JRX112M12" 2-way floor monitor 60Hz-16kHz 8ohms 250/1000W 43lbs	319.00
JRX112MIInstall version	359.00
JRX11515" 2-way, 38Hz-16kHz 8ohms 250/1000W 60.5lbs	329.00
JRX115IInstall version	369.00
JRX118S18" subwoofer, 38Hz-300Hz 4ohms, 350/1400W 71lbs	499.00
JRX118SP18" powered subwoofer, 300/500W amplifier, stereo crossover, XLR inputs	799.00
JRX125Dual-15" 2-way, 35Hz-16kHz 4ohms 500/2000W 94lbs	479.00

JBL MRX SERIES Compact, lightweight, truly portable, the MRX500 is the PA system for musicians and DJ's who need fully professional sound and performance within a budget. Features include 400W Differential Drive® transducer in 12" and 15" configurations, perfectly matched to the brand new 1.5" annular polymer diaphragm compression driver producing a transducer engine that weighs significantly less than traditional transducer designs, yet their performance, sound quality and power handling are extraordinary. They include Neutrik® NLAMP connectors and feature rugged plywood enclosures, covered with JBL's DuraFlex™ finish. The MRX512M and MRX515 feature a dual-angle pole mount with a 10° down angle.



ITEM	DESCRIPTION	PRICE
MRX512M12", 2-way main PA/stage w/monitor, 400W, 60Hz-20kHz	649.00
MRX51515", 2-way main PA, 400W, 52Hz-20kHz	689.00
MRX525Dual-15", 2-way main PA, 800W, 40Hz-20kHz	949.00
MRX518S18" subwoofer, 500W, 35Hz-200Hz	649.00
MRX528SDual-18" subwoofer, 1000W, 35Hz-250Hz	949.00



JBL PRX600 SERIES LOUDSPEAKERS This series employs technology that allows you to create versatile and portable systems. Each model is designed for specific applications but integrate seamlessly with one another to offer many choices when building a system. Features Neodymium compression drivers, strong, lightweight poplar plywood and are protected by JBL's DuraFlex™ finish. The amplifier input panel of all models has XLR or 1/4" mic/instrument inputs with XLR loop through.

ITEM	DESCRIPTION	PRICE
PRX612M12" 2-way active speaker, 1000W (2 x 500), Crown Class D amp, 50Hz-19.5kHz, 90° x 50° nominal coverage, pole mount socket	699.00
PRX615M15" 2-way active speaker, 1000W (2 x 500), Crown Class D amp, 45Hz-19kHz, 90° x 50° nominal coverage, 8 M10 suspension and one pullback point	799.00
PRX62515" dual 2-way active speaker, 1500W (3 x 500), Crown Class D amp, 40Hz-19.5kHz, 90° x 50° nominal coverage, 8 M10 suspension and 1 pullback point	1099.00
PRX63515" 3-way active speaker, 1500W (3 x 500), Crown Class D amp, 41Hz-19kHz, 90° x 50° nominal coverage, suspension points and pole mount socket	999.00
PRX618S18" active subwoofer, 600W, Class D, 41Hz-130Hz, top pole mount	999.00
PRX618S-XLF18" active subwoofer, 1000W (2 x 500), Class D, 30Hz-105Hz, top pole mount	1299.00

JBL SRX700 SERIES The SRX700 series features high-power low-frequency drivers which are also greatly reduced in weight. SRX700 uses JBL's patented Differential Drive® woofers with neodymium magnets. Neodymium's magnetic properties allow a few ounces to replace pounds of conventional magnet.



ITEM	DESCRIPTION	PRICE
SRX712M12", 2-way stage monitor, 800W, 90° x 50° horn, 83Hz-18kHz (±3dB), 33lbs	1099.00
SRX71515", 2-way, 800W, 75° x 50° coverage, 53Hz-20kHz(±3dB), 48lbs	1359.00
SRX722Dual 12" 2-way, 1600W, 75° x 50° coverage, 81Hz-20kHz (±3dB), 76lbs	1659.00
SRX725Dual 15" 2-way, 1200W, 75° x 50° coverage, 53Hz-20kHz (±3dB), 100lbs	1799.00
SRX73818" 3-way, 800W, 60° x 40° coverage, 44Hz-20kHz (±3dB), 95lbs	1829.00
SRX718S18" subwoofer, 800W, 34Hz-220Hz, (±3dB), 79 lbs	929.00
SRX728SDual 18" subwoofer, 1600W, 33Hz-220Hz (±3dB), 166.5lbs	1529.00



Where do you want to take your music?

M-AUDIO GSR SERIES TWO-WAY ACTIVE SPEAKERS The 250W 10" and the 300W 12" models feature a 24dB/octave crossover, a 2.5" voice coil, a 90°H x 60°V dispersion angle, integrated fly points, a 1.4" pole mount, and 4 EQ presets – normal, hi-fi, DJ, and voice. The GSR10 features a 1" HF compression driver while the GSR12 has a 1.3" HF compression driver. The 18" subwoofer features variable crossover, a phase invert button for a focused bass sound, and a 1.4" speaker stand receptacle. All models have a balanced XLR/1/4" TRS combo jack with XLR loop-through.



ITEM	DESCRIPTION	PRICE
GSR1010" 2-way active, 250W, 70Hz-18kHz, 25lbs	399.00
GSR1212" 2-way active, 300W, 55Hz-20kHz, 31lbs	499.00
GSR1818" active subwoofer, 500W, 40Hz-150Hz, 71lbs	799.00



MACKIE®

MACKIE THUMP SERIES POWERED LOUSPEAKERS

These lightweight & portable speakers feature Class "D" Fast Recovery™ amplification, integrated precision crossovers, and transducer time alignment. The TH-12A and TH-15A have a 12" and a 15" woofer respectively, 1" compression drivers, mic/line inputs, and 3-band EQ with a sweepable mid. Each works well as a monitor wedge, in addition to its normal pole-mountable orientation. The SRM1801 has an 18" woofer with 125Hz precision crossover, dual XLR inputs, stereo hi-pass and full-range outputs.

ITEM	DESCRIPTION	PRICE
TH-12A	12" powered pole-mountable loudspeaker, 400W, 25.5lbs	299.99
TH-15A	15" powered pole-mountable loudspeaker, 400W, 36lbs	349.99
SRM1801	18" powered subwoofer, 1000W, 73lbs	699.99

MACKIE SRM SERIES SPEAKERS

Both models feature XLR mic/line input, 24dB/ octave Linkwitz-Riley electronic crossover, electronic time correction, phase alignment and EQ for studio-quality sound. They are flyable, pole-mountable and also work as a floor wedge. The SRM450v2 additionally features a unique 3-piece wide-dispersion horn. The C200 and C300Z are passive versions of these models. The SRM1801 has an 18" woofer with 125Hz precision crossover, dual XLR inputs, stereo hi-pass and full-range outputs.



ITEM	DESCRIPTION	PRICE
SRM350-V2	2-way 10" biamped, 165W LF/30W HF, 26lbs	499.99
C200	Passive version of above	199.99
SRM450-V2-BLACK	2-way 12" biamped, 300W LF/100W HF, 40lbs	599.99
C300Z	Passive version of above	349.99
SRM1801	18" powered subwoofer, 1000W, 73lbs	699.99
SPM200	Locking speaker pole	39.99
GPA777	Rolling speaker bag for SRM450	199.99

MACKIE HD SERIES POWERED LOUSPEAKERS

The HD1221, HD1521, HD1531 feature Class "D" Fast Recovery™ amplification, precision crossovers, time correction and patented acoustic correction in order to provide high-definition clarity and superior performance. All 3 speakers feature custom EAW transducers and the HD1521 and HD1531 have an integrated user-adjustable 3-band EQ with sweepable mid. All 3 are flyable as well as pole-mountable and have a compact but rugged birch plywood cabinet. The HD1501 and HD1801 subwoofers also sport Class 'D' amplification and feature internal crossovers, tuning filters, phase alignment with loudspeakers, a high-pass output, and protection circuitry. The HDA is a 2-way 100"x20" constant curvature line array designed for installs or as a portable PA. Its features include Class "D" Fast Recovery™ amplification, a lightweight switch-mode power supply, custom EAW transducers, and hi-def audio processing featuring acoustic correction, transducer time alignment, phase correction, and precision 2-way crossover. The HDA has integrated fly points, can be attached to a flybar support, stacked on the ground or pole mounted on top of an HD1801 or tripod.



ITEM	DESCRIPTION	PRICE
HD1221	12" 2-way active speaker, 500W/LF, 100W/HF, 55Hz-20kHz, 90°H x 50°V, 133dB Max SPL, XLRf in, XLRM loop out, 50lbs	799.99
HD1521	15" 2-way active speaker, 700W/LF, 100W/HF, 50Hz-18kHz, 80°H x 50°V, 135dB Max SPL, XLRf in, XLRM loop out, 80lbs	999.99
HD1531	15" 3-way active speaker, 700W/LF, 100W/MF, 100W/HF, 50Hz-18kHz, 90°H x 40°V, 135dB Max SPL, XLRf in, XLRM loop out, 96lbs	1199.99
HD1501	15" powered subwoofer, 600W RMS, 1200W peak, 36Hz-145Hz, 126dB Max SPL, XLRf ins, balanced XLRM outs, 80lbs	849.99
HD1801	18" powered subwoofer, 800W RMS, 1600W peak, 35Hz-145Hz, 133dB Max SPL, XLRf ins, balanced XLRM outs, 106lbs	999.99
HDA	2-way line array, 12" woofer, 3" voice coil, 2x 1.7" comp. drivers, 500W/LF, 100W/HF, 52Hz-20kHz, 131dB Max SPL, 59lbs	1699.99
HDA-RIG-KIT-L	Replacement rigging kit L for HDA	75.00
HDA-RIG-KIT-R	Replacement rigging kit R for HDA	75.00
HDA-RIG-PIN-KIT	Replacement rigging pin and lanyard for HDA, HD1801	58.00
FB121	HDA flybar	1242.00
PA-A2	Eyebolt kit for HD Series speakers	47.99

NEXO

NEXO PS R2 SERIES LOUSPEAKERS SYSTEMS

Versatile, compact, full range loudspeakers created for a wide range of touring and installed sound reinforcement applications. Rotatable asymmetrical horns for PA, stage monitor and fill applications. Supported with a full range of mounting and flying accessories. Dedicated TD Controllers ensure linear and reliable operation. Also available with the horn located on the right or left (right listed below) and some models are available in a white painted finish (models listed below are black). Please call for more information.



ITEM	DESCRIPTION	PRICE
Speakers		
PS15U-R2	15" high power 2-way full range loudspeaker	CALL
PS15UR	Same as above, horn on right in monitor position	CALL
PS10U-R2	10" compact 2-way full range loudspeaker	CALL
PS10UR	Same as above, horn on right in monitor position	CALL
LS600-SUB	15" high power subwoofer for PS10-R2 loudspeakers	CALL
Signal Processors		
PS15U-TD-V3	Precision system controller for PS15U-R2	CALL
PS10U-TD-V3	Precision analog system controller for PS10U-R2/LS600-SUB	CALL
Accessories		
VNI-WS15	Wall mounted hanging bracket for PS15U-R2	CALL
VNI-WS10	Wall mounted hanging bracket for PS10U-R2	CALL
VNT-SSBRK10	Touring/production cradle for PS10U-R2	CALL
VNT-SSBRK15	Touring/production cradle for PS15U-R2	CALL
VNT-TCBRK	Truss clamp adaptor for various PS R2 accessories	CALL
VNT-XHBRK	Lifting ring for various PS R2 accessories	CALL
VNT-TTC	Adjustable tilt angle lifting bar for single PS R2 loudspeakers, requires VNT-XHBRK lifting ring or VNT-TCBRK truss clamp adaptor	CALL
VXT-PLSTD	Mounting accessory for PS R2 series; mast pole	CALL
VXT-UPSP10	Pole mount accessory for 2x PS10U-R2 on single pole	CALL



PEAVEY ELECTRONICS SPTM SERIES SPEAKERS This series features Peavey's Black Widow® loudspeakers, as well as field replaceable speaker baskets. All models also feature die-cast aluminum alloy frames, 4" edge-wound aluminum ribbon voice coils, vented magnet structure, spring-loaded terminals, and a 2" RX22™ titanium diaphragm compression driver coupled to a smooth, even response low distortion waveguide. The drivers also feature a phase correction system that provides smooth and extended high frequency response by preventing cancellations and interference in the horn.

ITEM	DESCRIPTION	PRICE
SP2	2-way speaker, 15" woofer, 1000W prgrm, 2000W peak, 54Hz-17kHz, Neutrik® Speakon® 4 pin jack and 2x 1/4" phone jacks	599.99
SP3	3-way speaker, 15" woofer, 6.5" mid-range, 1200W prgrm, 2400W peak, 54Hz-16kHz, 2x 1/4" phone jacks, 1x 4-pin twist lock connector, 1 Neutrik NL4 Speakon (bi-amp mode only)	799.99
SP4	Quasi-3-way speaker, 2x 15" woofers, 2000W prgrm, 4000W peak, 52Hz-17kHz, 2x 1/4" phone jacks, 1x 4-pin twist lock connector, bi-amp capability via internal wiring jumper	899.99
SP5	2-way speaker, 15" woofer, 800W prgrm, 1600W peak, 69Hz-17kHz, 2x 1/4" phone jacks, 1x 4-pin twist lock connector	499.99
SP6	Quasi 4-way speaker, 2x 15" woofers, 6.5" mid-range, 2000W prgrm, 4000W peak, 50Hz-16kHz, 2x 1/4" phone jacks, 1x 4-pin twist lock connector; bi-amp capability via internal wiring jumper	999.99
SP118	18" subwoofer, 1200W prgrm, 2400W peak, 49Hz-300Hz, 1x 4-pin Neutrik® Speakon® non-switching jack, 1x 4-pin Neutrik Speakon switching jack, 2x 1/4" jacks	599.99
SP218	2x 18" subwoofer, 2400W prgrm, 4800W peak, 51Hz-300Hz, 1x 4-pin Neutrik® Speakon® non-switching jack, 1x 4-pin Neutrik Speakon switching jack, 2x 1/4" jacks	899.99
SP-FH	18" subwoofer w/folded horn design, 1600W prgrm, 3200W peak, 30Hz-300Hz, 1x 4-pin Neutrik® jack, 2x 1/4" jacks, all inputs in parallel	799.99
SP12M	2-way floor monitor, 12" woofer, 1000W prgrm, 2000W peak, 108Hz-14kHz, 2x 1/4" phone jacks, 1x 4-pin twist lock connector	499.99
SP15M	2-way floor monitor, 15" woofer, 1000W prgrm, 2000W peak, 90Hz-14kHz, 2x 1/4" phone jacks, 1x 4-pin twist lock connector	599.99



IMPULSE® 12D

THE FUTURE OF POWERED ENCLOSURES IS NOW

RIBBON DRIVER

AN EXCLUSIVE DESIGN BASED ON
VERSARRAY™ TECHNOLOGY.

AWARD WINNING IPR™ POWER

1200 WATTS OF EFFICIENT CLASS D
POWER AT A LIGHTWEIGHT 39 LBS.

EXPANDABLE

EXPANSION MODULES INCLUDE
DELAY/TIME ADJUSTMENT, WIRELESS
I/O, ETHERNET I/O AND MORE.



DYNAQ™ AND I/O

TWO INDEPENDENTLY MIXABLE INPUT
CHANNELS WITH ADVANCED TONE
CONTROLS. PHOENIX CONNECTORS ON
BOTH INPUT AND OUTPUT.

FIELD-REPLACEABLE SPEAKER

A FIELD-REPLACEABLE, DUAL VOICE COIL
12" PREMIUM NEODYMIUM SPEAKER



ADDITIONAL FEATURES

- WOOFER SERVO TECHNOLOGY
- AUTO OFF CONTROL
- BASS ENHANCEMENT CIRCUIT
- EXCLUSIVE DDT™ ANTI-CLIPPING
- TWO INDEPENDENTLY MIXED CHANNELS
- POLE MOUNT OR TILT-BACK FOR MONITOR USE



INNOVATION. AMPLIFIED.™

FULL COMPASS

Call a Sales Pro Today! 800-356-5844 or Visit FullCompass.com

PRO AUDIO | VIDEO | AV | LIGHTING



PEAVEY ELECTRONICS PR SERIES SPEAKERS

Constructed with a lightweight molded polypropylene exterior, these speakers are ideal for live music or speech applications. All models feature woofers with 2.375" voice coils, 1.4" titanium compression driver, a 90°x40° constant directivity horn, top and bottom flying point inserts, and a molded-in pole mount. The non-powered versions can handle 400W program and 800W peak. Powered models feature DDT compression, are capable of up to 120dB SPL, balanced XLR-F/1/4" TRS mic/line combo jack, provides 150W RMS to the woofer, and 50W RMS to the tweeter. The PRSUB's woofer sports a 2.5" voice coil and has the same power rating as the unpowered speaker models.



ITEM	DESCRIPTION	PRICE
PR10	10" 2-way, passive, 400W, 54Hz-21kHz	149.99
PR12	12" 2-way, passive, 400W, 54Hz-21kHz	169.99
PR12D	12" 2-way, active, bi-amped, 200W, 54Hz-21kHz	399.99
PR15	15" 2-way, passive, 400W, 49Hz-21kHz	219.99
PR15D	15" 2-way, active, bi-amped, 200W, 49Hz-21kHz	479.99
PRSUB	15" passive subwoofer, 400W, 45Hz-3kHz (-10 dB, half space)	239.99

PEAVEY ELECTRONICS IMPULSE 12D POWERED ENCLOSURE

Features a true ribbon driver that provides 90° H x 30° V coverage, IPR™ power amp technology, and a 12" Black Widow® BWX-DVC Neo loudspeaker with dual voice coil, push-pull technology, and a neodymium magnet. The enclosure's Woofer Servo circuit monitors back-EMF and controls cone motion, making sure the cone's movement is similar to the power amp's driving signal. Also features two input channels with combo XLR-1/4", RCA and Phoenix connectors, mic/line source switches and gain controls, and one line output. The Impulse 12D's DynaQ™ section offers tone controls such as loudness boost, a music/speech switch for changing between EQs for each application, and contour. The rear panel also sports a bay for input function modules to be mounted.



ITEM	DESCRIPTION	PRICE
IMPULSE-12D	12" 2-way, active, 1200W	799.99

PEAVEY ELECTRONICS EU SERIES ACTIVE ENCLOSURES & PASSIVE FLOOR MONITOR

The EU112D & EU115D 2-way enclosures feature 1000W power amps for low frequencies, 200W power amps for high frequencies, Neo Black Widow® voice coil woofers (12" in 112D, 15" in 115D), 2" titanium compression drivers, asymmetrical horns that provide 100° H x 50° V coverage, and expansion ports for adding input/control modules. Both the 112 and the 115 feature 2 independent input channels with Neutrik® Speakon® 4-pin jacks, level control, and mic/line gain switch. Both models are also pole-mountable. The EU188D 18" subwoofer features a 1000W power amp, full power handling down to 34 Hz, a fourth order Linkwitz-Riley crossover with eight discrete low-frequency crossover points, a crossover in/out switch, a high-pass output, and a bass enhancement circuit. The EU112M floor monitor is a passive model that sports a 12" woofer, 2 NL-4 four-pin input jacks, an NL-4 bi-amp input jack, and a sloped rear-top panel. All models feature field-replaceable baskets.



ITEM	DESCRIPTION	PRICE
EU112D	1200W active enclosure w/12" woofer, 2" comp. driver	899.99
EU115D	1200W active enclosure w/15" woofer, 2" comp. driver	999.99
EU188D	1000W active 18" subwoofer	1049.99
EU112M	Floor monitor, passive, 12" woofer, 1000W program, 200W peak	599.99

PEAVEY ELECTRONICS PV® SERIES POWERED LOUDSPEAKERS

Both portable powered enclosures are rated at 400W program and feature DDT™ compression, RX™ 14 titanium compression drivers, 15" woofers with 2.375" voice coils, and LED signal present and DDT™ activation indicators. Also has combination 1/4"/XLR inputs, as well as XLR and 1/4" through outputs. Carpet covered with integrated pole mounts.



ITEM	DESCRIPTION	PRICE
PV115D	Powered loudspeaker w/(1) 15" woofer	299.99
PV215D	Powered loudspeaker w/(2) 15" woofers	499.99



QSC K SERIES POWERED LOUDSPEAKERS

These lightweight powered loudspeakers feature 1000 Class "D" power modules and fitted with identical woofers and 1.75" HF transducers (expect for the KSUB). Also features auto-standby mode, XLR & 1/4" TRS mic/line level ins, RCA phono-ins, direct-outs on each channel, a balanced out for daisy-chaining up to three sources and extensive DSP processing. EQ settings for both the high-freq. and low-freq. transducers are adjustable on each unit. LEDs can be set to show when the unit is on or when its clip limiter has been engaged. The extended bass LF setting allows for integration of an external subwoofer into the sound system. The KSUB includes a threaded pole-mount receptacle. The K8/1012 speakers feature fly-mount options as well as the Tilt-Direct™ pole cup mounting system for 7.5° downward tilt for better sound coverage. Multiple units can be daisy-chained for total gain control from a single remote pot. All units feature steel grills and are housed in an ABS enclosure, except for the KSUB in a birch housing.



ITEM	DESCRIPTION	PRICE
K8	8" LF, 1.75" HF transducers, 105° coverage pattern, 127dB max. SPL	649.99
K10	10" LF, 1.75" HF transducers, 90° coverage pattern, 129dB max. SPL	699.99
K12	12" LF, 1.75" HF transducers, 75° coverage pattern, 131dB max. SPL	799.99
KSUB	Dual 12" bandpass transducer, 130dB max. SPL, w/threaded speaker pole	1049.99

QSC KW SERIES LOUDSPEAKERS

Designed to provide the performance of QSC's K Series in a lightweight birch enclosure. Features 1000W Class "D" power modules (2 x 500W continuous) on all of its models. The series' Directivity Matched Transition™ technology offers matched LF & HF coverage, eliminating hot or dead frequency zones. The series also offers GuardRail™ protection from clipping and excursion limiting. The 122 and 152 offer tilting pole mount systems, while the 153 is pole-mountable, but cannot tilt. All models feature a four-position mic/line gain switch, mic/line level XLR/1/4" TRS inputs, and RCA phono inputs (except on the KW181). Each channel offers separate direct outs. Up to three audio sources can be internally mixed and summed to a balanced out as well. Preset EQ setting switches are featured on-board.



ITEM	DESCRIPTION	PRICE
KW122	1000W 2-way active loudspeaker, w/12" LF driver, 1.75" comp. driver	1099.00
KW152	1000W 2-way active loudspeaker, w/15" LF driver, 1.75" comp. driver	1199.00
KW153	1000W 3-way active loudspeaker, w/12" LF driver, 6.5" midrange, 1.75" comp. driver	1299.00
KW181	1000W 18" active subwoofer	1399.00
KW-M10-KIT	Eye bolt kit for KW122, 152, 153	34.72
KW-SUS-KIT-122	Suspension kit for KW122, 152, 153	59.70



SAMSON RESOUND HD PASSIVE PA ENCLOSURES

This series offers a variety of configurations of loudspeakers and floor monitors. Each speaker includes a 1.5" titanium compression driver for increased performance on the top end, 1" throat horn, dual-port tuned enclosures, and dual 1/4" and Speakon connections. Perfect for bands, houses of worship, performance venues, and more.



ITEM	DESCRIPTION	PRICE
RESOUND-RS10HD	10" passive 2-way speaker, 300W @ 8ohms	169.00
RESOUND-RS12HD	12" passive 2-way speaker, 500W @ 8ohms	199.00
RESOUND-RS15HD	15" passive 2-way speaker, 600W @ 8ohms	249.00
RESOUND-RS215HD	Dual 15" passive 2-way speaker, 1200W @ 4ohms	349.00
RESOUND-RS10MHD	10" passive 2-way wedge floor monitor, 300W @ 8ohms	169.00
RESOUND-RS12MHD	12" passive 2-way wedge floor monitor, 500W @ 8ohms	199.00
RESOUND-RS15MHD	15" passive 2-way wedge floor monitor, 600W @ 8ohms	249.00

Tenemos ventas y servicio en Español. Expertos que hablan Español disponibles en x1178 y x1164.



- AUDIO
- COMPUTER AV
- VIDEO
- LIGHTS
- MUSIC
- ACCESSORIES



RENKUS-HEINZ CFX SERIES Ideal for portable or permanent install applications. All models (except CFX61/CFX121M) feature tripod sockets for pole-mounting and 6 UMH attachment points to fly the cabinets using eyebolts. Speakers feature unique Complex Conic horns, designed on the spherical expansion of the acoustic pressure wave. The Complex Conic flare changes smoothly from a narrow diffraction slot, through an oval expansion, to a circular mouth producing smooth pattern control. Passive models are shown below, but may be upgraded to active models with the purchase of an optional Class "D" amp, easily installed in the field. Or upgrade with RHAON empowered amps, PFI-200R or PFI-500R. The resulting RHAON (Renkus-Heinz Audio Operations Network) empowered versions allow you to use Cobranet based digital audio distribution and have control over your system via free control software on any Windows based computer, using standard ethernet hardware and cabling. (To order either version of the amp modules factory-installed, call for part number and price.) All CFX passive models are provided with both looping 4-pin Neutrik Speakon type connectors and screw-type terminal strips. Models available in black or white. Call for various mounting options.




ITEM	DESCRIPTION	PRICE
CFX616.5" 2-way, passive, 150°x60°, rotatable horn, 80Hz-20kHz, 120W.....	442.00
CFX818" 2-way, passive, 150°x60°, rotatable horn, 70Hz-20kHz, 200W.....	526.00
CFX12112" 2-way, passive, 90°x60°, rotatable horn, 70Hz-18kHz, 500W.....	750.00
CFX15115" 2-way, passive, 90°x40°, rotatable horn, 60Hz-18kHz, 700W.....	900.00
CFX121M12" 2-way floor monitor, passive, 90°x60°, rotatable horn, 70Hz-18kHz, 500W.....	750.00
CFX18S18" subwoofer, passive, includes hi-pass filter, 900W, black finish only.....	900.00

Amplifier Options for CFX/CFX Series

PFI-200200W RMS Class "D" amp/processor for all CFX models.....	460.00
PFI-200RRHAON empowered PFI-200 200W Class D amplifier for all CFX models.....	1126.00
PFI-500500W RMS Class "D" amp/processor used to turn CFX121, CFX151, CFX18S models into self-powered models.....	900.00
PFI-500RRHAON empowered PFI-500 500W Class "D" amplifier used to turn CFX121, CFX151, CFX18S models into self-powered models.....	1568.00

RENKUS-HEINZ SYGMA SERIES INSTALL LOUDSPEAKER SYSTEMS

This series of install speakers is great for side- and front-fill applications, foreground music systems in retail stores or offices, or multi-channel playback systems in clubs. They incorporate European transducers and the same Complex Conic Horn technology found in the Renkus Heinz CFX Series. Passive models are shown below, but may be upgraded (with the exception of the SGX41) to active models with the purchase of optional Class "D" amplifiers, PFI-200 or PFI-500, easily installed in the field. Or choose the PFI-200R or PFI-500R amplifiers to add Ethernet audio networking. These RHAON (Renkus-Heinz Audio Operations Network) empowered versions allow you to use Cobranet based digital audio distribution and have control over your system via free control software on any Windows-based computer, using standard Ethernet hardware and cabling. (To order either version of the amps factory-installed, call for model numbers and pricing.) All SGX passive models have both looping 4-pin Neutrik Speakon type connectors and screw-type terminal strips. All models are available in black or white. Call for various mounting options.



ITEM	DESCRIPTION	PRICE
SGX414" coaxial passive, 150°x150°, 100Hz-20kHz, 120W@8ohms.....	300.00
SGX42Dual-4", "stair-step" speaker, passive, 300Hz-20kHz, 240W@16ohms.....	618.00
SGX616.5" 2-way, passive, 150°x60°, rotatable horn, 80Hz-20kHz, 120W@8ohms.....	600.00
SGX818" 2-way, passive, 90°x60°, rotatable horn, 80Hz-20kHz, 200W@8ohms.....	750.00
SGX12112" 2-way, passive, 90°x60°, rotatable horn, 70Hz-18kHz, 500W@4ohms.....	1218.00
SGX15115" 2-way, passive, 90°x40°, rotatable horn, 60Hz-18kHz, 500W@4ohms.....	1484.00
SGX12S12" subwoofer, passive, w/low pass filter, 65Hz-120Hz, 800W@4ohms.....	1160.00

Options for Sygma Series (partial listing, call for mounting options)

PFI-200200W RMS Class "D" amp/processor for all SGX models.....	460.00
PFI-200RSame as above but RHAON empowered.....	1126.00
PFI-500500W RMS Class "D" amp/processor to turn SGX121/SGX151/SGX12S into self-powered speakers.....	900.00
PFI-500RSame as above but RHAON empowered.....	1568.00
TR100W200W 70/100V transformer kit with 200, 162, 100, 80, 50, 32, 18, 8, & 4W taps, not installed.....	134.00
TR400W400W 70/100V transformer kit with 400, 200, 162, 100, 80, 50, 32, 18, 8, & 4W taps, not installed.....	150.00
WR61-RKHWeather-resistant option for SGX61 cabinet.....	160.00
WR81-RKHWeather-resistant option for SGX81 cabinet.....	192.00
WR121-RKHWeather-resistant option for SGX121 cabinet.....	410.00
WR151-RKHWeather-resistant option for SGX151 cabinet.....	450.00
WR12S-RKHWeather-resistant option for SGX12S cabinet.....	410.00
PF-WR-KITWeather-resistant option for all PF Series amps.....	332.00



RCF ART 700 SERIES All 700 series models are equipped with a 750W digital power amplifier (500W for the woofers, and 250W for the compression drivers), and offer both XLR/1/4" jack (combo) balanced inputs, XLR output link, volume and a switchable EQ mode (flat/boost). The amp features a solid mechanical aluminum structure which stabilizes the amp during transportation and assists in heat dissipation. All cabinets are made from a polypropylene composite material designed to dampen down vibrations even at maximum volume. Resized reflex porting offers better efficiency. All models have neodymium high power woofers of various sizes listed below. The 710A, 712A, and 715A models feature 1" titanium dome, neodymium high-frequency drivers, while the 722A, and 725A models feature 2" titanium dome, neodymium high-frequency drivers.



ITEM	DESCRIPTION	PRICE
ART-710A10" 2-way, active, 500W/LF, 250W/HF, 90°x70°, 129dB, 50Hz-20kHz.....	1100.00
ART-712A12" 2-way, active, 500W/LF, 250W/HF, 90°x60°, 129dB, 50Hz-20kHz.....	1230.00
ART-715A15" 2-way, active, 500W/LF, 250W/HF, 90°x60°, 30dB, 50Hz-20kHz.....	1400.00
ART-722A12" 2-way, active, 500W/LF, 250W/HF, 90°x60°, 130dB, 45Hz-20kHz.....	1529.00
ART-725A15" 2-way, active, 500W/LF, 250W/HF, 90°x60°, 131dB, 45Hz-20kHz.....	1741.00
ART-902AS12" active subwoofer, 1000W, Xover 80Hz-120Hz, 130dB, 45-120Hz.....	1495.00
ART-905AS15" active subwoofer, 1000W, Xover 80Hz-120Hz, 131dB, 40Hz-120Hz.....	1615.00

Technomad

TECHNOMAD NOHO LOUDSPEAKER The military-specification Noho offers a remarkable combination of high-output, wide-dispersion, long-throw, and excellent fidelity. An ideal choice for sports facilities, touring sound, military applications, or anywhere you need no-compromises outdoor audio. The Noho features a 1" HF compression driver, on a 120° horn for wide coverage, remarkable throw, and an open, natural sound. A custom-engineered 12" LF driver delivers astonishing bass. A 3-layer stainless WeatherTech™ grill, self-draining cabinet design, proprietary anti-fungal treatments, and fuse protection circuitry make the Noho virtually "unkillable". Two models are offered: the Install Model for indoor or outdoor installations, and the Tour Model, which comes with recessed folding handles and a gasketed clamp-on lid that converts the Noho into an indestructible ATA-III flight case for secure transport. 14 optional colors by special order (upcharge applies). Priced each.



ITEM	DESCRIPTION	PRICE
NOHO-C-INSTALL12" 2-way speaker, 275W, Neutrik NL4.....	CALL
NOHO-C-TOUR12" 2-way speaker, 275W, Neutrik NL4.....	CALL

Turbosound

TURBOSOUND MILAN M15 ACTIVE LOUDSPEAKER

Features a 450w Class D amp & integrated 2-channel mixer with mic & line inputs, and a symmetrical trapezoidal shape with 43° wedge angle. The lockable jack/XLR inputs will accept instruments, mics, & MP3 players. The internal DSO with frequency-dependent limiting delivers max audio quality & protects the drive units from damage. A mix-out function allows daisy-chaining, & a converging elliptical waveguide helps to distribute sound more evenly over a wider listening area. SPL is 125dB continuous & 131dB max.



ITEM	DESCRIPTION	PRICE
MILAN-M1515" LF driver, 1" HF compression driver, 450W, 90°h x 60°v dispersion.....	999.00

YAMAHA

YAMAHA MSR SERIES POWERED SPEAKERS

The MSR400 powered speaker can be used alone or in combination with the MSR800W powered subwoofer to assemble sound reinforcement systems from modest to massive. They look great, too. So good that they can be used as-is in many permanent installations without requiring any cosmetic cover-up. And, of course, they're more than rugged enough for demanding tour applications as well. The MSR100 can fill many sound reinforcement and stage monitor needs in one inexpensive, lightweight package.



ITEM	DESCRIPTION	PRICE
MSR1008" 2-way active speaker, 100W/6ohms.....	CALL
MSR40012" bi-amped 2-way speaker, 225W LF/75W HF.....	CALL
MSR800W15" active subwoofer, 500W/8ohms.....	CALL





YAMAHA CLUB-V PASSIVE LOUDSPEAKERS A best buy in price and performance. Great sounding speakers available in carpet covered, elastomeric spray finished and flyable models. The portable models have heavy-duty handles, pole socket and steel grill. All models are 2-way and powered by true compression drivers. Custom Eminence drivers are used, the horns have a 90x40 constant directivity pattern. Connectors are Neutrik Speakon and Switchcraft 1/4" with two of each connector for easy daisy chaining.

ITEM	DESCRIPTION	PRICE
S Series: road-worthy, rugged carpet covered models		
S112V	12" 2-way, 350W/8ohms, 60Hz-16kHz	CALL
S115V	15" 2-way, 500W/8ohms, 55Hz-16kHz	CALL
S215V	Dual-15" 2-way, 1000W/8ohms, 42Hz-16kHz	CALL
SM10V	10" floor monitor, 250W/8ohms, 70Hz-20kHz	CALL
SM12V	12" floor monitor, 350W/8ohms, 60Hz-16kHz	CALL
SM15V	15" floor monitor, 500W/8ohms, 55Hz-16kHz	CALL
SW118V	18" subwoofer, 600W/8ohms, 30Hz-2kHz	CALL
SW218V	Dual-18" subwoofer, 1220W/8ohms, 30Hz-2kHz	CALL
C Series: durable spray finished models with foamed steel grilles		
C112V	12" 2-way, 350W/8ohms, 60Hz-16kHz	CALL
C115V	15" 2-way, 500W/8ohms, 55Hz-16kHz	CALL
C215V	Dual-15" 2-way, 1000W/8ohms, 42Hz-16kHz	CALL
CM10V	10" floor monitor, 250W/8ohms, 70Hz-20kHz	CALL
CM12V	12" floor monitor, 350W/8ohms, 60Hz-16kHz	CALL
CM15V	15" floor monitor, 500W/8ohms, 55Hz-16kHz	CALL
CW118V	18" subwoofer, 600W/8ohms, 30Hz-2kHz	CALL
CW218V	Dual-18" subwoofer, 1220W/8ohms, 30Hz-2kHz	CALL
Flyable Models: ideal for installations		
C112VA	12" 2-way, 350W/8ohms, 60Hz-16kHz	CALL
C115VA	15" 2-way, 500W/8ohms, 55Hz-16kHz	CALL

YAMAHA DSR SERIES ACTIVE LOUDSPEAKERS

These include a combination of ultra-sophisticated digital sound processing and the latest acoustic technologies, including D-CONTOUR multi-band dynamic processing for consistent clarity at both high and low output levels. Each incorporates high power Class "D" amplifiers a/PFC switching mode power supply, and has 3-way fail-safe DSP protection. Advanced digital sound processing includes FIR-X tuning™ for the smoothest possible crossover transitions and high power DSP, plus 24bit discrete AD & DA converters for maximum dynamic range. Exclusive LTBD (Long Throw, Broad Dispersion) Constant Directivity Waveguide Horn provides 90° horizontal x 60° vertical coverage with full-frequency sound projected all the way to the edges of the coverage area (except DSR118W). The DSR112 and DSR115 are stand and pole mountable with 35mm pole sockets & have M10 rigging points for suspended installation. DSR112 can be tilted for use as a floor monitor and additional monitors can be daisy-chained via the XLR THRU jack on the rear panel. Models feature XLR and 1/4" TRS inputs (DSR118W has XLR only) that accept both mic and line level input. Easy to handle series capable of 1300W power output (DSR118W is 800W).

ITEM	DESCRIPTION	PRICE
DSR112	12" 2-way, biamp powered speaker, 60Hz-18kHz (-3db), 134dB SPL, 47lbs	CALL
DSR115	15" 2-way, biamp powered speaker, 55Hz-18kHz (-3db), 136dB SPL, 62lbs	CALL
DSR215	Dual 15" 2-way, biamp powered speaker, 55Hz-18kHz (-3db), 138dB SPL, 110lbs	CALL
DSR118W	18" powered speaker, 50Hz-110kHz (-3db), 132dB SPL, 93lbs	CALL



YAMAHA BR-SERIES PASSIVE SPEAKERS

BR models are designed to fit the budgets of performing musicians, small churches, and schools. Each model's large steel handles, corner protectors, and built-in pole sockets, assure both durability and flexibility. High-frequency response is also enhanced with a new titanium HF driver and 90° by 40° non-resonant horn. All BR-Series models are covered by a 3-year warranty. With integral protection circuitry built into the passive crossover, you can expect a long life of high output and minimal distortion. Speakers feature dual phone jack inputs.



ITEM	DESCRIPTION	PRICE
BR10	10" 2-way speaker, 250W/8ohms, 65Hz-20kHz	CALL
BR12	12" 2-way speaker, 300W/8ohms, 65Hz-20kHz	CALL
BR15	15" 2-way speaker 400W/8ohms, 60Hz-20kHz	CALL
BR12M	12" floor monitor, 250W/8ohms	CALL
BR15M	15" floor monitor, 400W/8ohms	CALL



YORKVILLE ELITE SERIES LOUDSPEAKERS

Features a complete range of flexible and practical FOH/monitor-combo enclosures. Can be used as an array, on tripod or used as a wedge monitor. Revoiced and refit, several models in the series also feature rotatable HF horns that allow reconfiguration of the HF section from 80°x50° to 50°x80. Small, loud and easy to use. Most new elite series enclosures are made of 15mm Baltic Birch and feature standard flying hardware. Many models are also available in black "Ultrathane" painted versions with additional fly points for touring and/or fixed installation applications. Also features distinctive curved anti-resonant grilles, inset handles & jack plates, all plywood construction with internal bracing, passive crossover networks with CTL, ATP or PTC high frequency driver protection, Speakon™ and 1/4" connectors, stand adaptors and Yorkville's two-year (even if you break it!) transferable warranty. Powered versions shown, passive models are also available in this series.



ITEM	DESCRIPTION	PRICE
Powered Full Range Loudspeakers		
E10P	350W, 8ohms, 10" woofer, 1" HF driver on 100°x30° horn, flying hardware, 300/50W bi-amped, built-in mixer, mic/line inputs	880.00
E10PB	Ultrathane black painted version of E10P	1000.00
EF500P	800W, 15" woofer, 2" HF driver on 60°x40° horn, 650/150W bi-amped	1480.00
EF500PB	Ultrathane black painted version of above - 15mm birch enclosure	1560.00
Powered Subwoofers		
LS200P	200W, 10" subwoofer, ultra-low profile mini subwoofer, level control	600.00
LS720P	720W, 15" subwoofer, mini subwoofer, level control, HF roll-off, variable LF boost frequency speaker or line levels inputs	920.00
LS701P	700W, two 10" subwoofers, low profile mini subwoofer w/internal x-over/processor, level control	779.91
LS701PB	Ultrathane black painted version of above	892.36
LS801P	1500W, 18" subwoofer, dual-tuned subwoofer enclosure, level control, HF roll-off, speaker or line levels inputs	1440.00
LS801PB	Ultrathane black painted version of above	1639.20

YORKVILLE YX SERIES LOUDSPEAKERS

Offers rugged 5/8" plywood cabinet construction, all metal bar handles, metal input plate, integrated speaker mounts and a custom punched, perforated metal grille to protect the speaker components. A modified trapezoidal shape (YX10, YX12, YX15) ensures the YX Series can function equally as well as a front-of-house or monitor speaker. Injection molded 90°x30° horns with 1" throat and 1.4" diaphragm neodymium compression drivers are used on all full-range cabinets in the line. Yorkville's dual-bulb CTL™ (current-to-light) protection system protects each horn driver's aluminum diaphragm ensuring unmatched reliability in the field. Road-ready with easy-to-clean, durable black carpet covering. All speakers have two 1/4" and 2 Speakon inputs (YX15P has mic/line inputs).



ITEM	DESCRIPTION	PRICE
Passive Full Range Models		
YX10	10", 150W, 100x25 horn, 1" Neodymium HF driver	200.00
YX12	12", 200W, 90x30 horn, 1" Neodymium HF driver	264.00
YX15	15", 300W, 90x30 horn, 1" Neodymium HF driver	320.00
YX150	15", 400W, 90x30 horn, 2" Neodymium HF driver	456.00
YX215	2x15", 600W, 90x30 horn, 1" Neodymium HF driver	560.00
Subwoofer		
YX18S	18", 400W, 6ohms, rectangular cabinet	399.00
Active Full Range Models		
YX15P	15", 180/20W bi-amped, 100x25 horn, 1" neodymium HF driver, built-in mixer, mic/line inputs	480.00

We service many of the major brands that we carry. Call our Authorized Repair Department at ext. 1172



- AUDIO
- COMPUTER AV
- VIDEO
- LIGHTS
- MUSIC
- ACCESSORIES