SOUND REINFORCEMENT SPEAKERS

NEW

°

MUSIC

MACKIE **MACKIE THUMP SERIES**

POWERED LOUDSPEAK-ERS These lightweight & portable speakers feature Class "D" Fast Recovery™ amplification, integrated precision crossovers, and



transducer time alignment. The TH-12A and TH-15A have a 12" and a 15" woofer respectively, 1" compression drivers, mic/line inputs, and 3-band EQ with a sweepable mid. Each works well as a monitor wedge, in addition to its normal pole-mounted orientation. The SRM1801 has an 18" woofer with 125Hz precision crossover, dual XLR inputs, stereo hi-pass and full-range outputs.

inputs, stereo	in pass and run runge outputs.	
ITEM	DESCRIPTION	PRICE
TH-12A		299.99
TH-15A		349.99
SRM1801		699.99
GPA-715		139.99
GPA-712SM	Rolling speaker bag for 12" speakers	119.99

MACKIE SRM SERIES SPEAKERS Both models feature XLR mic/line input, 24dB/octave Linkwitz-Riley electronic crossover, electronic time correction, phase alignment and EQ for studio-quality sound. They are flyable, polemountable and also work as a floor wedge. The SRM450v2 additionally features a unique 3-piece wide-dispersion horn. The C200 and



C300Z are passive versions of these models. The SRM1801 has an 18" woofer with 125Hz precision crossover, dual XLR inputs, stereo hi-pass and full-range outputs.

• •		
ITEM	DESCRIPTION	PRICE
SRM350-V2	2-way 10" biamped, 165W LF/30W HF, 26lbs	
C200	Passive version of above	
SRM450-V2-BLACK	2-way 12" biamped, 300W LF/100W HF, 40lbs	
C300Z	Passive version of above	
SRM1801	18" powered subwoofer, 1000W, 73lbs	
SPM200	Locking speaker pole	
	Rolling speaker bag for SRM450	



MACKIE HD SERIES POWERED LOUDSPEAKERS The HD1221, HD1521, HD1531 feature Class 'D' Fast Recovery™ amplification, precision crossovers, time correction and patented acoustic correction in order to provide high-definition clarity and superior performance. All 3 speakers feature custom EAW transducers and the HD1521 and HD1531 have an integrated user-adjustable 3-band EQ with sweepable mid. All 3 are flyable as well as pole-mountable and have a compact but rugged birch plywood cabinet. The HD1501 and HD1801 subwoofers also have Class 'D' amplification and feature internal crossovers, tuning filters, phase alignment with loudspeakers, a hi-pass output, and protection circuitry.

ITEM	DESCRIPTION	PRICE
HD1221	12" 2-way active speaker, 500W/LF, 100W/HF,	
	55Hz-20kHz, 90°H x 50V°, 133dB Max SPL, XLRF in,	
	XLRM loop out, 50lbs	799.99
HD1521	15" 2-way active speaker, 700W/LF, 100W/HF,	
	50Hz-18kHz, 80°H x 50V°, 135dB Max SPL, XLRF in,	
	XLRM loop out, 80lbs	999.99
HD1531	15" 3-way active speaker, 700W/LF, 100W/MF, 100W/HF,	
	50Hz-18kHz, 90°H x 40V°, 135dB Max SPL, XLRF in,	
	XLRM loop out, 96lbs	1249.99
HD1501	15" powered subwoofer, 600W RMS, 1200W peak, 36Hz-145Hz,	
	126dB Max SPL, XLRF ins, balanced XLRM outs, 80lbs	899.99
HD1801	18" powered subwoofer, 800W RMS, 1600W peak, 35Hz-145Hz,	
	133dB Max SPL, XLRF ins, balanced XLRM outs, 106lbs	999.99
	Flybar for HDA & HD1801	
PA-A2	Eyebolt kit for HD Series speakers	47.99



This series features Peavey's Black Widow® loudspeakers and field-replaceable speaker baskets, as well as a durable HammerHead exterior coating



PRICE
699.99
859.99
959.99
599.99
099.99
659.99
999.99
899.00
499.99
599.99

PEAVEY PVX SERIES SPEAKERS

Constructed with a lightweight molded polypropylene exterior, these speakers are ideal for live music or speech applications. All models feature woofers with 2-3/8" voice coils and a 1.4" titanium compression driver coupled to a constant directivity horn. Multiple cabinet fly points, angled sides for use as a floor monitor, and an integrated pole mount allow for flexible speaker placement. Active models feature DDT



compression, module bay for use of expansion modules, balanced XLR / 1/4" TRS combo input, and XLR /1/4" through outputs. Passive versions can handle 400W program and 800W peak, and utilize parallel 1/4" and 4-pin twist-lock inputs.

ITEM	DESCRIPTION	PRICE
PVXP12		
PVX12	As above, but passive	
	As above, but passive	

PEAVEY PR SERIES SPEAKERS

Constructed with a lightweight molded polypropylene exterior, these speakers are ideal for live music or speech applications. All models feature woofers with 2.375" voice coils, 1.4" titanium compres-



and bottom flying point inserts, and a molded-in pole mount. The non-powered versions can handle 400W program and 800W peak. Powered models feature DDT compression, are capable of up to 120dB SPL, balanced XLR-F / 1/4" TRS mic/line combo jack, provides 150W RMS to the woofer, and 50W RMS to the tweeter. The PRSUB's woofer sports a 2.5" voice coil and has the same power rating as the unpowered speaker models.

ITEM	DESCRIPTION	PRICE
PR10	. 10" 2-way, passive, 400W, 54Hz-21kHz	159.99
PR12	. 12" 2-way, passive, 400W, 54Hz-21kHz	189.99
	. 12" 2-way, active, bi-amped, 200W, 54Hz-21kHz	
PR15	. 15" 2-way, passive, 400W, 49Hz-21kHz	229.99
PR15D	. 15" 2-way, active, bi-amped, 200W, 49Hz-21kHz	399.00
PRSUB	. 15" passive subwoofer, 400W, 45Hz-3kHz (-10 dB, half space)	239.99



Visit fullcompass.com today!

For expert advice - call: 800-356-5844 M-F: 9:00-5:30 Central



SOUND REINFORCEMENT SPEAKERS



QSC K SERIES POWERED LOUDSPEAKERS

These lightweight powered loudspeakers feature 1000 Class "D" power modules and are fitted with identical 1.75" HF transducers (expect for the KSUB). Also features auto-standby mode, XLR & 1/4" TRS mic/line level ins, RCA phono-ins, direct-outs on each channel, a balanced out for daisy-chaining up to three sources and extensive DSP processing. EQ settings for both the high-freq. and low-freq. transducers are adjustable on each unit. LEDs can be set to show when the unit is on or when its clip limiter has been engaged. The extended bass LF setting allows for integration of an external subwoofer into the sound system. The KSUB includes a threaded pole-mount receptacle. The K8/10/12 speakers feature fly-mount options as well as the Tilt-Direct[™] pole cup mounting system for 7.5° downward tilt for better sound coverage. Multiple units can be daisy-chained for total gain control from a single remote pot. All units feature steel grills and are housed in an ABS enclosure, except for the KSUB in a birch housing.

encopt for t	ne ne e e e e e e e e e e e e e e e e e	
ITEM	DESCRIPTION	PRICE
K8	8" LF, 1.75" HF transducers, 105° coverage pattern, 127dB m	ax. SPL 699.99
K10	10" LF, 1.75" HF transducers, 90° coverage pattern, 129dB m	ax. SPL 749.99
K12	12" LF, 1.75" HF transducers, 75° coverage pattern, 131dB m	ax. SPL 849.99
KSUB	Dual 12" bandpass transducer, 130dB max. SPL,	
	w/threaded speaker pole	
GPA-712SM	Rolling speaker bag for K10/K12	

PEAVEY **PV®** SERIES **POWERED LOUDSPEAKERS** Both portable powered enclo-

sures are rated at 400W program and feature DDTTM compression, RXTM 14 titanium compression drivers, 15" woofers with 2.375" voice coils,



and LED signal present and $\text{DDT}^{\textsc{tm}}$ activation indicators. Also has combination 1/4"/XLR inputs, as well as XLR and 1/4" through outputs. Carpet covered with integrated pole mounts.

DESCRIPTION

PV115D Powered loudspeaker w/(1) 15" woofer PV215D ... Powered loudspeaker w/(2) 15" woofers.



ITEM

RCF ART 700 SERIES All 700 series models are equipped with a 750W digital power amplifier (500W for the woofers, and 250W for the

compression drivers), and offer XLR/1/4" jack (combo) balanced inputs, XLR output link, volume and a switchable EQ mode (flat/boost). The amp features a solid mechanical aluminum structure,



PRICE

299.99

499.99

dissipation. All cabinets are made from a polypropylene composite material designed to dampen vibrations even at maximum volume. Resized reflex porting offers better efficiency. All models have neodymium high power woofers of various sizes listed below. The 710A, 712A and 715A models feature 1" titanium dome, neodymium high-frequency drivers, while the 722A and 725A models feature 2" titanium dome, neodymium high-frequency drivers.

ITEM DESCRIPTION PRI	CE
ART-710A 10" 2-way, active, 500W/LF, 250W/HF, 90°x70°, 129dB, 50Hz-20kHz 1256.	.00
ART-712A12" 2-way, active, 500W/LF, 250W/HF, 90°x60°, 129dB, 50Hz-20kHz 1414.	.00
ART-715A 15" 2-way, active, 500W/LF, 250W/HF, 90°x60°, 30dB, 50Hz-20kHz 1571.	.00
ART-722A12" 2-way, active, 500W/LF, 250W/HF, 90°x60°, 130dB, 45Hz-20kHz 1728.	.00
ART-725A 15" 2-way, active, 500W/LF, 250W/HF, 90°x60°, 131dB, 45Hz-20kHz 2043.	
ART-902AS12" active subwoofer, 1000W, Xover 80Hz-120Hz, 130dB, 45-120Hz 1728.	
ART-905AS15" active subwoofer, 1000W, Xover 80Hz-120Hz, 131dB, 40Hz-120Hz 1885.	
SUB-70515" active subwoofer, 700W, Xover 80Hz-120Hz, 130dB, 45Hz-120Hz 1256.	.00
SUB-71818" active subwoofer, 700W, Xover 80Hz-120Hz, 132dB, 40Hz-120Hz 1807.	.00



QSC KW SERIES LOUDSPEAKERS

Designed to provide the performance of QSC's K Series in a lightweight birch enclosure. Features 1000W Class "D" power modules (2 x 500W continuous) on all of its models. The series' Directivity Matched Transition™ technology offers matched LF & HF coverage, eliminating hot or dead frequency zones. The series also offers GuardRail[™] protection from clipping and excursion limiting. The 122 and 152 bear tilting pole mount systems, while the 153 is pole-mountable, but cannot tilt. All models feature a four-position mic/line gain switch, mic/line level XLR/1/4" TRS inputs, and RCA phono inputs (except on the KW181). Each channel offers separate direct outs. Up to three audio sources can be internally mixed and summed to a balanced out as well. Preset EQ setting switches are featured on-board.

ITEM	DESCRIPTION	PRICE
KW122	1000W 2-way active loudspeaker,	
	w/12" LF driver, 1.75" comp. driver	
KW152	1000W 2-way active loudspeaker,	
	w/15" LF driver, 1.75" comp. driver	
KW153	1000W 3-way active loudspeaker, w/12" LF driver,	
	6.5" midrange, 1.75" comp. driver	
KW181	1000W 18" active subwoofer	
KW-M10-KIT	Eye bolt kit for KW122, 152, 153	
KW-SUS-KIT-122	Suspension kit for KW122, 152, 153	
	· , ,	

Roland[®] **ROLAND CM-110 & CM-220 CUBE MONITOR SYSTEM** The robust CM-110 & CM-220 combine two satellite speakers and a subwoofer to create full-range, high-quality monitoring systems. 3 input channels (Instrument, Line, Digital) with



discrete volume knobs provide flexible connections to your gear via digital, 1/4" TRS, or RCA connections. Dedicated controls adjust subwoofer volume/phase, while 2-band EQ and Master volume allow overall shaping. A speaker protection circuit protects against wide dynamic range or continuous high levels, while switchable Auto-off prevents unnecessary power consumption. CM-110 is a 100W package (25W sat., 50W sub) and CM-220 is 200W (50W sat., 100W sub).

ITEM	DESCRIPTION	PRICE
CM110		499.00
CM220		
STCMS1	Monitor speaker stand	

Technomad LOUDSPEAKER The military-TECHNOMAD

specification Noho offers a remarkable combination of high-output, wide-dispersion, long-throw, and excellent fidelity. An ideal choice for sports facilities, touring sound, military applications, or anywhere you need no-compromises outdoor audio. The Noho features a 1" HF compression driver, on a 120° horn for wide coverage, remarkable throw, and an open, natural sound. A custom-engineered 12" LF driver delivers astonishing bass. A



3-layer stainless WeatherTech[™] grill, self-draining cabinet design, proprietary antifungal treatments, and fuse protection circuitry make the Noho virtually "unkillable". Two models are offered: the Install Model for indoor or outdoor installations; and the Tour Model which comes with recessed folding handles and a gasketed clamp-on lid that converts the Noho into an indestructible ATA-III flight case for secure transport. 14 optional colors by special order (upcharge applies). Priced each.

ITEM	DESCRIPTION	PRICE
NOHO-C-INSTALL	. 12" 2-way speaker, 275W, Neutrik NL4	CALL
NOHO-C-TOUR	. 12" 2-way speaker, 275W, Neutrik NL4	CALL



PRICES SUBJECT TO CHANGE WITHOUT NOTICE. Call today or visit us online!

Welcome to the HOUSE OF K



Enter a place of infinite possibilities. In this house, over 40 years of amplifier, loudspeaker and DSP experience born under a single roof run through the veins of every K Family product. Incredibly intelligent and versatile, all 10 models work together in countless ways to solve your most difficult audio challenges. And just like any good home, the House of K provides genuine comfort, delivering service you can depend on today, tomorrow and for years to come.

Whether for Rental Sound, Installed Sound or Portable PA, the House of K is wherever you make it. Contact Full Compass and build your own house today.



fullcompass.com 800-356-5844



© 2012 QSC Audio Products, LLC: All rights reserved. QSC and the QSC logo are registered trademarks of QSC Audio Products, LLC in the U.S. Patent and Trademark Office and other countries.

ACCESSORIES

rh RENKUS-HEINZ

SOUND REINFORCEMENT SPEAKERS

RENKUS-HEINZ CFX SERIES Ideal for portable or permanent install applications. All models (except CFX61/CFX121M) feature tripod sockets for pole-mounting and 6 UMH attachment points to fly the cabinets using eyebolts. Speakers feature unique Complex Conic horns, designed on the



spherical expansion of the acoustic pressure wave. The Complex Conic flare changes smoothly from a narrow diffraction slot, through an oval expansion, to a circular mouth producing smooth pattern control. Passive models are shown below, but may be upgraded to active models with the purchase of an optional Class "D" amp, easily installed in the field. Or upgrade with RHAON empowered amps, PFI-200R or PFI-500R. The resulting RHAON (Renkus-Heinz Audio Operations Network) empowered versions allow you to use Cobranet based digital audio distribution and have control over your system via free control software on any Windows based computer, using standard ethernet hardware and cabling. (To order either version of the amp modules factory-installed, call for part number and price.) All CFX passive models are provided with both looping 4-pin Neutrik Speakon type connectors and screw-type terminal strips. Models available in black or white. Call for various mounting options.

white. Can for various mounting options.
ITEM DESCRIPTION PRICE
CFX61
CFX81
CFX12112" 2-way, passive, 90°x60°, rotatable horn, 70Hz-18kHz, 500W
CFX15115" 2-way, passive, 90°x40°, rotatable horn, 60Hz-18kHz, 700W
CFX121M12" 2-way floor monitor, passive, 90°x60°, rotatable horn, 70Hz-18kHz, 500W633.60
CFX18S
Amplifier Options for CF/CFX Series
PF1-200
PF1-200RRHAON empowered PF1-200 200W Class D amplifier for all CFX models 1126.00
PF1-500500W RMS Class "D" amp/processor used to turn CFX121,
CFX151, CFX18S models into self-powered models
PF1-500RRHAON empowered PF1-500 500W Class "D" amplifier used to
turn CFX121, CFX151, CFX18S models into self-powered models
SGX12S SGX121

RENKUS-HEINZ SYGMA SERIES INSTALL LOUDSPEAKER SYSTEMS This series of install speakers is great for side- and front-fill applications, fore-

ground music systems in retail stores or offices, or multi-channel playback systems



in clubs. They incorporate European transducers and the same Complex Conic Horn technology found in the Renkus Heinz CFX

Series. Passive models are shown below, but may be upgraded (with the exception of the SGX41) to active models with the purchase of optional Class "D" amplifiers, PF1-200 or PF1-500, easily installed in the field. Or choose the PF1-200R or PF1-500R amplifiers to add Ethernet audio networking. These RHAON (Renkus-Heinz Audio Operations Network) empowered versions allow you to use Cobranet based digital audio distribution and have control over your system via free control software on any Windows-based computer, using standard Ethernet hardware and cabling. (To order either version of the amps factory-installed, call for model numbers and pricing.) All SGX passive models have both looping 4-pin Neutrik Speakon type connectors and screw-type terminal strips. All models are available in black or white. Call for various mounting options.

ITEM DESCRIPTION	PRICE
SGX41	
SGX42Dual 4", "stair-step" speaker, passive, 300Hz-20kHz, 240W@16oh	
SGX61	
SGX81	
SGX121	
SGX151	
SGX12S	
Options for Sygma Series (partial listing, call for mounting options)	
PF1-200200W RMS Class "D" amp/processor for all SGX models	
PF1-200RSame as above but RHAON empowered	
PF1-500	
SGX121/SGX151/SGX12S into self-powered speakers	900.00
PF1-500RSame as above but RHAON empowered	
TR100W	
100, 80, 50, 32, 18, 8, & 4W taps, not installed	192.00
TR400W	
162, 100, 80, 50, 32, 18, 8, & 4W taps, not installed	210.00
WR61-RKH Weather-resistant option for SGX61 cabinet	
WR81-RKH Weather-resistant option for SGX81 cabinet	192.00
WR121-RKH Weather-resistant option for SGX121 cabinet	410.00
WR151-RKH Weather-resistant option for SGX151 cabinet	450.00
WR12S-RKH Weather-resistant option for SGX12S cabinet	410.00
PF-WR-KIT Weather-resistant option for all PF Series amps	332.00



YORKVILLE ELITE SERIES LOUDSPEAKERS Features a complete range of flexible and practical FOH-/monitor-combo enclosures. Can be used as an array, on tripod or used as a wedge monitor. Revoiced and refit, several models in the



series also feature rotatable HF horns that allow reconfiguration of the HF section from 80°x50° to 50°x80. Small, loud and easy to use. Most new elite series enclosures are made of 15mm Baltic Birch and feature standard flying hardware. Many models are also

available in black "Ultrathane" painted versions with additional fly points for touring and/or fixed installation applications. Also features distinctive curved anti-resonant grilles, inset handles & jack plates, all plywood construction with internal bracing, passive crossover networks with CTL, ATP or PTC high frequency driver protection, SpeakonTM and 1/4" connectors, stand adaptors and Yorkville's two-year (even if you break it!) transferable warranty. Powered versions shown, passive models are also available in this series.

ITEM DESCRIPTION PRICE
Powered Full Range Loudspeakers
E10P
hardware, 300/50W bi-amped, built-in mixer, mic/line inputs
E10PBUlrathane black painted version of E10P1000.00
EF500P800W, 15" woofer, 2" HF driver on 60°x40° horn, 650/150W bi-amped1480.00
EF500PBUltrathane black painted version of above – 15mm birch enclosure 1560.00
Powered Subwoofers
LS200P200W, 10" subwoofer, ultra-low profile mini subwoofer, level control 600.00
LS720P720W, 15" subwoofer, mini subwoofer, level control, HF roll-off,
variable LF boost frequency speaker or line levels inputs
LS701P700W, two 10" subwoofers, low profile mini subwoofer
w/internal x-over/processor, level control
LS701PB Ultrathane black painted version of above
LS801P1500W, 18" subwoofer, dual-tuned subwoofer enclosure,
level control, HF roll-off, speaker or line levels inputs
LS801PB Ultrathane black painted version of above 1639.20

YORKVILLE YX SERIES LOUDSPEAKERS Offers rugged 5/8" plywood cabinet construction, all metal bar handles, metal input plate, integrated speaker mounts and a custom punched, perforated metal grille to protect the speaker components. A modified trapezoidal shape (YX10, YX12, YX15) ensures the YX Series can function equally as well as a front-of-house or monitor speaker. Injection molded 90°x30° horns with 1" throat and 1.4" diaphragm neodymium compression drivers are used on all full-range cabinets in the line. Yorkville's dual-bulb CTLTM (current-to-light) protection system protects each horn



driver's aluminum diaphragm ensuring unmatched reliability in the field. Road-ready with easy-to-clean, durable black carpet covering. All speakers have two 1/4" and 2 Speakon inputs (YX15P has mic/line inputs).

ITEM	DESCRIPTION	PRICE
Passive Full H	Range Models	
YX10		207.20
YX12		271.20
YX15		320.00
YX150		456.00
YX215		560.00
Subwoofer		
YX18S		399.00
Active Full Ra	nge Models	
YX15P		
	1" neodymium HF driver, built-in mixer, mic/line inputs	480.00

YAMAHA

YAMAHA BR-SERIES PAS-SIVE SPEAKERS BR models are designed to fit the budgets of performing musicians, small



churches, and schools. Each model's large steel handles, corner protectors, and built-in pole sockets, assure both durability and flexibility. High-frequency response is also enhanced with a new titanium HF driver and 90° by 40° non-resonant horn. All BR-Series models are covered by a 3-year warranty. With integral protection circuitry built into the passive crossover, you can expect a long life of high output and minimal distortion. Speakers feature dual phone jack inputs.

ITEM	DESCRIPTION	PRICE
BR10	10" 2-way speaker, 250W/8ohms, 65Hz-20kHz	CALL
BR12		CALL
BR15		CALL
BR12M		CALL
BR15M	15" floor monitor, 400W/8ohms	CALL



Tube



YORKVILLE SOUND

Instrument Amplifiers Studio Effects Processors Audio Solutions Live Sound Installation Loudspeakers DJ PA Microphones Studio Monitors
Stands, Cables & Accessories Reference Monitors 70-volt Systems Touring Systems Tube-based Signal Processing



SOUND REINFORCEMENT SPEAKERS



YAMAHA CLUB-V PASSIVE LOUDSPEAKERS A best buy in price and performance. Great sounding speakers available in carpet covered, elastomeric spray finished and flyable models. The portable models have heavy-duty handles, pole socket and steel grill. All models are 2-way and powered by true compression drivers. Custom Eminence drivers are used, the horns have a 90x40 constant directivity pattern. Connectors are Neutrik Speakon and Switchcraft 1/4" with two of each connector for easy daisy chaining.

neetor for easy daisy channing.			
ITEM	DESCRIPTION	PRICE	
S Series: road-w	orthy, rugged carpet covered models		
S112V	12" 2-way, 350W/8ohms, 60Hz-16kHz	CALL	
S115V	15" 2-way, 500W/8ohms, 55Hz-16kHz	CALL	
S215V	Dual-15" 2-way, 1000W/8ohms, 42Hz-16kHz	CALL	
SM10V	10" floor monitor, 250W/8ohms, 70Hz-20kHz	CALL	
SM12V	12" floor monitor, 350W/8ohms, 60Hz-16kHz	CALL	
SM15V	15" floor monitor, 500W/8ohms, 55Hz-16kHz	CALL	
SW118V	18" subwoofer, 600W/8ohms, 30Hz-2kHz	CALL	
SW218V	Dual-18" subwoofer, 1220W/8ohms, 30Hz-2kHz	CALL	
C Series: durable	e spray finished models with foamed steel grilles		
C112V	12" 2-way, 350W/8ohms, 60Hz-16kHz	CALL	
C115V	15" 2-way, 500W/8ohms, 55Hz-16kHz	CALL	
C215V	Dual-15" 2-way, 1000W/8ohms, 42Hz-16kHz	CALL	
CM10V	10" floor monitor, 250W/8ohms, 70Hz-20kHz	CALL	
CM12V	12" floor monitor, 350W/8ohms, 60Hz-16kHz	CALL	
CM15V	15" floor monitor, 500W/8ohms, 55Hz-16kHz	CALL	
CW118V	18" subwoofer, 600W/8ohms, 30Hz-2kHz	CALL	
CW218V	Dual-18" subwoofer, 1220W/8ohms, 30Hz-2kHz	CALL	
Flyable Models:	ideal for installations		
C112VA	12" 2-way, 350W/8ohms, 60Hz-16kHz	CALL	
C115VA	15" 2-way, 500W/8ohms, 55Hz-16kHz	CALL	

YAMAHA DSR SERIES ACTIVE LOUDSPEAKERS These include a combination of ultra-sophisticated digital sound processing and the

latest acoustic technologies, including D-CONTOUR multi-band dynamic processing for consistent clarity at both high and low output levels. Each incorporates high power Class "D" amplifiers a/PFC switching mode power supply, and has 3-way fail-safe DSP protection. Advanced digital sound processing includes FIR-X tuningTM for the smoothest possible crossover transitions and high power DSP, plus 24bit discrete AD & DA converters for maximum dynamic range. Exclusive LTBD (Long Throw, Broad Dispersion) Constant Directivity Waveguide Horn provides 90° horizontal x 60° vertical coverage with full-frequency sound projected all the way to the edges of the coverage area (except DSR118W). The DSR112 and DSR115 are stand and pole mountable with 35mm pole sockets & have M10 rigging points for suspended installation. DSR112 can be tilted for use as a floor monitor and additional monitors can be daisy-chained via the XLR THRU jack on the rear panel. Models feature XLR and 1/4" TRS inputs (DSR118W has XLR only) that accept both mic and line level input. Easy to handle series capable of 1300W power output (DSR118W is 800W).

ITEM	DESCRIPTION	PRICE
DSR112	12" 2-way, biamp powered speaker,	
	60Hz-18kHz (-3db), 134dB SPL, 47lbs	CALL
DSR115	15" 2-way, biamp powered speaker,	
	55Hz-18kHz (-3db), 136dB SPL, 62lbs	CALL
DSR215	Dual 15" 2-way, biamp powered speaker,	
	55Hz-18kHz (-3db), 138dB SPL, 110lbs	CALL
DSR118W	18" powered speaker,	
	50Hz-110kHz (-3db), 132dB SPL, 93lbs	CALL

SAMAHA

YAMAHA DXR AND DXS SERIES ACTIVE LOUDSPEAKERS The DXR and DXS speakers use custom-designed transducers mated with highly-efficient Class 'D' amplifiers to generate up to 133dB with 700W of power. The DXR series feature an intelligent 3-ch mixer, flexible I/O, custom-designed DXR transducers, and the unique Smart Mixing/Linking function. Durable ABS enclosures can be mounted via rigging points, dual-angle pole socket, or optional U-brackets. DXS subwoofers feature D-XSUB processing and perfectly complement the DXR series.

ITEM	DESCRIPTION	PRICE
DXR8	. 700W, 129dB SPL, 57Hz-20kHz, 8" LFT	CALL
DXR10	. 700W, 131dB SPL, 56Hz-20kHz, 10" LFT	CALL
DXR12	. 700W, 132dB SPL, 52Hz-20kHz, 12" LFT	CALL
DXR15	. 700W, 133dB SPL, 49Hz-20kHz, 15" LFT	CALL
DXS12	. 600W, 131dB SPL, 45Hz-160Hz, 12" LFT	CALL
DXS15	. 600W, 132dB SPL, 45Hz-160Hz, 15" LFT	CALL



MSR400

MSR800W

YAMAHA MSR SERIES POWERED SPEAKERS The MSR400 powered speaker can be used alone or in combination with the MSR800W powered subwoofer to assemble sound reinforcement systems from modest to massive. They look great, too. So good that they can be used as-is in many permanent installations without requiring any cosmetic cover-up. And, of course, they're more than rugged enough for demanding tour applications as well. The MSR100 can fill many sound reinforcement and stage monitor needs in one inexpensive, lightweight package.

ITEM	DESCRIPTION	PRICE
MSR100	8" 2-way active speaker, 100W/6ohms	CALL
MSR400	12" bi-amped 2-way speaker, 225W LF/75W HF	CALL
MSR800W	15" active subwoofer, 500W/8ohms	CALL

SAMSON'

SAMSON AURO SERIES Active Loudspeakers

Compact and powerful, these loudspeakers provide full-range audio with power and clarity. All include a 1-3/8" pole-mount receptacle and floor monitor positioning options for flexible setup. Available in 200W or 400W

configurations, all models feature a 1" (D208, D210) or 1.34" (D412, D415) compression driver with 1" exit, Class "D" power amplifier, mic/line input, volume control and clip LED. D412 & D415 add 2-band shelving EQ and built-in Optimax compressor/limiter with 2-stage speaker protection. Multiple cabinets can be





linked via XLR line output. The 500W D1800 subwoofer has an $18^{\prime\prime}$ low frequency transducer with a $3^{\prime\prime}$ voice coil.

ITEM	DESCRIPTION	PRICE
	8" 2-way active loudspeaker, 200W	
AURO-D210	10" 2-way active loudspeaker, 200W	
AURO-D412	12" 2-way active loudspeaker, 400W	
AURO-D415	15" 2-way active loudspeaker, 400W	
AURO-D1800	18" active subwoofer, 500W	

