### 412

ALIDIO

















MUSIC



COMPUTER AV







































### VIDEO MONITORS AND DISPLAYS (LCD, PLASMA, AND CRT)

# Blackmagicdesign





# BLACKMAGIC DESIGN SMARTVIEW LCD MONITORS Smartview Monitors include 3-color integrated tally borders,

international power supply, Ethernet connection, USB 2.0 update port, SDI inputs with loop out, switchable between SD-, HD- and 3G-SDI. Duo features (2) 8" LCD screens in a compact 3RU design while HD features (1) 17" 1080p LCD screen in a sleek 6RU design. Both are only 1" thick and perfect for any rackmount setup.

	U			
ITEM	DESCRIPTI	ON		PRICE
SMARTVIEW-DUO	Dual 8" LCI	D 3RU rackr	nount monitor	 470.25
SMARTVIEW-HD	17" HD LCC	6RU rackm	nount monitor	 850.25

# datavideo



**DATAVIDEO TLM-702 DUAL 7" TFT LCD MONITORS** The TLM-702 includes two 7" TFT LCD monitors (1440x234) in a standard 19" rackmount, 3RU high. It can tilt up to +/- 30° and lock in any position. Controls include flip, 4:3 aspect, 16:9 aspect, mirror image, source select, contrast, brightness, color, and tint.

ITEM	DESCRIPTION					PRICE
TLM702	(2) 7" TFT LCD m	onitor, 3RU.				. 850.00
TLM702MH	TLM-702 monitor	with holder	to attach to	SE-500 st	witcher	1050.00



**DATAVIDEO TLM433 THREE 4.5" LCD MONITOR UNIT** This rackmountable unit has adjustments for contrast, brightness, color and tint and an LED tally light indicator above each screen. Includes 3 composite video BNC outs for loop-through.

	1
ITEM	DESCRIPTION PRICE
TLM433	Rackmount (3) 4.5" LCD broadcast monitors, 2RU

#### DATAVIDEO TLM-170H LCD MONITOR

The TLM-170H is a 17.3", HD-SDI desktop monitor. It features a 1600x900 resolution and a backlit LED screen (desktop only). It also has built in stereo speakers and an audio level indicator. Connections include two CV inputs, one S-Video. HD-YUV. HD-SDI and HDMI

one 3-video, nD-1	UV, ND-SDI AHU NDIVII.	
ITEM	DESCRIPTION	PRICE
TLM-170H	. Desktop monitor with backlit LED	1400.00
TLM-170HM	. 1RU rack-mounted LCD monitor	1850.00
TIM 170UD	7DII rook mounted LCD monitor	1500.00

# DATAVIDEO TLM-700HDPD 7" HD/SD-SDI FIELD MONITOR Suited

for use in the field or studio, this unit can be powered with 12V DC or AC and automatically switches between PAL and NTSC. It features a standard V-mount that allows you to use universal batteries. A sunshade is included for in-the-field applications. It can be calibrated with an internal color bar,



color temperature, color select and the "blue-only" mode. Inputs include HD/SD-SDI, HDMI, YUV component and composite and a 15-pin D-sub connector for tally control. Includes 12V DC power supply, battery not included.

ITEM	DESCRIPTION	PRICE
TLM-700HDPD	7" TFT LCD field monitor with HD/SD-SDI input	805.00
MO-TLM700	Case for TLM700HD (by Porta-Brace)	181.41
E7S	IDX Li-Ion V-Mount battery 71Wh/4.8Ah, 14.8V	259.00

### **IKAN D-SERIES LCD MONITORS**

These small and lightweight camera field monitors have a HD resolution of 1280x800 pixels and are equipped with 3G-SDI (input/output) and a HDMI input. Features false color, peaking, DSLR scaling and customizable function buttons on the back. Units come in 5" or 7" IPS and are available as waveform monitors



with waveform, vectorscope, and RGB parade options.

ITEM	DESCRIPTION	PRICE
D5-C	5.6" 3G-SDI LCD monitor, Canon '900 Series' DV battery plate	629.00
D5-P	As above, with Panasonic 'D54' DV battery plate	629.00
D5-S	As above, with Sony 'L' Series DV battery plate	629.00
D5W-C	5.6" 3G-SDI LCD monitor with waveform and	
	Canon '900 Series' DV battery plate	899.00
D5W-P	As above, with Panasonic 'D54' DV battery plate	899.00
D5W-S	As above, with Sony 'L' Series DV battery plate	899.00
D7-C	7" 3G-SDI LCD monitor, Canon '900 Series' DV battery plate	899.00
D7-P	As above, with Panasonic 'D54' DV battery plate	899.00
D7-S	As above, with Sony 'L' Series DV battery Plate	899.00
D7W-C	7" 3G-SDI LCD monitor with waveform and	
	Canon '900 Series' DV battery plate	1169.00
D7W-P	As above, with Panasonic 'D54' DV battery plate	1169.00
D7W-S	As above, with Sony 'L' Series DV battery plate	1169.00

VHR-C

### IKAN VK5 AND VH8 HDMI MONITORS The ikan 5" VK5 and 8" VH8 are perfect solutions for DLSR monitoring with their lightweight, low profile

designs. Both monitors feature HDMI inputs, red peaking, DSLR scaling, false color and clip guides. The VH8 has addi-



tional features including a HD IPS display panel, looping HDMI, composite input and 4 touch-sensitive buttons. Powering these monitors in the field is easy with snap-on/ screw-on battery plates that are compatible with a variety of Pro, DV style, and LP-E6 style batteries. Deluxe kits are available which also include a battery, battery charger and soft case—contact your sales rep for more information.

ITEM DESCRIPTION	PRICE
VK71-C7" HDMI IPS field monitor with Canon battery adapter plate	449.00
VK71-PAs above, with Panasonic battery adapter plate	449.00
VK71-SAs above, with Sony 'L' Series battery adapter plate	449.00
VK7I-SUAs above, with Sony BPU Series battery adapter plate	449.00
VH8-CVH8 Monitor with Canon "900" Series battery adapter plate	359.00
VH8-PAs above with Panasonic "D54" Series battery adapter plate	359.00
VH8-SAs above with Sony "L" Series battery adapter plate	359.00



### JVC BROADCAST LCD MONITORS

Full 1080p image displays that offer a wide color range and wider viewing angle. Includes digital closed captioning, superior scaling, de-interlacing and 10-bit 4:4:4 1080p processing. Models also have 12-channel audio level meter with peak hold. Inputs include DVI-D,



component and composite video as well as RCA audio-in. DT-E models feature a TN Panel with LED backlighting that provides improved contrast and black level, as well as 20-30% less power consumption. DT-V models have a superior IPS display. built-in waveform/vectorscope and a 3G/dual-link HD-SDI input that enables monitoring of 1080/60p signals. The DT-3D24G1U uses passive 3D technology to display flicker-free images and is compatible with side-by-side and line-by-line 3D formats.

ITEM	DESCRIPTION	PRICE
DTE17L4GU	. 17" HD LED LCD monitor with HD/SD-SDI	2415.00
DTE21L4U	. 21" HD LED LCD monitor with HD/SD-SDI	2650.00
DTV17G1Z	. 17" HD IPS LCD monitor with 3G/dual-link HD-SDI	2695.00
DTV24G1Z	. 24" HD IPS LCD monitor with 3G/dual-link HD-SDI	3795.00
DT3D24G1U	. 24" HD 3D LCD monitor with (2) 3G/dual-link HD-SDI	CALL
RAK17LCDGS	. Rackmount kit for DTV17G1Z	140.00
RAK2024LCD	. Rackmount kit for DTV 20" to 24" LCDs	174.81

### **Marshall Electronics**



MARSHALL ELECTRONICS MD SERIES LCD RACK DISPLAYS WITH MODULAR INPUTS The MD series of rack monitors feature interchangeable input modules. V-MD434 and V-MD503 units feature advanced front panel menu and feature control. V-MD702, V-MD171X, and V-MD201 feature composite and component inputs. All models feature false color filter, markers, freeze function, status display, color temp presets, RGB gain/bias adjust, blue gun, pixel-to-pixel and hard tally. V-MD171X and V-MD201 monitors can be used on desktops with purchase of optional stand. Monitors can be purchased with 3GSDI input modules already installed.

ITEM	DESCRIPTION	PRICE
V-MD434	2RU (4) 4.3" 800x480 widescreen rack monitor unit, with	
	front-panel menu/feature control, without input modules	2597.85
V-MD503		
	menu/feature control, without input modules	2011.35
V-MD563		
	with composite/component inputs	2988.85
V-MD72	3RU (2) 7" LED-backlit 800x480 rack monitor unit,	
	without input modules	
V-MD702	As V-MD72, with composite/component inputs	1907.85
V-MD171X	6RU 17" 1900x1200 rack monitor with composite/component inputs .	1896.35
V-MD201	7RU 20" 1600x900 rack monitor with composite/component inputs.	1493.85
Input Modules	for V-MD434, V-MD503	
MD-3GSDI-B	3G/HD/SDI input module with loop-through	320.85
MD-HDSDIX2-B.	2-channel HDSDI input module with switched output	412.85
	2-channel HDMI input module	
	DVI-I input module	
	for All Other Models	
	3G/HD/SDI input module with loop-through	320.85
	2-channel HDSDI input module with switched output	
	2-channel HDMI input module	
	DVI-I input module	
Desktop Stand	•	
	Desktop stand for V-MD171X rack monitor	3/1//
	Desktop stand for V-MD201 rack monitor	
V-0120	Desktop stalia for Y-MDZOI rack illullitul	43.34

V-R231-IMD-HDSDI



ELECTRONICS IN-MONITOR DISPLAY-CAPABLE LCD MONITORS Allows UMD (Under-Monitor Display) information and tallies to be displayed directly within the monitor. Available features include on-screen video time code, 3-color "Soft" Tallies, audio presence indicator and easy menu navigation. Integrates easily with existing Tally systems and controllers, while supporting Image Video, NVISION, TSL, and MEI protocols. All except the Quad Viewer monitors include HDSDI/SDI inputs and can be used as standalone displays with HDSDI loop-through. Quad Viewer models offer full-screen mode for video and DVI and quad-split mode (via built-in HD quad splitter) which is scaled to fit onscreen in the highest resolution. The Quad Viewer models have (4) independent HDSDI inputs, (1) DVI input, field-upgradeable firmware, and an RS422/485 port with pass-through. Dual Link/Waveform models feature 10-bit video path with 3G capable monitors and can display live video, audio bars, waveform and vectorscope in quad-view mode. They also have (2) 3G/HD/SDI inputs, Dual Link, a DVI input, RS485 firmware updating, and closed captioning (CEA-608-B, CEA-708-B). The NCB-1005 allows connected IMD monitors to be controlled by PC via Ethernet.

ITEM DESCRIPTION PR	ICE
V-R653P-IMD-TE (3) 6.5" HD/SD monitors in 2RU rack unit, 1024xRGBx768 4483	.85
V-R653SB-IMD As above, outdoor version	.85
V-R1041-IMD-TE4U 10.4" HD/SD rackmount monitor, 4RU, 1024xRGBx768 2068	.85
V-R1042-IMD-TE4U (2) 10.4" HD/SD monitors in 4RU rack unit, 1024xRGBx768 3444	.25
V-R171X-IMD-HDSDI 17" HD/SD rackmount monitor, 6RU	.85
V-R201-IMD-TE 20" HD/SD rackmount monitor, 6RU, 1680xRGBx1050	.85
VP-LCD171H-ST-01 VESA mount stand with pivot and tilt for 20", 23" monitors 182	.85
NCB-2010 Network control box for -IMD monitors	
V-R171X-IMD-HDSDI 17" rackmount monitor, 6RU, 1920xRGBx1200	
V-R185-DLW	
V-R185-IMD-3GTE 18.5" desktop monitor, 3G/HD/SDI, 1366x768	.86
V-ST15 Desktop stand for Quad Viewer monitors	
<b>V-R261-DLW</b>	.35































































































### Marshall Electronics



V-R72DP-2C

MARSHALL ELECTRONICS PROFESSIONAL LCD RACKMOUNT MONITORS These come in a wide variety of size and mounting arrangements. Displays are lightweight, have a shallow depth, run cool and tilt for optimum viewing. Many models feature TFT MegaPixel $^{\rm TM}$  displays for better images and pixel density compared to other monitors. Configurations are also available with HDSDI, SDI, DVI, component HD/SD and composite video inputs.

ITEM	DESCRIPTION	PRICE
V-R43P	Triple 4" in 2RU, composite ins on each	1006.25
V-R44P	Four 4" in 2RU, composite ins on each	1263.85
V-R573P	Triple 5.7" in 3RU, 2 composite ins on each	1378.85
V-R653P-HDSDI	Triple 6.5" HD in 3RU, HD/SD-SDI inputs,	
	composite and component ins	3103.85
V-R70P-HDSDI	. Standalone 7" HD widescreen 1.2 TFT-Megapixel,	
	video assist monitor, HD/SD-SDI ins	1608.85
V-R70-1M	Rackmount adapter for V-R70P units	59.80
V-R72DP-2C	Dual 7" widescreen in 3RU, 2 composite ins on each	1608.85
V-R82SB-AFHD	Dual 8.4" backlit/for outdoor use in 4RU, 800x600, with HD/SD-	·SDI,
	component, composite, S-Video, DVI, SXGA ins on each	4081.35
V-R902-DLW	Dual 9" in 4RU, 1280x768, with In-Monitor-Display and waveform functions, with HD/SD-SDI, DVI, HDMI,	
	component and composite ins on each	4437.85





MARSHALL ELECTRONICS PORTABLE FIELD MONITORS These models are designed for outdoor and high ambient light situations. The LCD70XP and LCD651STX models have expanded hi-definition input options (HDMI/3GSDI), false color exposure assist, and peaking filter focus assist. The LCD651STX and LCD70XP models are also available with Canon, JVC, Panasonic and Sony battery mounts.

ITEM Sunbright Models	DESCRIPTION	PRICE
	6.5" hi-res Sunbright monitor, RGB, 640x480	1493 85
	8.4" hi-def Sunbright monitor, RGB, 800x600,	1100.00
	also has SDI/HDSDI, VGA, DVI and S-Video inputs	1608.85
V-LCD15SB-AFHD-DT	15" hi-def Sunbright monitor, 1024x768, SDI/HDSDI,	
	VGA, DVI and S-Video inputs, includes desktop stand	2528.85
5" Model	511 UDAN	510.05
	5" HDMI camera-top monitor, 800x480, uses AA batteries	516.35
6.5" Models	0.5% 1.004.700	
	. 6.5" hi-res camera-top monitor, 1024x768	
	. As above, with Anton Bauer battery adapter	
	6.5" hi-res camera-top monitor with HDMI in, 1024x768	
	As above, with Anton Bauer battery adapter	
	As above, with V-Mount battery adapters	
	6.5" hi-res camera-top monitor w/ 3G/HD/SD in, 1024x768 1	
	. As above, with Anton Bauer battery adapter	
V-LCD651STX-3GSDI-VM	. As above, with V-Mount battery adapter	1884.85
7" Models		
	7" high brightness camera top monitor w/3G-SDI in, 800x480	
	. As above, with Canon BP battery adapter	
	. As above, with Sony B series battery adapter	
	7" high brightness camera top monitor w/HDMI in, 800x480	
	As above, with Canon BP battery adapter	
V-LUU/UXHB-HUIPI-3B.	. As above, with Sony B series battery adapter	C8.01UJ

### Marshall Electronics

MARSHALL ELECTRONICS LYNX™ SERIES LCD MONITORS Displays are lightweight, shallow in depth, run cool and tilt for viewing. Many models feature TFT MegaPixel™ displays offering the highest pixel density for improved images compared to similar CRT and standard LCD products. Available in 10" to 19" displays. Significant improvements have been made to brightness, contrast ratio, and viewing



angles. Various input configurations available. MegaPixel models feature screens calibrated to SMPTE/IBU standards for color gamut and color temperature.

camprated to biii	12 120 ottandardo for coror gamat and coror temperature.	
ITEM [	DESCRIPTION	PRICE
M-LYNX-10	10" 4:3 LCD monitor, 800x600 with composite,	
	S-video, VGA and stereo inputs	.311.22
M-LYNX-10W	10" TFT 16:9 LCD monitor with rear speakers, remote control,	
1	1024x600, composite, S-video, DVI, VGA and stereo audio inputs	.375.06
M-LYNX-15	15" 4:3 LCD monitor with speakers, 1024x768, (2) composite,	
(	component, S-video, VGA, DVI and (2) audio inputs	.420.66
M-LYNX-17	17" 5:4 LCD monitor with speakers,1280x1024, (2) composite,	
(	component, S-video, VGA, DVI and (2) audio inputs	.454.86
M-LYNX-17SDI	17" 4:3 LCD monitor with SD-SDI BNC loop-thru	1287.06
M-LYNX-191	19" 5:4 LCD monitor with speakers, 1280x1024, (2) composite,	
(	component, S-video, VGA, DVI inputs and (2) audio inputs	.557.46
M-LYNX-19SDI	19" 5:4 LCD monitor with SD-SDI BNC loop-thru	1366.86



MARSHALL ELECTRONICS ORCHID® SERIES RACKMOUNT BROADCAST LCD MONITORS This series of rackmount monitors not only integrates interchangeable components or DVI input modules, but is also packed with additional features such as re-clocked outputs, auto-sensing HDSDI inputs, real-time waveform monitors and color vectorscopes, tri-color tally indicators, adjustable color temperature, timecode, precision gamma settings, adjustable clipping indicators, and more. All models are capable of de-embedding and displaying up to 16 channels of audio, any 2 channels of which can be monitored at one time. Each unit comes with at least one HDSDI input, one HDSDI output, and one input slot per screen, and stereo audio 3.5mm outputs

ITEM	DESCRIPTION	PRICE
OR-434	. Four 4.3" monitors, 2RU, 5 assignable function keys and	
	1 joystick menu system, 800x480	.4426.35
OR-503	. Three 5" monitors, 3RU, 6 assignable buttons/screen,	
	4 assignable rotary encoders, 5-button menu system, 800x480	.3908.85
OR-701A	. Single 7" monitor, 3RU, dual HD/SD-SDI inputs, stereo speakers,	
	11 assignable function keys, 4 assignable rotary encoders,	
		.2413.85
OR-702	. Two 7" monitors, 3RU, 11 assignable function keys,	
	4 rotary encoders, 5-button menu system, 800x480	.3310.85
OR-841-HDSDI	. Single 8.4" portable field monitor, 4RU, 1024x768,	
	9 assignable buttons	.2758.85
OR-901-XDI	9" monitor, rack/camera mountable, 4RU, HD-SDI/HDMI, 3D ready	.3276.35
	. Optional component input module	
	Optional DVI-I input module	

BTLH1760

### **Panasonic**

PANASONIC BROADCAST LCD MONITORS

Designed for critical broadcast and production

applications as reference grade HD and SD monitors.	
ITEM DESCRIPTION	PRICE
BTLH910GJ	
HDMI, BNC, and D-Sub inputs, 3.7 lbs	2995.00
BTLH1760PJ17" LCD monitor (16:9), 1280x768, Vectorscope/WFM,	
DVI-D and (2) HD-SDI/SDI inputs, embedded audio,	
time code/CC capable, with desk stand, 13.7 lbs	4220.00
BTLH2550PJ 25.5" HD widescreen monitor, 1920x1200, DVI-D and	
(2) HD-SDI inputs, composite, component, vectorscope, 18.1 lbs	3509.00
Accessories	
BT-MOUNT Camera monitor mount for BTLH910GJ	151.20
BT-YUC1700 Thermodyne case for BTLH1760	361.20
BT-YUC2550 Travel case for BTLH2550	616.80
MO-LH910B Flat screen monitor case for the BTLH910G, black (by Porta-Brad	ce) 181.41
Call for more accessories.	











## 416

















































### **Panasonic**

#### PANASONIC TH-39LRU60U **HOSPITALITY SERIES DISPLAY**

Panasonic's Hospitality Series integrated LED-backlit displays has a built-in ambient light sensor that automatically adjusts the screen's brightness and contrast to suit the lighting of the room. Ideal for any



hotel environment for entertainment and communication in guestrooms, lobbies and waiting areas, as well as digital signage. They allow for easy connection to many external devices, while existing devices can be linked via the RS-232C interface.

,	8	
	DESCRIPTION	PRICE
TH39LRU60U	39" hospitality series display	683.40
TH42LRU60U	42" version	810.81
TH50LRU60U	50" version	1061.83
TH65LRU60U	65" version	3542.29

### PANASONIC BT-4LH310 4K LCD MONITOR For broadcast and cinema applications, this 31" 4K 10-bit IPS panel monitor supports 2K/HD and meets DCI (P3) color gamut standards. Its Look-Up Table function allows high-precision color management for digital cinema workflows. Display func-



tions include waveform monitoring, vectorscope, zoom, focus-in-red, Y-map, frame grab, error indication, zebra, RGB color, and markers and grid. Additional features include 1450:1 contrast ratio, a 178° viewing angle, an audio level meter, fanless operation, and time code/closed caption (2K/HD) display. SDI, HDMI, and DisplayPort inputs. Remote control via RS-485, RS-232C, and GPI remote.

ITEM	DESCRIPTION	PRICE
BT-4LH310	. 31" 4K IPS panel broadcast/cinema monitor	CALL

### PANASONIC TH-70LF50U **PROFESSIONAL**

**DISPLAY** These 3.5" thin LED displays offer excellent picture quality and visibility in applications from digital signage to boardroom display. Features include landscape and portrait modes, a ceiling suspension option, 24/7 operation, RS-232C



control, Slot 2.0 expandability, and LAN control compatibility.

ITEM	DESCRIPTION	PRICE
TH70LF50U	70" LED display	CALL
	80" version	

## PANASONIC PROFESSIONAL

LCD DISPLAYS Built with an IPS (In-Plane-Switching) panel, these pro LCD displays have an incredibly wide viewing angle and sharp 1080p resolution. The LF6 Series feature 450-cd/m2 brightness and 12-ms response for excellent performance. A slim bezel makes for a stylish display for digital signage and even allows them to be config-



ured in multi-screen video wall solutions. They are capable of stable 24/7 operation and includes an Eco Mode that detects surrounding light conditions and adjusts screen brightness accordingly for optimum viewing and energy savings.

			-		-	 -	
ITEM	DES	CRIPTION					PRICE
TH42LF6U	42"	1920x1080	IPS LCD	display		 	. 1032.00
TH47LF6U	47"	1920x1080	IPS LCD	display		 	. 1362.00



### LG PROFESSIONAL DIRECT LIT IPS LED DISPLAYS In-Plane-

Switching (IPS) technology provides these displays with a clear image at virtually any angle. It even reduces image distortion when touch pressure is applied to the screen. Built-in temperature control adjusts to light and heat elimi-



nating dark or blackened areas. Smart energy saving reduces consumption by 30% and USB multi-media playback ensure easy and fast content delivery. Features Full HD 1080p, 400 nits brightness and a 1000:1 contrast ratio. Inputs include HDMI, DVI-D, RGB, RS232C, RJ45, IR, USB and stereo mini jack; outputs include DVI-D, IR, stereo audio and RS232C.

ITEM	DESCRIPTION	PRICE
47WL10MS-B	47" 1080p direct lit IPS LED display with tuner	1015.54
42WL10MS-B	As above, 42" version	835.66

### SAMSUNG

### SAMSUNG PROFESSIONAL **EDGE LIT LED DISPLAYS**

These ultra-slim displays have an extremely narrow bezel that makes them perfect for video wall and digital signage applications. Full HD 1080p, 450 nits brightness



and a 5000:1 contrast ratio combine for sharp, detail-rich images and easily legible type. Offers USB cloning, auto source switching and recovery, video wall functionality (10x10), image rotation and a built-in media player. Series includes VGA, DVI-D, (2) HDMI, DisplayPort 1.2, component, USB, RJ45, RS232C, stereo mini jack and TV inputs with RS232C, DisplayPort 1.2 (Loop-out) and stereo mini outputs.

ITEM	DESCRIPTION	PRICE
ME75C		7139.95
ME55C	As above, 55" version	2176.95
ME46C	As above, 46" version	1409.46
ME40C	As above, 40" version	1124.95
ME32C	As above, 32" version	799.95

### SHARP

SHARP PROFESSIONAL LED LCD DISPLAYS Sharp's PN-E Series portrays uniform brightness, enhanced reliability and greater legibility of text. Engineered for 24/7 commercial use, these displays excel in digital signage applications



and even include stereo speakers, eliminating the need for an external audio system. Standard I/O includes HDMI, VGA and stereo audio inputs, stereo audio line-output and RS-232C input/output. The optional PN-ZB01 expansion board adds DVI-D, 5-BNC RGB, component, S-Video, composite, stereo audio, RJ45 LAN and stereo speaker output connections. Optional PN-TPC1 signage controller permits all-in-one digital signage package.

ITEM	DESCRIPTION	PRICE
PN-E802	.80" 1080p LED display with 7W speakers	CALL
PN-E702	. As above, 70" version	4980.94
PNE602	. As above, 60" version	3382.00
PN-E521	. As above, 52" version with 10W speakers	2012.87
PN-E471R	. As above, 47" version	1291.06
PN-E421	. As above, 42" version	975.70
PNZB01	PN-E expansion board	284.70







All include LED backlight for better color saturation and longer life.

1 LCD-703HD in rackmount kit, 3RU

2 LCD-703HD in rackmount kit, 3RU.

LCD-703HD with Anton Bauer QRC-Gold mount

Two 8" LCD in rackmount kit, no audio, 4RU...

RS232, supports 1080p/i, 720p and 480p/i.....

LCD-703HD with 'V' lock mount for IDX batteries .

. 9.7", 2x composite in/out, 2x speakers, 1024x768.......

As LCD410, adds BNC in/out..

As LCD562, adds BNC.

4" field monitor with audio, battery pack, NTSC

5" field monitor with stereo audio headphone jack, NTSC/PAL

5.6" field monitor with audio, battery pack, NTSC/PAL.

Three 5.6" LCD units in rackmount kit, tilts 90°, NTSC/PAL, 3RU.

.HD 8.4", 4:3 with 16:10 capability, composirt, component, S-Video, VGA, HDMI.

. 15.4", 16:9, audio, composite, component, S-Video analog RGB, HDMI,

DESCRIPTION

### SONY

#### 4K ULTRA HD 3D LED DISPLAYS

See more than ever before with Ultra HD (3,840x2160 pixels), four times the reso-Unition of Full HD (1920x1080). The new
4K X-Reality™ PRO chip enhances and upscales HD (and lower resolution) images by analyzing and refining images with



beautifully natural detail and astounding color. Dynamic Edge LED backlighting with local dimming boosts contrast in just the right areas, rather than illuminating the entire screen. A built-in front-facing speaker system offers 65W of power and simulated 5.1 surround sound. Built-in WiFi allow access to services like Netflix®, YouTube® and Hulu Plus™ as well as remote control via smartphones and tablets. Inputs include (4) HDMI, component, composite, analog audio, (3) USB, RF, Ethernet and RS232C. Outputs include digital optical audio, analog audio and headphone out. Supports 3D picture and includes (4) 3D glasses.

ITEM	DESCRIPTION	PRICE
XBR65X900A	65" 4K Ultra HD 3D LED display with 65W speaker system	CALL
XBR55X900A	As above, 55" version	3999.99



#### SONY PROFESSIONAL LCD COLOR MONITORS

An extensive line-up of SD and SD/HD professional LCD monitors from 15" to 42" featuring fast video response, extremely high brightness, contrast, color depth and wide viewing angle. A one-piece construction that includes integrated stand. The LMD4251TD add 3D capability, 3D glasses required. All models are ideal for HDV production applications with some models supporting HDMI or DVI.

ITEM	DESCRIPTION	PRICE
LMD1510W	15.6", 1366x768, HDMI, Composite, Component, Y/C, SDI	759.36
LMD2110W	21.5",1920x1080, HDMI, SDI, Composite, Y/C and RGB	959.40
LMD2451W	24", 1920x1200, DVI inputs, Composite, Y/C and RGB	. 3596.76
LMD2451WHD	LMD2451W packaged with BKM243HS HD/SD SDI adapter	. 3659.08
LMD4251TD	42", 1920x1200, 3D, DVI inputs, Composite BNC	CALL
Accessories		
BKM243HS	HDSDI/4:2:2 SDI input adapter, for LMD2051W, LMD2451W	. 1030.38
TDGBR250/B	3D glasses	39.97

### SONY PVM SERIES OLED PROFESSIONAL VIDEO MONITOR The PVM series uses an OLED

(Organic Light Emitting Diode) panel, which creates true blacks and higher contrast than LCDs. Picture quality is excellent both indoors and outdoors, plus the new panels allows for off-axis viewing without color shift. Supports broadcast standards SMPTE-C, EBU and ITU-R BT.709, with resolutions from NTSC/PAL to 1080p60. The PVM Series monitors come standard with



two 3G/HD/SD-SDI inputs, an HDMI input, composite input, internal waveform monitor and AC power adapter. The PVM-741 includes 1/4" and 3/8" holes for camera mounting.

2			
ITEM	DESCRIPTION	PRICE	
PVM741/A	7.4" 960x540 OLED professional field monitor	2058.00	
PVMA170	. 17" 1920x1080 OLED professional monitor	4081.69	
PVMA250	. 25" 1920x1080 OLED professional monitor	CALL	
SU561	Monitor stand for PVM1741 or PVM2541	186.47	

SONY FWD SERIES HD LED DISPLAYS These public display HD LED LCDs have slim bezels for a more refined and stylish look. Incorporating high-quality, professional 46" and 42" (diagonal) LCD panels, they offer full HD (1920x1080) resolution and high brightness for use in bright light conditions. They support audio in/out (pinjack), HDMI in, HD15 in/out with audio in, composite in/ out (BNC x 2) with audio in, component video in with



audio in (pin jack x 3) and L/R speaker out. Also equipped with a network port for remote control/monitoring. An option slot accepts a range of adapters for versatility. Well-suited for retail shops, shopping malls, hospitals or schools. The FWDS42B2 is a low power consumption (120W) model and has DVI-D and HDMI inputs.

ITEM	DESCRIPTION	PRICE
FWDS42H2	. 42" slim HD LED display	. 1811.04
FWDS46H2	. 46" slim HD LED display	. 2028.37
FWD42B2	. 42" slim HD LED display, low power consumption	. 1303.95
BKMFW16	. HDSDI/SDI input adapter	879.89

4" to 5.6" Monitors

ITEM

LCD400X4...

LCD410

I C.D411

LCD501

LCD562

LCD565

LCD703HD.

LCD703HD1

LCD703HD2

LCD703HDA

LCD703HDV

LCD842HD

LCD842HD2

10.4" MONITORS LED1002HD

15.4" MONITORS LCD1560HD

LCD703HD-KIT.

7" - 8" Monitors

LCD560X3



Four 4" LCD units in 19" rackmount kit, tilts 90°, NTSC/PAL, 2RU .... 1010.00

. HD 7", 16:9, DVI, component in/out, S-Video in/out, BNCin/out, 1080p... 629.00 . LCD-703HD with rechargeable battery pack, tote bag, and AC.......................807.00

214.00

258.00

942.00

317.00

317.00

740 00

1256.00

. 617.00

595.00

.. 785.00

1660.00

479.00

662.00



















COMPUTER AV

































# TV ONE PROFESSIONAL RACK MOUNT LCD MONITORS These LCD monitors are

LCD1560HDR ...... LCD-1560HD in rackmount kit, 6RU.

available in a variety of screen sizes and input configurations to satisfy most applications.

All LCD panels used are top-grade, professional products. High brightness and contrast ratios are standard features, along with wide viewing angles. LM404HD is 16:9 (800x480) with 1080P playback, all other models have a 4:3 aspect ratio.

ITEM	DESCRIPTION	PRICE
LM404R	.Quad 4", composite and S-video inputs, tilt rackmount	1440.75
LM563R	.Triple 5.6", composite and S-video inputs, tilt rackmount	1695.75
LM701M	.Single 7" with dual composite inputs, metal case, Vesa	505.75
LM1511R	.Single 15" composite, S-video, PC, stereo, XGA tilt	
	rackmount, VESA mount	1270.75
LM1911R	.Single 19" composite, S-video, PC, stereo, SXGA tilt	
	rackmount, VESA mount	1610.75
LM1920R	.Single 19", composite, S-video, PC, stereo, VESA mount	930.75



### **VADDIO PREVIEW RACK MOUNT MONITORS**

Excellent rackmount monitors for a variety of applications that require high resolution monitoring of SD cameras. Each includes 2 or more monitors in a 3RU enclosure with tilt mechanism (PREVIEW-OUAD-4 is 2RU). Color, contrast, brightness, and On/Off controls per LCD (except PREVIEW-QUAD-4). The SD monitors offer active matrix LCD screens and inputs with active looping outputs on BNC connectors.

TEM	DESCRIPTION	PRICE
PREVIEW-DUAL-6.4	Dual 6.4" LCD rack mount monitor, 3RU	1345.00
PREVIEW-TRIPLE-5.6	Triple 5.6" LCD rack mount monitor, 3RU	1255.00
PREVIEW-QUAD-4	Quad 4" LCD rack mount monitor, 2RU	1165.00

## VariZoom

### VARIZOOM VZ-TFT7 16:9 7" ON-CAMERA

MONITOR An external video display allowing more free movement away from camera with a generous 30°/60° viewing angle. Can use for most aspect ratios and has RCA video and 2.1mm 12V DC input. 10W max power consumption. Includes AC adapter and 4' RCA cable.

•		
ITEM	DESCRIPTION	PRICE
VZ-TFT-7	7" 16:9 on-camera monitor with video cable and universal power supply	. 195.57
VZ-TFT-7U	7" 16:9 on-camera monitor with case, 702M battery kit, shoe and sunhood .	. 323.49