

# 32" & 26" Free-standing HD LCD Monitors

LCD-3200HD

LCD-3200HDL

LCD-2600HD



LCD-3200HD

Shown without detachable speakers.



LCD-3200HDL



LCD-2600HD

- HD compatible (supports 480p/i, 720p, 1080i)
- PIP: Picture in picture capability
- LCD-3200HD: 2 detachable speakers provide 3D MTS stereo  
LCD-2600HD: 2 built-in 10W speakers provide 3D MTS stereo
- Hard anti-glare coating enhances viewing
- Composite, S-Video, component, DVI, PC, HDMI, RS-232
- Black cases made of durable ABS plastic
- Wide viewing angle
- Active matrix technology eliminates distortion
- Built-in removable desk stand
- Built-in power supply 100-240VAC, 50/60 Hz
- Closed-caption and V-chip features
- IR remote control works within 30 feet
- RS-232 serial port control
- Widescreen 16:9 aspect ratio, 4:3, zoom
- 3D-comb filter
- Environmentally safe: RoHS compliant, no x-radiation, power-saving feature

Resolution: 1366 (H) x 768 (V) dots  
Brightness rating: 500 cd/m<sup>2</sup> (Nit)  
Contrast Ratio: 800:1

Display: LCD-3200HD: 32.0" TFT LCD active matrix  
LCD-2600HD: 26.0" TFT LCD active matrix

Input Signal: Composite NTSC/PAL, S-Video,  
analog RGB, component, HDMI, DVI

PC compatibility: IBM compatible

Colors: 16.7M

Viewing angle L/R/T/B: 85/85/85/85 degrees

Number of Pixels: 983,040

Response Time:(rising/falling) : LCD-3200HD: 12/12mS, LCD-2600HD: 15/5mS

LCD-3200HD: Dimensions (WHD): 1026 x 536 x 231mm / 40.4" x 21.1" x 9.1"

LCD-2600HD: Dimensions (WHD): 804 x 536 x 230mm / 31.6" x 21.1" x 9.1"

LCD-3200HD: Dimensions w/o speakers & deskstand (WHD): 804 x 496 x 120mm / 31.7" x 19.5" x 4.7"

LCD-2600HD: Dimensions w/o deskstand (WHD): 804 x 496 x 120mm / 31.7" x 19.5" x 4.7"

Actual visible screen size (WH): LCD-3200HD: 698.5 x 393.7mm / 27.5" x 15.5"

LCD-2600HD: 567 x 340mm / 22.3" x 13.4"

Operating temperature/humidity: 50 ~ 104°F / 10 ~ 40°C, 20% ~ 90% humidity

Power Requirements: 100~240VAC / 50~60 Hz

Power Consumption: 130W (max.)

Rear Terminal Connections: 2 composite RCA Video IN

Component: RCA YPbPr & R/L audio inputs, and  
RCA Y/Cb/Cr & R/L audio inputs,

2 S-Video IN

Audio: 2 RCA R/L audio inputs, PC audio IN, and  
RCA audio R/L outputs

PC: RGB 15-pin D-sub

HDMI, DVI, RS-232: 9-pin

Power: AC IN

LCD-3200HD: Weight: Net: 16 kg./ 35 lbs.

Gross: 24 kg./ 52 lbs.

LCD-2600HD: Weight: Net: 15.1 kg./ 33 lbs.

Gross: 19 kg./ 42 lbs.

## Flush-mounted 32" HD LCD Monitor

### Model LCD-3200HDL:

Dimensions (WHD): 33.4" x 21.4" x 9.1"

Installer's Cut-out (WH): 31.5" x 20"

Distance between horizontal mounting holes: 32-3/8"

## Optional Accessories

PLT-2300	VESA conversion plate (for landscape & portrait positioning)
WM-3018VT	Fixed wall mount bracket
WM-4200VT	4-way pan/tilt wall mount bracket (order w/ PLT-2300)
WMC-2342	Ceiling mount (order w/ PLT-2300)