

LCD-1560HD Free-Standing Monitor

LCD-1560HDL Flush Mount Monitor

LCD-1560HDR Rack Mount Monitor

MODEL NUMBERS

LCD-1560HD	
LCD-1560HDL	Monitor in Flush Mount Kit
LCD-1560HDR	Monitor in Rack Mount Kit

DESCRIPTION

HD compatible (supports 480p/i, 720p, 1080p/i)
RS-232 feature allows external devices to control the monitor through the serial port
Underscan capability/Blue screen feature
Displays 16:9 and 4:3
Front controls for power menu, up/down, select
On-screen display for: brightness, contrast, back light, hue, volume
IR remote control - Rear IR Jack allows direct connection for use with IR repeater systems.
IB Composite x 2, S-Video, component HDMI, and PC capability
Low power consumption
Case made of durable black metal
Active matrix technology allows wide viewing angle & eliminates distortion
Anti-glare surface treatment provides enhanced viewing pleasure
Built-in removable desk stand included
Response Time: 8mS
Built-in interface for wall mounting VESA 75mm FPMPMI compliant

OPTIONAL ACCESSORIES

HM-400	Under-cabinet hinge mount
WM-30	Wall mount bracket (fixed)
WM-302	Wall mount with swing arm & 4-way adjustable
WMC-2342	Ceiling mount

SPECIFICATIONS (LCD-1560HD)

Resolution	1336 (H) x 768 (V) dots
Brightness Rating	250 cd/m ² (Nit)
Dot Pitch	0.252 (H) x 0.252(V)mm
PC Compatibility	XGA, SVGA, VGA, MAC II
Contrast Ratio	500:1
Display	15" TFT LCD active matrix
Back Light	CCFT
Input Signal	Composite NTSC/PAL (auto switching), S-Video, Analog RGB, component, HDMI
Colors	8-bit, 144, 16.2m
Number of Pixels	1,049, 088 dots
Pixel Configuration	Stripe
Input Signal Level	1.0V P-P (positive) 75 Ohm
Viewing angle (L/R/T/B)	90/90/65/65
Speakers	8 ohms, 2 W, 28 x 40mm oval type x 2
Speaker Amplifier	5 W x 2 @ 10% THD, 100 mV
1560HD w/desk stand	380 x 295 x 45mm / x 11.6"
w/o desk stand	380 x 255 x 45mm / x 10.0"
1560HDR Dimensions	(WHD) 19" x 10.5" (Occupies 6 RU)
1560HDL Flush Mount	(WHD) 16.5" x 11.4" x 2.0" / .8"
Installers Cut-Out (WH)	14-3/4" x 10-1/8"
Visible Screen Size (WH)	344.2 x 193.5mm / 13.6" x 7"
Operating Temperature	32~122°F or 0~50°C
Power Requirement	Regulated 12VDC, 3A, negative ground Part No. DC-1500 required for use in vehicles
Power Consumption	12 W (max)
Includes Switching Power Supply	100 ~ 240VAC, 47/63Hz
Rear Connections	Component RCA y/Pb/Pr jacks PC 15-pin mini D-sub (female), External IR jack, RS-232P 9-pin IN jack, 3.5 audio line out, BNC video IN/OUT, S-Video jack 4 RCA IN jacks (composite x2, audio L/R), 3.5 stereo audio jack and RCA video OUT jack for video 1 or 2
Screw-down connections	R/L external speaker output, 12 VDC input
LCD-1560HD Weight	Net 3.2 kg / 7.05 lbs Gross 6.72 kg / 14.82 lbs
LCD-1560HDL Weight	Net 3.2 kg / 7.1 lbs Gross 5 kg / 11 lbs
LCD-1560HDR Weight	Net 2.8 kg / 6.15 lbs Gross 5 kg / 11 lbs

GSA Schedule 3S-07F-0069L, SIN: 246-42(1), 246-50