

LCD-1212T Free-Standing TV



LCD-1212TL Flush Mount TV



LCD-1212TC Counter Mount TV



LCD-1212TW Wall Mount



**MODEL NUMBERS**

LCD-1212T	Free-Standing TV
LCD-1212TC	Counter Mount TV
LCD-1212TL	Monitor in Flush Mount
LCD-1212TW	Wall Mount TV

**DESCRIPTION**

- Cable ready ATSC/NTSC/QAM TV tuner
- All cables concealed for LCD-1212TC and LCD-1212TW
- LCD-1212TC / 1212TW in custom 4-way mounts
- LCD-1212TC Pan/Tilt: 30°/30°/60°/0° (L/R/T/B)
- LCD-1212TW Pan/Tilt: 30°/30°/0°/60° (L/R/T/B)
- Aspect ratio: 16:9
- Front controls for power, menu, channel up/down, volume up/down, mode, mute
- On-screen display for brightness, contrast, tint, H/V position, saturation, sharpness
- Response time: 50mS (rising/falling)
- Wide Viewing angle
- IR remote control
- LCD-1212T case made of durable black ABS plastic. Comes with removable desk stand and conversion plate makes the unit VESA 75mm compliant
- LCD-1212TC case made of durable black ABS plastic and mount is watertight to protect counter and cabinetry
- LCD-1212TL has black metal front with durable ABS plastic back  
Installer's Cut-Out (WH): 11.8" x 8.7"
- LCD-1212TW case made of durable black ABS plastic
- LCD-1212T and LCD-1212TL are powered by external switching power supply
- LCD-1212TC and LCD-1212TW come with built-in AC power (electrician required for connection)
- LCD-1212TW attaches to double gang electrical box

**OPTIONAL ACCESSORIES**

HM-400	Under-cabinet hinge mount
WM-302	4-way adjustable wall mount
WM-30	Fixed and locking wall mount bracket
WM-31	Fixed wall mount bracket

**SPECIFICATIONS (LCD-1212T)**

Resolution	1280(H) x 768(V) dots
Brightness Rating	300 cd/m <sup>2</sup> (Nit)
Dot Pitch	0.2055 (H) x 0.2055(V)mm
PC Compatibility	XGA, SVGA, VGA, MAC II
Contrast Ratio	600:1
Display	12.1" TFT LCD active matrix
Back Light	CCFT
Input Signal	ATSC/NTSC/QAM/CATV
Colors	16.7M
Number of Pixels	983,040 dots
Pixel Configuration	RGB Vertical Stripe
Input Signal Level	1.0V P-P (positive) 75 Ohm
Viewing angle (L/R/T/B)	60/30/20/10 degrees
Speakers	4 ohms, 1 W x 2
LCD-1212T Dimensions (WHD)	300 x 220 x 45mm / 11.8" x 8.7" x 1.8"
LCD-1212TC Dimensions (WHD)	300 x TBD x TBDmm / 11.8" x 8.7" x 6.4"
LCD-1212TL Dimensions (WHD)	337 x 259 x 45.7mm / 13.3" x 10.2" x 1.8"
LCD-1212TW Dimensions (WHD)	300 x 220 x 162.6mm / 11.8" x 8.7" x 6.4"
Actual screen size (WH)	266 x 161mm / 10.5" x 6.3"
Operating temperature	50~104°F or 10~40°C
Power Requirement / Consumption	Regulated 12VDC, 4A, negative ground 60 W (max)
Includes switching power supply	110 ~230 VAC, 50/60Hz, DC 10~16V, 4A
Rear Connections	<b>Composite</b> RCA video IN/OUT jacks <b>TV "F"</b> connector for CATV <b>Audio</b> RCA R/L IN/OUT jacks, 2 headphone jacks <b>Power</b> LCD-1212T / LCD-1212TL 2.1mm DC IN <b>LCD-1212TC / LCD-1212TW</b> Raw wire for AC connection by electrician
LCD-1212T Weight	<b>Net</b> 4.3 kg / 9.5 lbs <b>Gross</b> 6.4 kg / 14 lbs
LCD-1212TC Weight	<b>Net</b> 5.2 kg / 11.5 lbs <b>Gross</b> 7.3 kg / 16 lbs
LCD-1212TL Weight	<b>Net</b> 5.2 kg / 11.5 lbs <b>Gross</b> 7.3 kg / 16 lbs
LCD-1212TW Weight	<b>Net</b> 4.8 kg / 10.5 lbs <b>Gross</b> 6.8 kg / 15 lbs