

## LED-1212T - Front



## LED-1212T

This commercial-grade TV is ideal for retail, sports arena, hospitality and residential applications.

### Benefits

- Widescreen 16:9 native aspect ratio
- ATSC/QAM TV tuner with combined off-air/cable signal capability
- Composite In/Out
- Built-in stereo speakers
- IR remote control

### Accessories

- HM-400 Under-cabinet hinge mount
- WM-302 4-way adjustable wall mount
- WM-31 Fixed wall mount bracket
- WMC-2342 Ceiling mount bracket for 1.5" NPT pipe

### Related Products

- LED-1212TW - Wall Mount Monitor
- LED-1212TC - Counter Mount TV Monitor
- LED-1212TL - Flush Mount TV Monitor
- LED-1212TR - Rack Mount TV Monitor

## LED-1212T - Back



### Specifications

Mount	Wall; Double gang J box; Concealed cables
HD Compatible	Yes
Anti Glare Coating	Yes
V Chip/Closed Caption	Yes
Case	Durable ABS Plastic
Built-in Power Supply	Yes
IR Remote Control	Yes
Native Aspect Ratio	16:9
Visible Screen Size (WH)	263 x 157mm / 10.3" x 6.1"
Resolution	1280 x 768
Brightness Rating	370 cd/m <sup>2</sup> (Nit)
Contrast Ratio	600:1
Back Light	LED (30k)
Dot Pitch	0.2055 (H) x 0.2055 (V)
Color Depth	16.7 M
Number of Pixels	983,040
Response Time	13/12ms (Rising/Falling)
Audio Power / Speakers	4 Ohms, 1 W x 2
Viewing Angle (L/R/T/B)	30/30/20/10
Pixel Configuration	Stripe
Input Signal	ATSC, NTSC, QAM, CATV, composite video
Input Signal Level	1.0V P-P (positive) 75 Ohm
Dimensions w/o Deskstand	320x 220 x 130mm / 12.6" x 8.7" x 5.4"
Operating Temp/Humidity	50 ~ 104°F / 10 ~ 40°C, 20% ~ 90% humidity
Power Requirements	Regulated 12VDC, 4Amps, negative ground
Power Consumption	18 W
Composite	RCA video IN/OUT jacks
Audio	Yes
Power	Raw wire for AC by electrician
Weight	Net: 2.9 kg / 5.25 lbs, Gross: 3.1 kg / 6.7 lbs
GSA	