

LCD-703HD2 - Front



LCD-703HD2 - Back



LCD-703HD2 Rack Mount Monitor

This versatile high-definition monitor is designed primarily for field broadcast and video production, and remote surveillance applications.

Benefits

- Displays HD signals (1080p/i and 720p)
- 16:10 native aspect ratio; displays 15:9 & 4:3
- LED backlight – better color saturation
- Underscan, tally, and blue gun functions
- IR remote control
- RS-232 control

Accessories

Related Products

- LCD-703HD1
- LCD-703HDL
- LCD-703HDLX
- LCD-703HD
- LCD-703HDA
- LCD-703HDV
- LCD-703HDX

Specifications

Mount	Rack: 3 RU
HD Compatible	Yes
Anti Glare Coating	Yes
Selected Color Temp.	No
Case	Metal
Built-in Power Supply	No
IR Remote Control	Yes
180° Rotation Display	No
Native Aspect Ratio	15:9
Visible Screen Size (WH)	152.4 x 91.4mm / 6" x 3.6"
Resolution	800(H) x 480(V) dots
Brightness Rating	350 cd/m ² (Nit)
Contrast Ratio	300:1
Back Light	LED (20 k-30 K)
PC Compatibility	PC via HDMI port
Dot Pitch	0.19(H) x 0.19(V)mm
Colors	384,000
Number of Pixels	1.2 M
Response Time	25ms (Rising/Falling)
Audio Power / Speakers	No
Viewing Angle (L/R/T/B)	65/65/55/60 degrees
Pixel Configuration	Stripe
Input Signal Level	1.0 V P-P (positive) 75 Ohm
Dimensions w/ Deskstand	
Dimensions w/o Deskstand	482 x 133 x 55mm / 19" x 5.25" x 2.2" (3 RU)
Operating Temp/Humidity	10 ~ 104°F / -12 ~ 40°C
Power Requirements	350mA + pin, - ground
Power Consumption	4.2W (max)
Component	BNC IN/OUT
Composite	BNC video IN/OUT
S-Video	IN/OUT
PC	HDMI
HDMI / DVI / RS-232	Yes / No / 9-pin
Audio	No
Power	2.1mm DC IN jack
Weight	Net 2.5 kg / 5.5 lbs Gross 03.2 kg / 7 lbs
RoHS Compliant	Yes
GSA	Yes