

LED-1902HDTL - Front



LED-1902HDTL

A NEW versatile, high-definition, mid-size monitor that is effective for any commercial video use, especially with choice of available mounts.

Benefits

- Displays HD signals (1080p/i and 720p)
- Widescreen (16:9) native aspect ratio
- Durable black steel case
- Built-in speakers
- Built-in removable desk stand
- 75mm pattern for mounting
- IR remote control
- RS-232 Control

Related Products

- LCD-1902HDT Deskstand and wall-mount version
- LCD-1902HDTR Rack-mount version

LED-1902HDTL - Back



Specifications	
Mount	Desk Stand: VESA 75 x 75mm
HD Compatible	Yes
Anti Glare Coating	Yes
V Chip/Closed Caption	Yes
Case	Durable Metal
IR Remote Control	Yes
Native Aspect Ratio	16:9
Visible Screen Size (WH)	409.8 x 230.4mm / 16.1" x 9.1"
Resolution	1366(H) x 768(V)
Brightness Rating	250 cd/m ² (Nit)
Contrast Ratio	1000:1
Back Light	LED (40 K)
PC Compatibility	Yes
Dot Pitch	0.30(H) x 0.30(V)mm
Color Depth	16.7M
Number of Pixels	1,049,088
Response Time	5ms (Rising/Falling)
Audio Power / Speakers	8 ohm, 3.5W, 40 x 71mm oval
Viewing Angle (L/R/T/B)	85/85/80/80
Pixel Configuration	Stripe
Input Signal Level	1.0V P-P (positive) 75 Ohm
3D Comb Filter	Yes
Removable Desk Stand	No
Dimensions	492 x 311 x 51mm/19.375" x 12.25" x 2"
Operating Temp/Humidity	6 ~ 104°F or -14 ~ 40°C
Power Requirements	100 ~ 240 VAC, 50/60Hz
Power Consumption	25.8W
Component	RCA y/Pb/Pr jacks
Composite	1 RCA Video IN
S-Video	IN jack
PC	15-pin mini D-sub
HDMI / DVI / RS-232	x2 / No / 3.5mm
Audio	RCA L/R IN / OUT, 3.5 PC IN
Power	2.5mm DC IN jack
Weight	Net 4.8 kg / 10.6 lbs., Gross 6.9 kg / 15.3 lbs.