

## LED-1902HDT - Front



## LED-1902HDT - Back



## LED-1902HDT

A NEW versatile, high-definition, mid-size monitor that is effective for any commercial video use, especially with choice of available mounts.

### Benefits

- Displays HD signals (1080p/i and 720p)
- Widescreen (16:9) native aspect ratio
- Durable black steel case
- Built-in speakers
- Built-in removable desk stand
- 75mm pattern for mounting
- Rack or Flush mounts available
- IR remote control
- RS-232 Control

### Related Products

- LCD-1902HDTL
- LCD-1902HDTR

### Accessories

- HM-401 Under-cabinet hinge mount
- WM-31 Wall mount bracket (fixed)
- WM-302 Wall mount with swing arm & 4-way adjustable

| Specifications           |  |
|--------------------------|--|
| Mount                    | Desk Stand: VESA 75 x 75mm                       |
| HD Compatible            | Yes  |
| Anti Glare Coating       | Yes  |
| V Chip/Closed Caption    | Yes  |
| Case                     | Durable Metal                                    |
| IR Remote Control        | Yes  |
| Native Aspect Ratio      | 16:9   |
| Visible Screen Size (WH) | 409.8 x 230.4mm / 16.1" x 9.1"                   |
| Resolution               | 1366(H) x 768(V)                                 |
| Brightness Rating        | 250 cd/m <sup>2</sup> (Nit)                      |
| Contrast Ratio           | 1000:1   |
| Back Light               | LED (40 K)                                       |
| PC Compatibility         | Yes  |
| Dot Pitch                | 0.30(H) x 0.30(V)mm                              |
| Color Depth              | 16.7M  |
| Number of Pixels         | 1,049,088  |
| Response Time            | 5ms (Rising/Falling)                             |
| Audio Power / Speakers   | 8 ohm, 3.5W, 40 x 71mm oval                      |
| Viewing Angle (L/R/T/B)  | 85/85/80/80                                      |
| Pixel Configuration      | Stripe   |
| Input Signal Level       | 1.0V P-P (positive) 75 Ohm                       |
| 3D Comb Filter           | Yes  |
| Removable Desk Stand     | Yes  |
| Dimensions w/ Deskstand  | 436 x 307.3 x 127mm/17.2" x 12.1" x 5"           |
| Dimensions w/o Deskstand | 436 x 278 x 49mm/17.2" x 11" x 2"                |
| Operating Temp/Humidity  | 6 ~ 104°F or -14 ~ 40°C                          |
| Power Requirements       | 100 ~ 240 VAC, 50/60Hz                           |
| Power Consumption        | 25.8W  |
| Component                | RCA y/Pb/Pr jacks                                |
| Composite                | 1 RCA Video IN                                   |
| S-Video                  | IN jack  |
| PC                       | 15-pin mini D-sub                                |
| HDMI / DVI / RS-232      | x2 / No / 3.5mm                                  |
| Audio                    | RCA L/R IN / OUT, 3.5 PC IN                      |
| Power                    | 2.5mm DC IN jack                                 |
| Weight                   | Net 5.6 kg / 12.3 lbs., Gross 6.9 kg / 15.3 lbs. |