



LED-4202HDT

This LED-backlit slim design monitor with tuner features the latest technology with enhanced picture clarity and sharpness for both analog and digital video signals.

Benefits

- ADA compliant slim design with only 16mm (2.4") depth
- True HD (1080p/i) with no downscaling
- LED backlight – brighter picture using less power
- Great picture quality - 10 Bit / 120Hz
- Wide viewing angle (89/89/89/89)
- ATSC / QAM Tuner
- Widescreen (16:9) native aspect ratio
- Built-in stereo speakers
- Built-in removable desk stand
- IR remote control
- RS-232 control

Accessories

- WM-3742 Fixed wall mount bracket
- WM- 4200VT 4 way pan/tilt wall mount bracket
- WMC- 2342 Ceiling mount bracket (order with PLT2300)



Specifications	
Mount	VESA 200 x 200 mm
HD Compatible	Yes
Anti Glare Coating	Yes
V Chip/Closed Caption	Yes
Selectable Color Temp.	Yes
Case	Durable ABS Plastic
Built-in Power Supply	Yes
IR Remote Control	Yes
Native Aspect Ratio	16:9
Visible Screen Size (WH)	914 x 520mm / 36" x 20.5"
Resolution	1920(H) x 1080(V)
Brightness Rating	450 cd/m ²
Contrast Ratio	4000:1
Back Light	LED (60 K)
PC Compatibility	Yes
Dot Pitch	0.681(H) x 0.227(V)mm
Color Depth	16.7M
Number of Pixels	2,073,600
Response Time	6.5ms (Rising/Falling)
Audio Power / Speakers	8W x 2 / 8W + 8W
Viewing Angle (L/R/T/B)	89/89/89/89 degrees
Pixel Configuration	Stripe
TV Tuner	Yes
Input Signal Level	1.0V P-P (positive) 75 Ohm
3D Comb Filter	Yes
Removable Desk Stand	Yes
Dimensions w/ Deskstand	1004 x 671 x 250 / 39.6" x 26.4" x 9.8"
Dimensions w/o Deskstand	1004 x 623 x 60 / 39.6" x 24.5" x 2.4"
Operating Temp/Humidity	32 ~ 140°F / 0 ~ 60°C, 20% ~ 90% humidity
Power Requirements	90 ~ 240 VAC, 50/60 Hz
Power Consumption	230W (max)
Component	3 RCA YPbPr
Composite	1 RCA Video IN
S-Video	1 IN
PC	RGB 15-pin D-sub
HDMI / DVI / RS-232	x2 / No / 3.5mm
Audio	3.5 audio input, PC audio IN, and RCA audio R/L outputs
Power	AC IN
Weight	Net 16.4 kg / 36 lbs, Gross 19 kg / 41.8 lbs