

LED-3204HDT - Front



LED-3204HDT

This popular, mainstay monitor is used in a variety of applications including school classrooms displays, HD surveillance, and as suite displays in sports venues.

Benefits

- FHD displays HD signals (1080p/i and 720p)
- ATSC/QAM tuner
- Wide viewing angle (89/89/89/89)
- Widescreen (16:9) native aspect ratio
- Stereo speakers with surround sound
- Built-in removable desk stand
- IR remote control
- RS-232 control

Accessories

- WM-3742 Fixed wall mount bracket
- WM- 4200VT 4 way pan/tilt wall mount bracket
- WMC- 2346 Ceiling mount bracket

LED-3204HDT - Side



Specifications	
Mount	Desk Stand: VESA 200 x 100mm
HD Compatible	Yes
Anti Glare Coating	Yes
V Chip/Closed Caption	Yes
Selectable Color Temp.	Yes
Case	Durable ABS Plastic
Built-in Power Supply	Yes
IR Remote Control	Yes
Native Aspect Ratio	16:9
Visible Screen Size (WH)	698.5 x 393.7mm / 27.5" x 15.5"
Resolution	1920(H) x 1080(V)
Brightness Rating	400 cd/m ²
Contrast Ratio	4000:1
Back Light	LED (30 K)
PC Compatibility	Yes
Dot Pitch	0.51075(H) x 0.51075(V)mm
Color Depth	16.7M
Number of Pixels	983,040
Response Time	6.5ms (Rising/Falling)
Audio Power / Speakers	10W x 2 / 8Ohm
Viewing Angle (L/R/T/B)	89/89/89/89
Pixel Configuration	Stripe
TV Tuner	Yes
Input Signal Level	1.0V P-P (positive) 75 Ohm
3D Comb Filter	Yes
Removable Desk Stand	Yes
Dimensions w/ Deskstand	772 x 540 x 230mm / 30.4" x 21.3" x 1.8"
Dimensions w/o Deskstand	772 x 492 x 45mm / 30.4" x 19.4" x 1.8"
Operating Temp/Humidity	32 ~ 122°F / 0 ~ 50°C, 20% ~ 90% humidity
Power Requirements	100 ~ 240 VAC, 50/60 Hz
Power Consumption	<60W
Component	3 RCA YPbPr
Composite	1 RCA Video IN
S-Video	1 IN
PC	RGB 15-pin D-sub
HDMI / DVI / RS-232	x2 / No / 3.5mm
Audio	2 RCA R/L audio inputs, 3.5 PC audio IN, and RCA audio R/L outputs
Power	AC IN
Weight	Net 10.6 kg / 23.3 lbs, Gross 12.8 kg / 28.2 lbs