

## LED-1212TL - Front



## LED-1212TL

This commercial-grade TV is ideal for retail, sports arena, hospitality, elevator and residential applications.

### Benefits

- Widescreen 16:9 native aspect ratio
- ATSC/QAM TV tuner with combined off-air/cable signal capability
- Composite In/Out
- Built-in stereo speakers
- No front controls
- IR remote control

### Related Products

- LED-1212T - Free-Standing Monitor
- LED-1212TW - Wall Mount TV Monitor
- LED-1212TR - Rack Mount TV Monitor
- LED-1212TC - Counter Mount TV Monitor

### Specifications

Mount	Flush
HD Compatible	Yes
Anti Glare Coating	Yes
V Chip/Closed Caption	Yes
Case	Durable ABS Plastic/metal
IR Remote Control	Yes
Native Aspect Ratio	16:9
Visible Screen Size (WH)	263 x 157mm / 10.3" x 6.1"
Resolution	1280 x 768
Brightness Rating	370 cd/m <sup>2</sup> (Nit)
Contrast Ratio	600:1
Back Light	LED (30k)
Dot Pitch	0.2055 (H) x 0.2055 (V)
Color Depth	16.7 M
Number of Pixels	983,040
Response Time	13/12ms (Rising/Falling)
Audio Power / Speakers	4 Ohms, 1 W x 2
Viewing Angle (L/R/T/B)	30/30/20/10
Pixel Configuration	Stripe
Input Signal	ATSC, NTSC, QAM, CATV, composite video
Input Signal Level	1.0V P-P (positive) 75 Ohm
Dimensions w/o Deskstand	368x 281 x 55mm /14.5" x 11.1" x 2.2"
Operating Temp/Humidity	50 ~ 104°F / 10 ~ 40°C, 20% ~ 90% humidity
Power Requirements	Regulated 12VDC, 4Amps, negative ground
Power Consumption	18 W (max)
Composite	RCA video IN/OUT jacks
Audio	Yes
Power	2.1mm DC IN jack
Weight	Net: 5.2 kg / 11.5 lbs, Gross: 7.3 kg / 16 lbs
GSA	<b>GSA</b>

## LED-1212TL- Back

