

TANNOY **TS8** & **TS10**

ACTIVE SUBWOOFERS

Complement your home theater or studio system with a powerful subwoofer from the new Tannoy TS Series.

The ultimate performance in either a traditional stereo or 5.1 surround system, the TS8 and TS10 offer power and accuracy that will satisfy even the most discerning customer.

The TS Series utilizes long throw transducers that are carefully designed to maximize the low frequency extension while maintaining the ability to deliver high sound pressure levels required by today's music and film soundtracks.

The TS Series employs state of the art electronic circuitry to control and integrate into a 2-channel or 5.1 system and provide increased dynamics and a cleaner transient response.

The result is a system that provides the accurate, musical bass dynamics needed for today's modern recordings and soundtracks with the impact and depth that was intended.



TANNOY
TS8



TANNOY
TS10



TANNOY TS8 & TS10

ACTIVE SUBWOOFERS

Specifications	TS8	TS10
Output Power	200W RMS	300W RMS
Low Frequency Response (-6dB)	32Hz	29Hz
Limit for usable output	18Hz	16Hz
Inputs	2 x line level phono 2 x XLR balanced	2 x line level phono 2 x XLR balanced
Outputs	2 x XLR balanced (direct or 80Hz HIPASS)	2 x XLR balanced (direct or 80Hz HIPASS)
Input Filter	2nd order low pass, 50Hz - 150Hz, -6dB	2nd order low pass, 50Hz - 150Hz, -6dB
Auto Mute	After approximately 12 mins. in absence of input signal	After approximately 12 mins. in absence of input signal
Driver Type	200mm (8")	250mm (10")
Enclosure Type	Closed Box	Closed Box
Enclosure Volume	12.5 litre / 0.45cu.ft	16.75 litre / 0.6cu.ft
Additional Features	Phase control Crossover defeat switch for LFE operation Soft limiting to avoid overload LF extension control	Phase control Crossover defeat switch for LFE operation Soft limiting to avoid overload LF extension control
Enclosure (HxWxD) - including feet	292 x 280 x 255mm 11 ¹ / ₂ " x 11 ¹ / ₂ " x 10"	323 x 286 x 286mm 12 ¹ / ₁₆ " x 11.3" x 11 ⁵ / ₁₆ "
Enclosure Weight	7.0kg / 15.4 lbs	9.5kg / 21 lbs
Mains Voltage	120V nominal AC ~, 60Hz 230V nominal AC ~, 50Hz	120V nominal AC ~, 60Hz 230V nominal AC ~, 50Hz
Mains Fuse	120V - T2AL / 250V 230V - T1AL / 250V	120V - T3.15AL / 250V 230V - T1.6AL / 250V
Maximum Power Consumption	275VA	416VA

TANNOY
TS8



TANNOY
TS10



TANNOY

Tannoy United Kingdom | T: +44 (0) 1236 420199 | F: +44 (0) 1236 428230 | E: enquiries@tannoy.com
Tannoy North America | T: (519) 745 1158 | F: (519) 745 2364 | E: inquiries@tannoyna.com

tannoy.com