



LED-2152HSDI

This high performance LED-backlit monitor features the latest technology with enhanced picture clarity and sharpness which is ideal for professional broadcast production and HD-SDI video surveillance.

Benefits

- Full HD (1080i/p) with no downscaling
- LED backlight: brighter picture, less power, longer life
- Great picture quality with motion adaptive 3D De-Interlacer, digital noise reduction and 4H Comb filter Y/C separation
- HD-SDI Input and Output (Loop-through)
- Wide viewing angle (85/85/80/80)
- Built-in removable desk stand

Specifications

Mount	VESA 100 x 100mm; removable desk stand
Monitor Size	21.5" (Diagonal) TFT Active Matrix Flat Panel Display
Back Light	LED (50K)
HD Compatible	1080i/p
Anti Glare Coating	Yes
Case	Durable ABS Plastic
Visible Screen Size	18.76" x 10.5" / 476.6 x 268.1mm
Native Aspect Ratio	16:9
Resolution	1920(H) x 1080(V)
Brightness Rating	250 cd/m ²
Contrast Ratio	10,000:1
Response Time	5ms (Rising/Falling)
Color Depth	16.7M
Number of Pixels	2.073M
Pixel Pitch	0.248 x 0.248mm
Viewing Angle (L/R/T/B)	85/85/80/80 degrees
Pixel Configuration	Stripe
Input Signal Level	1.0V P-P (positive) 75 Ohm
3D De-Interlacer	Yes with DNR and 4H Comb Filter
Monitor Desk Stand	Removable
Dimensions w/o Deskstand	20.2" x 13.2" x 2.1" / 513 x 335 x 53.5mm (W x H x D)
Dimensions with Deskstand	20.2" x 15.4" x 6.5" / 513 x 391 x 164mm (W x H x D)
Operating Temperature	32 ~ 104°F / 0 ~ 40°C
Power Requirements	100 ~ 240 VAC, 50/60 Hz; 12VDC/3.3A adapter included
Power Cord	NEMA 5-15; supports up to 10A 250V
Power Consumption	Active 30W Max / Stand-by <3W
HD-SDI Interface	x1 (BNC) Input / x1 (BNC) Output
VGA (PC) Interface	x1 RGB 15-pin D-sub
HDMI Interface	x1 Input
Composite Interface	x1 (BNC) Input / x1 (BNC) Output
Audio Interface	RCA x2 L/R Input, PC Audio x1 Input
Built-in Speakers	Yes, 1.5W x 2
Remote Control	Infrared
Weight	Net: 7.7 lbs / 3.5kg ; Gross: 11.4lbs / 5.2kg

Specifications are subject to change.