



SPLITTER-L **(SP1X3LUNT)**

The SPLITTER-L provides one direct and two transformer isolated outputs from one mic level input through an ultra-high quality Lundahl transformer.

INPUT

Female XLR input jack for connection of a low impedance balanced signal such as that from a microphone.

DIRECT OUT, ISO 1 and ISO 2 (Male XLR Jacks)

The DIRECT OUT is a straight through connection from the input jack and will pass phantom power. The ISO 1 and ISO 2 outputs each provide a low impedance balanced output signal through a Lundahl LL1581XL transformer and WILL NOT pass phantom power.

GND / LIFT (Buttons X 2)

Disconnects the ground between the corresponding input and ISO output when set to the LIFT position. Ground remains connected when set to the GND position. The DIRECT OUTPUT always has a connected ground.

PAD / OFF button engages a -20dB pad on the input for reducing the possibility of overdriving the unit with strong input signals.

This product is warranted to be free of defects in materials or workmanship to the original purchaser for a period of 3 years from the date of purchase. Should warranty service be required, return the unit postage paid along with the original sales receipt to:

Whirlwind Music Dist., Inc.
99 Ling Road
Rochester NY 14612

Whirlwind will, at its option, repair or replace the unit. This warranty does not cover damage resulting from abuse, unauthorized modifications or use of the product in unintended applications.

