

# The Biggest Thing in LCD Field Monitors

# LCD-562



BB-5000 Anton-Bauer Battery Pack



Shown with MB-1 Desk Stand



Side View

## Active Matrix 5.6" Color LCD Monitor

- Battery pack for field monitor use included
- Ideal for troubleshooting system setup/fault location
- Slim space saving design
- For color and B&W applications
- Compact and light weight for easy installation or mobile use
- Low power consumption
- Case made of durable ABS plastic
- Active matrix technology allows wide viewing angle
- Active matrix technology eliminates distortion
- Manual controls for tint, color, brightness
- Battery pack provides approximately 2.5 hrs operation
- Battery pack holds 8AA or 10 NiCad rechargeable batteries (batteries not included)

### Optional Accessories

AC-2000	AC adaptor
BB-5000	Metal bracket for Anton-Bauer batteries (shown above)
DC-12	Car cord
DC-12D	Dual car cord
HS-1	Hot Shoe mount
MB-1	Desk Stand (shown above in side view)
MB-72M	Metal Mounting Bracket
TB-565	Custom Totebag with sun shield
WM-1	Wall mount bracket

Display: 5.6" TFT LCD active matrix  
Black Light: Built-in (CCFT)  
Input Signal: NTSC/PAL (switchable dual capability)  
Dot Format: 960(H) x 234(V) dots  
Dot Pitch: 0.120mm(H) x 0.360mm(V)  
Brightness rating: 200 cd/m<sup>2</sup> (Nit)  
Number of Pixels: 224,640 Dots  
Contrast Ratio: 100 : 1  
Viewing angle L/R/T/B: 40°/40°/10°/30°  
Pixel Configuration: Stripe  
Power Requirements: 12VDC ~ 15VDC, 1000mA, +pin, - ground  
Power Consumption: 6.5 W  
Input Signal Level: 1.0V P-P (positive) 75 Ohm  
Dimensions w/ pack (WHD): 158 x 130 x 55mm / 6.2" x 5.1" x 2.2"  
Dimensions w/o pack (WHD): 158 x 130 x 42mm / 6.2" x 5.1" x 1.7"  
Actual visible screen size (WH): 116 x 86mm / 4.6" x 3.4"  
Monitor Mounting: Mounting pad with ¼ - 20 threaded socket  
Operating temperature: 23~104°F or -5~40°C  
Storage temperature: -13 ~ 108°F or -25 ~ 60°C  
Connections: BNC video IN/OUT (female) jacks  
2.1mm DC IN jack  
Weight: 440g / 15.4 oz.

GSA Schedule

GS-07F-0069L, SIN: 246-42(1), 246-50

Specifications subject to change without notice

©2004 ToteVision

10K

Available through:

**For BNC IN/OUT order model  
LCD-565 (no audio)**

1319 Dexter Ave. N. • Ste. 020 • Seattle, WA 98109  
Tel: 206-623-6000 • FAX: 206-623-6609  
E-mail: sales@totevision.com  
http://www.totevision.com

**TOTE  
VISION®**