



LED-1561TL

15.6" LED-backlit, flush mount LCD monitor with built-in ATSC/QAM digital TV tuner has optimal picture quality with native Full HD resolution (1920 x 1080). This latest generation model is ideal for any small screen, high quality video installations. For hotel applications, this model includes hotel TV functions, pro:idiom, and a MPI port for head-end connectivity.

Benefits

- Displays native Full HD signals (1080i/p) with no downscaling
- LED backlight: brighter picture using less power
- Hotel TV Functions: default input source, default TV channel, max volume, keypad lock, and cloning through USB
- Built-in speakers

Related Products

- LED-1561T: HD LCD Monitor
- LED-1561TR: Rack-mount version of LED-1561T

Specifications	
Mount	Flush Mount
HD Compatible	Yes
Anti Glare Coating	Yes
Case	Durable ABS Plastic; Flush Frame: Metal
IR Remote Control	Yes
Native Aspect Ratio	16:9
Visible Screen Size (WH)	13.6" x 7.6" / 345 x 195mm
Resolution	1920(H) x 1080(V) (Full HD)
Brightness Rating	220 cd/m ² (Nit)
Contrast Ratio	400:1
Back Light	LED (30K)
Dot Pitch	0.215(H) x 0.215(V)mm
Color Depth	16.7M
Number of Pixels	2,073,600
Response Time	8ms (Rising/Falling)
Audio Power / Speakers	8 Ohm, 2 Speakers x 5 Watts
Viewing Angle (L/R/T/B)	70/70/60/60 degrees
ATSC/QAM Digital Tuner	x1 RF Input
Encryption	Pro:idiom
3D Comb Filter	Yes
Dimensions	16.7" x 11.4" x 1.9" / 424.2 x 289.6 x 48mm
Operating Temp	32 ~ 104°F / 0 ~ 40°C
Humidity	10% ~ 90%
Power Requirements	Regulated 12VDC; 3A; Negative Ground
Power Consumption	30 Watts (Max)
Composite	x1 RCA Input
HDMI	x1 Input
MPI Port	x1 RJ-45 Input for PPV / VOD control
USB	x1 Input
Audio	x1 RCA L/R Input / Output
Power	x1 2.1mm DC Input
Weight	Net: 3.6 lbs / 1.6 kg; Gross: 5.9 lbs / 2.7 kg

Specifications subject to change.