

The Biggest Thing in LCD Field Monitors

LCD-410



*Shown with optional
desk stand*

Active Matrix 4" Color LCD Monitor

- Battery pack for field monitor use included
- Ideal for troubleshooting system setup/fault location
- Snap on battery pack holds 8AA Alkaline or 9 Nicad rechargeable batteries (batteries not included)
- Compact and light weight for easy installation or mobile use
- Controls for tint, color, brightness and audio volume
- For color and B&W applications
- Low power consumption
- Case made of durable ABS plastic
- Active matrix technology allows wide viewing angle
- Active matrix technology eliminates distortion
- Battery pack provides 5.5hrs operation (approximately)
- Response Time: 30ms/50ms (Rising/Falling)

Optional Accessories

AC-1000	A/C adaptor
DC-12	Car Cord
DC-12D	Dual Car Cord
HS-1	Hot Shoe mount
MB-1	Desk Stand (shown above)
MB-72M	Metal mounting bracket
TB-410	Custom Totebag with sun shield
WM-1	Wall mount bracket

Display: 4" TFT LCD active matrix

Back Lights: Built-in (CCFT)

Input Signal: NTSC

Resolution: 383(H) x 234(V) dots

Dot Pitch: 0.214(H) x 0.234(V)

Brightness Rating: 100 cd/m² (Nit)

Contrast Ratio: 60:1

Viewing angle L/R/T/D: 45/45/30/10.

Power Requirements: 12VDC, 380mA, + pin

Power Consumption: 5 W

Dimensions w/ pack (WHD): 145 x 117 x 58mm / 5.7" x 4.6" x 2.3"

Dimensions w/o pack (WHD): 145 x 117 x 45mm / 5.7" x 4.6" x 1.8"

Actual visible screen size (WH): 82 x 62mm / 3.2" x 2.4"

Monitor Mounting: Mounting pad with ¼-20 threaded socket

Operating temperature: 50~104°F or 10~40°C

Storage temperature: -13 ~ 108°F or -25 ~ 60°C

Connections: 3.5 A/V IN jack (from BNC video/ RCA audio)

3.5 audio OUT jack (mono)

2.1mm DC IN jack

3.5 video OUT jack (provides active composite video output)

Net Weight: 425g. / 15oz.

Gross Weight: 0.61 kg. / 1.35 lbs.

GSA Schedule

GS-07F-0069L, SIN: 246-42(1), 246-50

Specifications subject to change without notice

©2005 ToteVision

10K

Available through:

1319 Dexter Ave. N. • Ste. 020 • Seattle, WA 98109

Tel: 206-623-6000 • FAX: 206-623-6609

E-mail: sales@totevision.com

http://www.totevision.com

**TOTE
VISION**