

The Biggest Thing in Little LCD Monitors

LCD-501 LCD-501X3



Active Matrix 5"
Color LCD Monitor



LCD-501X3 19" Rack Mount Kit

- Wide operating power range (10 ~ 30VDC)
- Picture on demand/power saving feature
- Stereo headphone jack for private listening (no built-in speakers)
- Slim space saving design
- For color and B&W applications
- Compact and light weight for easy installation or mobile use
- Low power consumption
- Case made of durable ABS plastic
- Active matrix technology allows wide viewing angle
- Active matrix technology eliminates distortion
- Front controls for color, brightness and audio volume
- A/C adaptor, Part No. AC-2000, included

Optional Accessories

- BB-5000 Metal bracket for *Anton-Bauer* battery
- BC-5000 Charger for *Anton-Bauer* battery
- BP-5000 *Anton-Bauer* Proformer battery
- DC-12 Car Cord
- DC-12D Dual Car Cord
- HS-1 Hot Shoe mount
- LM-BR-501 Brass Flush Mount Kit
- MB-1 Desk Stand
- MB-72M Metal Mounting Bracket
- RM-501 EIA Rack Mount Panel, black metal (shown above)
19"(W) x 5.3"(H) x 0.8"(D) (occupies 3 RU)
Holds 3 monitors.
- WM-1 Wall mount bracket

- Display: 5" TFT LCD active matrix
- Back Light: CCFT
- Input Signal: NTSC/PAL (auto switching)
- Resolution: 600(H) x 234(V) dots
- Active Area: 102.6(H) x 73.9(V)
- Dot Pitch: 0.171(H) x 0.316(V)
- Brightness rating: 240 cd/m² (Nit)
- Number of Pixels: 140,400
- Contrast Ratio: 120:1
- Viewing angle L/R/T/B: 55°/55°/15°/35°
- Pixel Configuration: Stripe
- Power Requirement: 12VDC (1A, + pin)
- Operating Power Range: 10 ~ 30 VDC
- Power Consumption: 7 W (max.)
- Input Signal Level: 1.0V P-P (positive) 75 Ohm
- Audio Input Level: 1.0V P-P
- Audio output: 0.3 W
- Audio Input Impedance: 10K ohm
- Audio Band Width: 15 KHz
- Dimensions (WHD): 146 x 105 x 30.5mm / 5.7" x 4.1" x 1.2"
- Actual visible screen size(WH): 102 x 74mm / 4" x 2.9"
- Monitor Mounting: Mounting pad with ¼-20 threaded socket
- Operating temperature: 50 ~ 104°F or 10 ~ 40°C, 85% RH max.
- Storage temperature: -4 ~ 104°F or -20 ~ 60°C, 85% RH max.
- DIN Cable Connections: RCA video IN
RCA right audio IN
RCA left audio IN
2.1 DC IN jack

LCD-501 Weight: 363g / 12.8oz.
LCD-501X3 Weight: 2.4 kg / 5.3 lbs.

GSA Schedule

Contract GS-07F-0069L SIN: 246-42(1), 246-50

Specifications subject to change without notice

©2004 ToteVision

10K

Available through: