

# The Biggest Thing in LCD Field Monitors

# LCD-565 LCD-562



**LCD-565**

## Active Matrix 5.6" Color LCD Monitor

- Battery pack for field monitor use included
- Ideal for troubleshooting system setup/fault location
- BNC IN/OUT jacks located on top for easy access
- Switch for Auto/Manual color adjustment
- Slim space saving design
- For color and B&W applications
- Compact and light weight for easy installation or mobile use
- Low power consumption
- Case made of durable ABS plastic
- Active matrix technology allows wide viewing angle
- Active matrix technology eliminates distortion
- Manual controls for tint, color, brightness
- Battery pack provides approximately 2.5 hrs operation
- Battery pack holds 8AA or 10 NiCad rechargeable batteries (batteries not included)
- Response Time: 15ms/20ms (Rising/Falling)

### Optional Accessories

- AC-2000 AC adaptor
- BB-5000 Metal bracket for Anton-Bauer batteries (shown above)
- DC-12 Car cord
- DC-12D Dual car cord
- HS-1 Hot Shoe mount
- MB-1 Desk Stand (shown above in side view)
- MB-72M Metal Mounting Bracket
- TB-565 Custom Totebag with sun shield
- WM-1 Wall mount bracket



**LCD- 562  
Unit with Audio**



*BB-5000  
Anton/Bauer bracket*



*Side View*

- Display: 5.6" TFT LCD active matrix
- Black Light: Built-in (CCFT)
- Input Signal: NTSC/PAL (switchable dual capability)
- Dot Format: 960(H) x 234(V) dots
- Dot Pitch: 0.120mm(H) x 0.360mm(V)
- Brightness rating: 200 cd/m<sup>2</sup> (Nit)
- Number of Pixels: 224,640 Dots
- Contrast Ratio: 100 : 1
- Viewing angle L/R/T/B: 40°/40°/10°/30°
- Pixel Configuration: Stripe
- Power Requirements: 12VDC ~ 15VDC, 1000mA, +pin, - ground
- Power Consumption: 6.5 W
- Input Signal Level: 1.0V P-P (positive) 75 Ohm
- Dimensions w/ pack (WHD): 158 x 130 x 55mm / 6.2" x 5.1" x 2.2"
- Dimensions w/o pack (WHD): 158 x 130 x 42mm / 6.2" x 5.1" x 1.7"
- Actual visible screen size (WH): 116 x 86mm / 4.6" x 3.4"
- Monitor Mounting: Mounting pad with ¼ - 20 threaded socket
- Operating temperature: 50~104°F or 10~40°C
- Storage temperature: -13 ~ 108°F or -25 ~ 60°C
- Connections: BNC video IN/OUT (female) jacks  
2.1mm DC IN jack
- Net Weight: LCD-562/565: 440g / 15.4 oz.
- Gross Weight: LCD-562: 0.7 kg./ 1.6 lbs  
LCD-565: 0.6 kg/ 1.3 lbs.

**For audio capability order model LCD-562 (without BNC IN/OUT) shown in inset above.**

**GSA Schedule**  
GS-07F-0069L, SIN: 246-42(1), 246-50

Specifications subject to change without notice

©2005 ToteVision

10K

**Available through:**