


# LCD-1900V



The Biggest Thing  
in LCD Monitors



HM-400  
Under-cabinet bracket



WM-300  
Wall Mount Bracket



Side View

## Active Matrix 19" Color LCD Monitor

- Hot key allows toggling between video, S-Video, component, and PC modes
- **PIP: Picture in picture capability**
- Front controls for : power, menu, select (+,-), adjust (+,-)
- On-screen display for: brightness, contrast, back light, hue, volume
- Slim space saving design
- Composite, S-Video, component, and PC capability
- For color and B&W applications
- Low power consumption
- Case made of durable ABS plastic
- Active matrix technology allows wide viewing angle
- Active matrix technology eliminates distortion
- Built-in removable desk stand included
- Built-in interface for wall or arm mounting  
VESA 100mm FPMPMI compliant
- Includes switching power supply 90-240V, 12V, 50W
- Response Time: 25ms/25ms (rising/falling)

### Optional Accessories

- DC-1500 Factory approved car cord
- HM-400 Under-cabinet hinge mount (shown above)
- WM-30 Wall mount bracket (fixed)
- WM-300 Wall mount with swing arm & 4-way (shown above)
- WM-1700V Wall mount bracket (4-way adjustable)

Touch screen available: order # LCD-1900TS.

- Display: 19.0" TFT LCD active matrix
- Back Light: Built-in (CCFT)
- Input Signal: Composite NTSC/PAL (auto switching), S-Video, Analog RGB
- Resolution: SXGA 1280(H) x 1024(V)dots, Mac 832 x 624 (75Hz)
- PC compatibility: IBM / MAC compatible
- Dot Pitch: 0.294(H) x 0.294(V)mm
- Brightness rating: 250 cd/m<sup>2</sup> (Nit)
- Colors: 16.7M
- Contrast Ratio: 500:1
- Number of Pixels: 1,310,720 dots
- Response Time: 25mS (Tr + Tf)
- Viewing angle L/R/T/B: 80/80/80 degrees
- Pixel Configuration: Stripe
- Input Signal Level: 0.7V P-P (positive) 75 Ohm
- Rear Speakers: 8 ohms, 1W, 28 x 40mm oval type x 2
- Stereo Amplifier: 1 W x 2 @ 10% THD, 100 mV
- Dimensions w/o desk stand (WHD): 444 x 376 x 73mm / 17.5" x 14.8" x 2.9"
- Dimensions w/ desk stand (WHD): 444 x 426 x 215mm / 17.5" x 16.8" x 8.5"
- Actual visible screen size (WH): 376 x 302mm / 14.8" x 11.9"
- Operating temperature: 50~104°F or 10~40°C
- Storage temperature: -4 ~140°F or -20~60°C
- Power Requirement: Regulated 12VDC, 4A, negative ground
- Power Consumption: 48 W (max), 3 W (power saving off mode)
- Rear Terminal Connections: BNC video IN/OUT jack, 3.5 stereo audio IN/OUT jacks, 2.1mm DC IN jack, S-Video jack, 15 pin mini D-sub (female), 9-pin component IN jack
- Net Weight: 7.5 kg / 16.5 lbs.
- Gross Weight: 10 kg. / 22 lbs.



Schedule

GS-07F-0069L, SIN: 246-42(1), 246-50

Specifications subject to change without notice

©2005 ToteVision

50K

Available through: