

MPC-12

12 - Slot Universal Mini-Mod Chassis and Power Supply



MPC-PSF12/16

Universal Power Supply Module

Features

- High capacity fully regulated power supply provides the most efficient performance, ensuring reliability over a wide range of environmental conditions
- High efficiency power supply (over 70%) equipped with cooling fan minimizes power consumption and heat dissipation
- Current overload protection prevents damage to system and prolongs power supply life
- Internal fusing circuitry provides current overload protection and precise voltage regulation, preventing component damage



MPC-BP

Universal-Chassis Blank Plate

Features

- Blocks escape of cool air when used with forced air ventilation systems
- Provides uniform look when not all module slots are filled
- Slides easily into Pico Macom mini-chassis systems and those of other manufacturers



Specifications

Module Capacity	12
Input Voltage Range	90-240VAC
Input Voltage Frequency	47~63Hz
Power Required	68 Watts Each
Output Volt. (V1) @ 4A	5VDC
Output Volt. (V2) @ 4A	12VDC
Efficiency	70%
Line Load Regulation	±1%
Minimum Load	10%
Video Input Conn.	75Ω F-Female

Audio Input Conn.	5KΩ F-Female Unbalance
RF Output Conn.	75Ω F-Female
UR Listed Power Supply	Yes
Operating Temperature	10~50°C

DIMENSIONS

MPC-12/12C	19"(L) x 7.5"(D) x 3.5"(H)
MPC-BP	1"(L) x 4"(D) x 3.4"(H)

WEIGHT

MPC12	7.8 lbs.
MPC-BP	0.4 lbs.

Ordering Information

MPC-12	12 Slot Universal Mini-Mod Chassis and Power Supply
MPC-12C	12 Slot Universal Mini-Mod Chassis Only
MPC-PSF12/16	Universal Power Supply
MPC-BP	Universal-Chassis Blank Plate

Also Available:
MPC-12C
Chassis only

