



## LED-1562HDR

15.6" rack mount, LED-backlit LCD monitor, has optimal picture quality with native Full HD resolution (1920 x 1080). This latest generation model is ideal for any small screen, high quality video installations.

### Benefits

- LED backlight: brighter picture using less power
- Displays native Full HD signals (1080i/p) with no downscaling
- Widescreen (16:9) native aspect ratio
- Multiple connections including HDMI, VGA, RS-232 and USB
- Built-in speakers

### Related Products

- LED-1562HD: 15.6" HD LCD monitor with HDMI, RS-232, VGA and USB
- LED-1562HDL: Flush mount version of LED-1562HD
- LED-1562HDLX: Flush mount version of LED-1562HD with no front controls

Specifications	
Mount	Rack (6RU)
HD Compatible	Yes
Anti Glare Coating	Yes
Case	Durable Metal
IR Remote Control	Yes
Native Aspect Ratio	16:9
Visible Screen Size (WH)	13.6" x 7.6" / 345.4 x 193.04mm
Resolution	1920(H) x 1080(V) (Full HD)
Brightness Rating	300 cd/m <sup>2</sup> (Nit)
Contrast Ratio	600:1
Back Light	LED (30K)
PC Compatibility	Yes
Dot Pitch	0.17925(H) x 0.17925(V)mm
Color Depth	6-bit, 262K
Number of Pixels	2,073,600
Response Time	8ms (Rising/Falling)
Audio Power / Speakers	8 Ohm, 2 Speakers x 5 Watts
Viewing Angle (L/R/T/B)	70/70/60/60 degrees
Digital Signal Processor	3D Comb Filter
Dimensions	18.98" x 10.47" x 1.85"; 482 x 266 x 47mm (6RU)
Operating Temp	32 ~ 104°F / 0 ~ 40°C
Humidity	10% ~ 90%
Power Requirements	Regulated 12VDC; 3A; Negative Ground
Power Consumption	8 Watts (Max)
Composite	x2 BNC Inputs / Outputs
VGA	x1 15-pin mini D-sub Input
HDMI	x1 Input
RS-232	x1 Input
Audio	x1 RCA L/R Input; x1 3.5mm PC Input
Power	x1 2.1mm DC Input
Weight	Net: 5.6 lbs / 2.5 kg

Specifications subject to change.