

Introducing the Micros



World's smallest condenser microphones with integrated preamp and detachable cable.

features

- ▶ Excellent for both recording and live applications
- ▶ Miniaturized integrated preamplifier
- ▶ No additional external power adapter needed
- ▶ Mini-XLR connector
- ▶ 12 mm gold vapor diaphragm
- ▶ Fully balanced for long cable runs (up to 150')
- ▶ Extremely low noise
- ▶ Hi-SPL handling (over 144 dB with M1244)
- ▶ Lightweight



applications

- ▶ Acoustic instruments
- ▶ Ambient room miking
- ▶ Symphonic area miking
- ▶ Overhead mic for choir, group vocal



Model M1244 is Hi-SPL model for close miking drums and other instruments with high sound pressure levels.



M1290 for stereo miking



M1245 with invisible cable hanger

specifications

M1244 / M1245

Transducer Type	Condenser
Frequency Response	80 Hz - 20 kHz
Polar Pattern	Cardioid
(M1245-hc)	Hypercardioid
Output Impedance	250 Ohms
Sensitivity (M1244)	4 mV/Pascal @ 1k
(M1245)	14 mV/Pascal @ 1k
Equivalent Noise Level	19 dBA
Signal to Noise Ratio	75 db
Power Requirements	48-52v phantom
Maximum SPL (M1244)	> 144 dB
(M1245)	> 138 dB
Cable/Connector	Shielded
	12' mini XLR-XLR
Housing	Machined Brass
Weight	.6 oz/17 grams
Length	1.7 inches/45mm



(actual size)

M1290

Transducer Type	Condenser
Frequency Response	40 Hz - 20 kHz
Polar Pattern	Cardioid
(M1290-hc)	Hypercardioid
(M1290-o)	Omni
Output Impedance	250 Ohms
Sensitivity	14 mV/Pascal @ 1k
Equivalent Noise Level	19 dBA
Signal to Noise Ratio	75 db
Power Requirements	48-52v phantom
Maximum SPL	> 138 dB
Cable/Connector	Shielded
	12' mini XLR-XLR
Housing	Machined Brass
Weight	1 oz/28 grams
Length	3.5 inches/90mm



(actual size)

Supplied Accessories

- ▶ 12' high quality 3.3mm cable with mini-XLR (f) -XLR (m) connectors (**CBL-M12**)
- ▶ Mic stand adapter (**MC-MICRO**)
- ▶ Rosewood case



Rosewood Case



CBL-M12



M1290 shown with MC-MICRO mic stand adapter clip

Optional Accessories

- ▶ **CBL-M25** 25' high quality 3.3mm cable with mini-XLR (f) -XLR (m)
- ▶ **CBL-M50** 50' high quality 3.3mm cable with mini-XLR (f) -XLR (m)
- ▶ **HANGER-MICRO** Clip with hanger for overhead use
- ▶ **SMT-MICRO (pictured)** Stand adapter with rubber insulated shockmount
- ▶ **Dclamp-Micro (pictured)** Lug mount attachment with shock mount ring. Applications include hand percussion instruments.
- ▶ **Dvice-Micro (pictured)** Drum rim mount attachment with shock mount ring.
- ▶ **MGN-6** Slim line 6-inch Podium gooseneck stand for Micros. Standard XLR(m) base to mini-XLR(f). For use with all Micros models. Allows Micros to be stored or used for multiple applications.
- ▶ **MGN-12** As above in 12-inch length
- ▶ **MGN-18 (pictured)** As above in 18-inch length



Dclamp-Micro



MGN-18 shown with M1245 mic and AT510 stand

MGN-18 Podium gooseneck stand



Dvice-Micro



HANGER-MICRO



SMT-MICRO

SERVICE AND WARRANTY:

This microphone is under warranty for a period of 1 year from any and all manufacturing defects. Should your microphone fail in any way, please contact the Audix Service department at 503-682-6933. A Return Authorization number is required before returning any products.

CALL: 503-682-6933 FAX: 503-682-7114
www.audixusa.com

Audix Corporation 9400 SW Barber Street, Wilsonville, OR 97070. In Canada, Cabletek Electronics LTD, 604-942-1001 fax 604-942-1010
 © Audix Corporation 2003. All rights reserved. Audix and the Audix logo are trademarks of Audix Corporation.

AUDIX
 PERFORMANCE IS EVERYTHING