

M4315-PRO & M4320-PRO

PROFESSIONAL HOME THEATER

Power Management with Interactive Control
and Real Time Monitoring



M4315-PRO and M4320-PRO

DEDICATED 15 AMP
OR 20 AMP
COMPONENTS



M4315-PRO
(15 Amp)

FEATURES:

- Eight Fully Controllable/Programmable Outlets via RS-232C or BlueBOLT™
- Linear Filtration with Four Isolated Outlet Banks
- Two Front Panel Programmable Reboot Buttons
- IP Control with BlueBOLT-CV1 and RS-232C Cards
- Sleek New Design Including Volt/Amp Meter, Outlet Status and Warning LED's
- Removable Rack Ears (Included)

BlueBOLT™



M4320-PRO
(20 Amp)

BlueBOLT™ Provides Web Based Remote Power Management to Monitor
and Control Your System - From Anywhere, 24/7.

www.panamax.com

PANAMAX®

M4315-PRO



M4320-PRO

M4320-PRO - Two 20 Amp Outlets and Six 15 Amp Outlets. 20 Amp detachable AC power cord (10 ft.).

20 Amp Plug



Front Panel 20A Over Load Breaker



Two 20 Amp Outlets

All other features are common with the M4315-PRO

M4315/4320-PRO SPECIFICATIONS

AC Power

Line Voltage.....	120V, 60Hz
Isolated Banks.....	2
Voltage Regulation.....	No
Total Outlets.....	9 outlets
High Current Outlets.....	2 outlets
Total Current Capacity.....	M4315-PRO 15 A (1800W) - M4320-PRO 20 A (2400W)
Voltage Protection Rating (UL 1449 3rd Edition, 3,000A).....	500V
Protection Modes.....	L-N, L-G, N-G
Initial Clamping Level.....	200V Peak, 141V RMS
Energy Dissipation.....	.2700 Joules
Peak Impulse Current.....	135,000 Amps
Catastrophic Surge Circuit.....	Yes
Thermal Fusing.....	Yes
Auto-resetting Over-voltage shutoff.....	134 VAC ± 2 VAC
Auto-resetting Under-voltage shutoff.....	100 VAC ± 2 VAC
EMI/RFI Noise Filtration	
Banks 1, 2, 3.....	.76db, 5KHz - 250 kHz
Bank 4, High Current Outlets.....	.46 db, 250 KHz - 1 Mhz

LAN Protection

Clamping Level.....	60 ± 5V
Compatibility.....	10/100/1000 BASE-T
Jacks.....	RJ-45
Wires Protected.....	8-Wires

Telco Protection

Fuseless/Auto-resetting.....	Yes
Clamping Level.....	260V
Capacitance.....	30pf (approx.)
Suppression Modes.....	Metallic & Longitudinal
Connectors.....	RJ-11
Lines Protected.....	2-Wire, Pins 4 & 5

Universal Coax Protection

HD 1080 i/p Ready.....	Yes
Bidirectional.....	Yes
Shielded.....	Yes
Clamping Level.....	75V
Frequency Range.....	.0MHz - 2.2 GHz
Insertion Loss.....	< 0.5 dB
Connectors.....	Female "F", Gold Plated

Specifications subject to change due to product upgrades and improvements..

WARRANTIES*

\$5,000,000 Connected Equipment Limited Lifetime Warranty • Limited 3 Year Product Warranty

*Refer to actual warranty documentation for full details.


Why roll a truck when you can reboot from anywhere at anytime!

BlueBOLT™

Reduce service calls and lock-ups with BlueBOLT™ technology.

Online Remote Power Management for Home Theater Systems

PROVIDES: Secure, hosted IP system control and monitoring for the M4315-PRO & M4320-PRO.



Model: BlueBOLT-CV1

(Card Included)

WEIGHTS & MEASUREMENTS, QUANTITIES, UPC'S FOR ORDERING & SHIPPING

PRODUCT DIMENSIONS		Weight
L 12.25" x W 17" x H 1.75"		12 lbs.
19" wide with rack ears		
SINGLE UNIT CARTON		
Dimensions	Qty.	Weight
L 19.25" x W 21.25" x H 4.25"	1	17 lbs.
MASTER CARTON		
Dimensions	Qty.	Weight
L 20.25" x W 21.25" x H 10.75"	2	37 lbs.
UPC'S SINGLE UNIT CARTON		UPC'S MASTER CARTON
M4315-PRO	050616008594	M4315-PRO 50 050616008599
M4320-PRO	050616008600	M4320-PRO 50 050616008605

MODELS: M4315-PRO, M4320-PRO



PANAMAX®

1690 Corporate Circle, Petaluma, CA. 94954 • 800-472-5555 • 707-283-5900

Fax 707-283-5901 • www.panamax.com