HuddleCamHD Webcam

Conferencing Webcam

The HuddleCamHD webcam is an easy to use, Plug-and-Play camera with USB 2.0 connectivity & power.

Model Number: HC-WEBCAM-94

https://huddlecamhd.com/webcam/

KEY FEATURES

- Plug & Play USB power
- USB 2.0
- 1920 x 1080
- 94° Field of View
- Up to 30 fps
- OSD Menu Software





1. Lens 94° Field of View lens

4. Mounting BaseTo mount camera to monitor or 1/4 20 screw

2. LED Indicator

LED is illuminated during use

5. USB 2.0 Cable

For connection to PC USB 2.0 port

3. Microphone Array

Beamforming microphones for high quality pickup

Image Sensor & Lens	
Video CMOS Sensor	1/2.7" CMOS, 2.07 Mega Pixel
Resolution	1080p-30/25, 720p-30/25
Frame Rate	up to 30fps (MJPEG)
Lens	Focus: f=3.1mm
Field of View	94°
Min. Illumination	0.05 Lux @ (F1.8, AGC ON)
Digital Noise Reduction	2D, 3D DNR
Electrical Index	
Input Voltage	5V (USB Power)
Current Consumption	270mA
Power Consumption	1.4W
Working Environment	Indoor

Physical Specifications	
Material	Plastic
Dimensions (in.)	4.6"W x 1.5"H x 1.2"D (not including bracket)
Dimensions (mm)	118 x 37.2 x 30.8 (not including bracket)
Weight	0.36 lbs (0.16 kg)
Box Dimensions	5.4"W x 3.1"H x 3.0"D (137mm x 79mm x 76mm)
Boxed Weight	0.4 lbs (0.18 kg)
Operating Temperature	14°F to 104°F (-10°C to 40°C)
Storage Temperature	-40°F to 140°F (-40°C to 60°C)
Rear Board Connectors	
Video/Power Interface	USB 2.0
Other	
Mfg. Warranty	3 Years Parts & Labor