



TR311HN

AI Auto Tracking

12X NDI PTZ Streaming Camera

NDI[®] | HX



Track. Stream. Collaborate Remotely.

The sleekly designed AVer TR311HN AI Auto Tracking Camera is the affordable solution that uses advanced artificial intelligence (AI) technology to effectively track your speaker or shoot zone without a dedicated camera operator.

The 12X optical zoom and full HD 1080p60 video resolution are ideally suited for distance learning classrooms, houses of worship or training environments. With IP/HDMI/USB output, NDI|HX2 support, PoE+ and Visca & ONVIF control, you have all you need to connect and stream professional quality videos.

Our industry-leading AVerCare warranty program offers 3 years protection and 24-hour replacement to give you total peace of mind.



2 Auto Tracking Modes



12X Optical Zoom



IP/HDMI/USB Output



Support NDI|HX2 Protocol



PoE Supports



Wide Dynamic Range


People Tracking

- Capture every interaction
- Either track full body or half body
- Simple click to track



Zone Tracking

- Establish preset zones
- Create video focused on content
- Enhance the capture of content on multiple displays



Wide Dynamic Range

The Wide Dynamic Range (WDR) of the TR311HN uses special algorithms to balance dark or bright lighting for one clear image.



Tally Light

Simplify multi-camera live video productions with an illuminated red light on the active camera.



AVer's EZLive is a free application that lets users easily record video, livestream, and capture images during real-time video conferencing.



Annotation



Recording



Streaming



Capture

Compatible Software



Product Specifications

Camera	Sensor Size	1/2.8" CMOS
	Pixel	2MP
	Output Resolution	Resolution: 1080p/720p Frame Rate : 60/59.94/50/30/29.97/25
	TV Line	900 (center/wide)
	Focal Length	f = 3.9 ~ 46.8mm
	Iris	F = 1.6 (Wide) ~ 2.8 (Tele)
	Optical Zoom	12X
	Digital Zoom	12X
	Total Zoom	144X
	D FOV	78°(wide)~7°(Tele)
	H FOV	70°(wide)~6°(Tele)
	V FOV	42°(wide)~3°(Tele)
	Minimum Illumination	0.4 lx (50 IRE, F1.6, Max. AGC, 1/30)
	Minimum Working Distance	Wide 0.3m, Tele 1.5m
	Focus	Auto/Manual/One Push
	White Balance	Auto /Manual
	Gain	Auto/Manual
	Shutter Speed	1/1 s to 1/10,000 s
	BLC (Back Light Compensation)	Yes
	Exposure	Auto, Manual, Priority AE(Shutter, IRIS), BLC, WDR
	Noise Reduction	2D/3D NR
	Frequency	50Hz & 60Hz
	S/N Ratio	≥50dB
	Image Effect	Mirror/ Flip Freeze / WDR / BLC
WDR (Wide Dynamic Range)	Yes	
Parameter	Pan Angle	-170°~+170°
	Tilt Angle	-30°~+90°
	Pan Control Speed	0.1 ~ 100°/Sec
	Tilt Control Speed	0.1 ~ 100°/Sec
	Preset Speed	Pan : 200°/Sec, Tilt : 200°/Sec
	Preset Number	10 Locations by Remote, 256 vis RS232
IP Streaming	Resolution (Max)	1080P (60FPS)
	Video Compression	H.264,H.265,MJPEG
	Audio Compression	AAC, G.711,PCM
	Protocol	NDI, IPv6,IPv4, TCP, UDP, ARP, ICMP, IGMP, HTTP, DHCP, RTP/RTCP, RTSP, RTMP,VISCA over IP
	Bitrate	512Kbps ~ 32Mbps
	Bitrate Control Mode	VBR/CBR
	Multi-stream Capability	1080P60 mode: 1080P60 * 1, 1080P60 * 1, 720P10 * 1
	NDI Protocol	NDI HX2
	SRT Protocol	Yes

I/O Interface	Video Output	HDMI, IP, USB	
	Audio Output	HDMI, IP, USB	
	Audio Input	MIC in/ Line in	
	Baud Rate	2400, 4800, 9600, 38400	
	Control Interface	RS-232 / RS-422 / Ethernet	
	Control Protocol	VISCA/PELCO-D (RS232/RS422/IP), CGI (IP)	
	Network Interface	10/100/1000 Base - T	
	USB	3.0	
	POE+	PoE+ (IEEE802.3at)	
	Power Requirements	12V	
USB	Connector	USB3.0 (typeC)	
	Video format	MJPEG, YUV	
	Resolution (Max)	1080P	
	Video Class	UVC 1.1	
Audio	Audio Class	UVC 1.0	
	Channel	2ch (stereo)	
	Codec	AAC-LC (48/44.1/32.24K), G.711/PCM (8K)	
	Security	Kensington slot	
System	Sample Rate	48/44.1/32/24/16/8Khz	
	IR Remote control	Yes	
	Tally	Yes	
	Power Consumption	18W	
	Operating Temperature	0°C ~ +40°C	
	Operating Humidity	20%~80%	
	Storage Temperature	-20°C ~ +60°C	
	Storage Humidity	20% ~ 95%	
	Dimensions	W180*D145*H183.5mm	
	Net Weight	1.7 kg(+/-0.1)	
	Application	Indoor	
	Accessory	Remote control, 12V power adapter, power cable, Din8 to D-Sub9 cable, RS232 in/out cable, screw for mount, ceiling mount, cable fixing plates, quick guide.	
	Warranty	Camera	3 Years
		Accessories	1 Year
Tracking	Mode	Presenter, Zone	
	Mechanism	Human detection (half or full body)	
Ordering Info	Part Number	PATR311HN	

Hardware Specifications



AVer Information Inc. Americas
668 Mission Court, Fremont, CA 94539
Toll free 1.877.528.7824 T 408.263.3828 F 408.263.8132

©2020 AVer Information Inc. All rights reserved.
All brands and logos are trademarks of their respective companies. Specifications subject to change without notice

pro.averusa.com