



SmartBoom® LITE Headset Product Specifications

Electret Microphone Headset Models: PHS-SB11LE-4F, PHS-SB11LE-5M, PHS-SB11LE-U, PHS-SB11LE-DMG

PHS-SB11LE-DMG model is only for use with MicroCom® products.

Overview

The SmartBoom Series of headsets is part of a line of communications headsets that incorporate a convenient flip-up microphone muting feature. Specifically designed for exceptional comfort, flexibility, and durability, SmartBoom headsets deliver unparalleled quality and consistent performance, even in the most demanding professional environments.

SmartBoom LITE Key Features

- Single-ear lightweight design with enhanced on-ear stability and comfort
- Closed back supra-aural (on ear) design
- Flexible, ambidextrous swiveling mic boom
- SmartBoom flip-up microphone mute
- Electret noise-canceling cardioid microphone optimized for voice communications
- Comfort-fit adjustable headband
- Replaceable ear cushion pad, temple pad, and windscreen
- Non-reflective rubberized matte black finish
- Fixed cable (1.5 m/5 ft.)

What's in the Box?

- Headset
- Datasheet
- Magnetic Cable Clip
- Windscreen

Replacement Parts

- SBL-EAR-10PK Ear Pad (10-Pack)
- SBL-PAD-TEM Temple Pad
- SBL-WS-10PK Windscreen (10-Pack)
- PHS-CLIP-6PK Magnetic Cable Clip (6-Pack)


Specification*	SmartBoom LITE
Microphone	
Microphone Type	Electret Condenser
Frequency Response	20–16,000 Hz
Mic Sensitivity	-45 ± 2 dBV/Pa at 1 kHz
Pattern	Unidirectional
Output Impedance	1–1.9 kΩ
Bias Voltage	1.5V~2.2V
Speaker (Headphone)	
Speaker Type	Dynamic
Frequency Response	100–20,000 Hz
Sensitivity at 1 kHz 316 mV	110 dB ± 3 dB SPL
Nominal Impedance	96 Ω ± 15% at 1 kHz
Max Input Power	500 mW
Cables	
Termination at Ear	Fixed
Length	1.52 m (5.00 ft.)
Outside Diameter	4.00 mm (0.15 in.)
Physical Features	
Mic Boom Length	215.90 mm (8.50 in.)
Weight (with cable)	144 g (5.1 oz.)
Connector Options	
PHS-SB11LE-4F	4-Pin Female XLR
PHS-SB11LE-5M	5-Pin Male XLR
PHS-SB11LE-DMG	Dual Mini (3.5 mm TRRS)
PHS-SB11LE-U	Unterminated

PHS-SB11LE-4F AND PHS-SB11LE-DMG PIN CONNECTION		
Wire (Color and Description)	4-Pin Female XLR	Dual Mini
Uncoated Shield (Mic Ground)	1	S (Left)
Brown (Mic +)	2	T (Left)
Red (Speaker -)	3	S (Right)
Orange (Speaker +)	4	R (Right)

PHS-SB11LE-5M PIN CONNECTION	
Wire (Color and Description)	5-Pin Male XLR
Uncoated Shield (Mic Ground)	1
Green (Mic +)	2
Yellow (Speaker -)	3
Red (Speaker +)	4
Blue (Speaker +)	NC



PHS-SB11LE
Single-Ear Lightweight
Headset



3.5 mm Dual Mini (Gold)
TRRS Connector

Pliant Technologies, LLC
205 Technology Parkway
Auburn, Alabama 36830 USA
www.plianttechnologies.com
Phone +1.334.321.1160
Toll-Free 1.844.475.4268 or 1.844.4PLIANT
Fax +1.334.321.1162

* Notice about Product Specifications: While Pliant makes every effort to maintain the accuracy of the information contained in this manual, this information is subject to change without notice. Please check our website for the latest system specifications and certifications.

Copyright ©2019–2020 Pliant Technologies, LLC. All rights reserved. The Pliant® and CrewCom® word marks and the Pliant "P" logo are trademarks of Pliant Technologies, LLC. The SmartBoom® word mark is a trademark of CoachComm LLC. All other trademarks are property of their respective owners.

PHS-SB11LE_DATASHEET_D0000486_C

