

12GSDI-B-B 4K UHD Cable

Video Coax BNC to BNC Assemblies

Built with high quality Canare single-channel BNC cable for fixed and cable reel deployment in studios, OB trucks, and live events, the 12GSDI-B-B cables transmit up to 325 feet.

Features

- Designed for UHD and 4K Video Transport
- SDI Formats: 1.5G, 3G, 6G, 12G
- SMPTE 2082-1 Compliant
- Excellent Attenuation
- Transmits up to 328 ft/100 m
- Terminated with 12G 75 Ohm BNC Connectors
- Elongated Connector Body Design for Better Grip
- Flame Retardant UL 1666 Riser
- Available in Lengths from 3 to 325 Feet



Laird 12GSDI BNC Cable

Specifications

Canare L-5.5CUHD 16AWG Cable

- Highly-Foamed Multi-Layer PE Insulation
- Characteristic Impedance: 75 Ohm
- Inner Cond. Resistance: 12.8 Ohm
- Outer Cond. Resistance: 10.3 Ohm
- Attenuation: 39.1 dB/100m
- Inner Conductor: Annealed Copper
- Outer Conductor 1: Copper Laminated Tape
- Outer Conductor 2: Tinned Annealed Copper Braid >=91%

Specifications

Canare BCP-D55UHD BNC Connectors

- SMPTE ST-2082-1 Compliant
- Characteristic Impedance: 75 Ohm
- Return loss: 15dB@12GHz, 20dB @6GHz & 26 dB@3GHz
- Pull Strength: 200N
- Gold-Plated "Snap Lock" Center Pin & Beryllium Copper Outer Contact
- Position Mark on Body Makes it Easier to Check if Connector is Locked



Mount Marion, NY - 12456

sales@lairddigitalcinema.com • 800-898-0759

www.lairddigitalcinema.com