

HC-EPTZ-NDI-NTG Specifications:

HuddleCam HC-EPTZ-NDI Specifications:

- Camera & Lens Specifications
 - Field of View: 108°
 - Video CMOS Sensor: 1/2.5" CMOS 8.51M Mega Pixel
 - Focal Length: 2.8mm
 - EPTZ Control Methods: IR Remote, VISCA over IP, HTTP-CGI
 - Compression: MJPEG, YUY2, H.264, H.265
 - Frame Rate: 50Hz: 1 ~ 25, 60Hz: 1 ~ 30
 - Min Lux: 0.05 Lux @ F1.8, AGC ON
 - Zoom: 8x Digital Zoom
- Physical Specifications
 - Connection Interface: RJ-45, USB 2.0 (Future use)
 - Material: Aluminum, Plastic
 - Dimensions (HxWxD): 2.36" x 7.63" x 3.66"
 - Weight: 0.7 lbs
 - Input Voltage: DC 12V / PoE (IEEE 802.3af)
 - Operating Temperature 14°F ~ 104°F
 - Storage Temperature -40°F ~ 140°F

Netgear GSM4212P-100NAS Specifications:

- Primary Port Speed : 1 Gigabit
- Number of Ports : 12 (10x 1G, 2x SFP)
- PoE Ports / Budget : 8 PoE+ (30W/port), 125W Budget
- IGMP Support : Enhanced (NETGEAR IGMP Plus™)
- Jumbo Frame Support : Yes, up to 12kb
- Acoustics : Fanless or 30dB@25°C
- Power Consumption : With PoE: 163.9W/559.555Btu/hr; Without PoE: 17.32W/59.13Btu/hr; Standby without any port connection: 8.53W/29.121Btu/hr
- AVB Support : Yes. Electronic license required, activation key sent via email (AVB4212P-10000S)
- Dimensions (WxDxH) : 440 x 200 x 43.2mm
- Weight : 2.85Kg (6.28lb)
-