

The Biggest Thing in LCD Field Monitors

LCD-411 LCD-410



LCD-411
Monitor with BNC

Active Matrix 4" Color LCD Monitor



Right Side



Left Side



LCD-411
Shown with optional
MB-1 desk stand



LCD-410
Monitor with Audio

• **BNC IN/OUT jacks located on top for easy access (with self-termination feature)**

NEW

• **LED backlight provides longer life, uses less power and provides better color saturation**

- Battery pack for field monitor use included
- Ideal for troubleshooting system setup/fault location
- Snap on battery pack holds 8AA Alkaline or 9 Nicad rechargeable batteries (batteries not included)
- Controls for tint, color, brightness (and audio volume for LCD-410)
- Case made of durable ABS plastic
- Battery pack provides 5.5hrs operation (approximately)
- Response Time: 30ms/50ms (Rising/Falling)

**LCD-410 Unit with Audio Capability
(without BNC IN/OUT)
shown in inset above.**

Optional Accessories

- AC-1000 A/C adaptor
- BP-563 Rechargeable 2600mAH battery pack provides approximately 7 hrs of operation.
- DC-12 Car Cord
- DC-12D Dual Car Cord
- HS-1 Hot Shoe mount
- MB-1 Desk Stand (shown above)
- MB-72M Metal mounting bracket
- TB-410 Custom Totebag with sun shield
- WM-1 Wall mount bracket

Display: 4" TFT LCD active matrix

Back Lights: Built-in LED

Input Signal: NTSC/PAL

Resolution: 383(H) x 234(V) dots

Dot Pitch: 0.214(H) x 0.234(V)

Brightness Rating: 100 cd/m² (Nit)

Contrast Ratio: 60:1

Viewing angle L/R/T/D: 45/45/30/10.

Power Requirements: 12VDC, 380mA, + pin

Power Consumption: 5 W

Dimensions w/ pack (WHD): 145 x 117 x 58mm / 5.7" x 4.6" x 2.3"

Dimensions w/o pack (WHD): 145 x 117 x 45mm / 5.7" x 4.6" x 1.8"

Actual visible screen size (WH): 82 x 62mm/ 3.2" x 2.4"

Monitor Mounting: Mounting pad with 1/4-20 threaded socket

Operating temperature: 50~104°F or 10~40°C

Storage temperature: -13 ~ 140°F or -25 ~ 60°C

LCD-411: Connections: BNC video IN/OUT (female) jacks
2.1mm DC IN jack

Net Weight: 425g. / 15oz.

Gross Weight: 0.61 kg. / 1.35 lbs.

**For Rechargeable Battery Pack
order BP-563
to go in TB-410 tote bag**