

The Biggest Thing in Small HD Monitors

LCD-703HD LCD-703HD2



Back View



LCD-703HDL Unit in flush mount kit



LCD-703HD2 Dual Rack Mount Unit

LCD-703HD1 Single Rack unit

Active Matrix 7" Color LCD Monitors

• HD compatible (supports 480p/i, 576p/i, 720p, 1080p/i)

NEW

• LED backlight provides longer life, uses less power and provides better color saturation

• RS-232 feature allows external devices to control the monitor through the serial port.

• Underscan capability

• Blue gun feature provides for easy adjustment of screen display

LCD-703HDL (flush mount unit shown above)

Dimensions (WHD): 215 x 175 x 35mm / 8.5" x 6.9" x 1.4"
Installer's Cut-out (WH): 174 x 134mm / 6.9" x 5.3"

LCD-703HDLX - w/ no LEDs & no controls showing
- (Special Order Only)

- Anti-glare treatment adds to viewing pleasure
- Displays either 16:9 or 4:3 aspect ratio
- Front controls for : menu, up, down, On/Off, mode
- IR remote control
- Case made of durable metal.
- A/C adaptor (Part No. AC-1000) included
- Built-in interface and proper cable exiting for wall or arm mounting VESA 75mm FPMPMI compliant
- Response time: 22mS (Rising), 35mS (Falling)
- Mounting pad with 1/4"-20 threaded socket

GSA Schedule
GS-07F-0069L, SIN: 246-42(1), 246-50

Available 4Q07:
LCD-703HDT
Unit with
ATSC/NTSC tuner
(refer to separate catalog)

- Display: 7" TFT LCD active matrix
- Back Light: LED
- Input Signal: NTSC/PAL (auto sensing)
- Resolution: 800 (H) x 480 (V) dots
- Dot Pitch: 0.19(H) x 0.19(V)mm
- Brightness rating: 350 cd/m² (Nit)
- Contrast Ratio: 300 : 1
- Number of Pixels: 1.2 M
- Viewing angle L/R/T/B: 65/65/55/60 degrees
- Pixel Configuration: Stipe
- Power Requirements: 6~20 VDC, 500mA, + pin, - ground
- Power Consumption: 350mA@ 12 VDC (max)
- Video Input Level: 1.0 V P-P (positive) 75 Ohm
- LCD-703HD: Dimensions (WHD): 174 x 134 x 35mm / 6.9" x 5.3" x 1.4"
(Height including 5mm mounting pad: 134 + 5mm = 139mm)
- LCD-703HD2 Dimensions (WHD): 482 x 133.4 x 55mm / 19" x 5.25" x 2.2", 3RU
- Actual visible screen size (WH): 152.4 x 91.4mm / 6" x 3.6"
- Operating temperature: 10 ~ 104°F / -12 ~ 40°C
- Storage temperature: -13 ~ 140°F / -25 ~ 60°C
- Rear inputs: BNC composite video IN/OUT, S-Video IN/OUT, BNC component IN/OUT, RS-232, Tally, DVI, 2.1mm DC IN jack
- LCD-703HD: Weight: Net: 0.7 kg./ 1.5 lbs. Gross: TBD
- LCD-703HD2: Weight: Net: 2.5 kg. / 5.5 lbs. Gross: TBD
- LCD-703HDS: Weight: Net: 2.0 kg. / 4.4 lbs. Gross: TBD

Field Monitor Kit

Order LCD-703HD KIT for unit with monitor, tote bag, and rechargeable 2600mAH battery pack (approx. 6 hrs. operation).

Optional Accessories

- HS-1 Hot shoe mount
- MB-3 Desk stand
- SS-703HD Sun shield
- TB-703 Custom Tote bag with sun shield for LCD-703HD

1319 Dexter Ave. N. • Ste. 020 • Seattle, WA 98109
Tel: 206-623-6000 • FAX: 206-623-6609
E-mail: sales@totevision.com
http://www.totevision.com

