

LCD-1510V

The Biggest Thing in LCD Monitors

with
RS-232 &
DVI



Shown with LM-1510V Flush Mount

Active Matrix 15.1" Color LCD Monitors

•HD compatible (supports 480p/i, 720p)

•RS-232 feature allows external devices to control the monitor through the serial port.

- Hot key allows toggling between video, S-Video, and PC modes
- PIP: Picture in picture capability
- Front controls for power menu, up/down, +/-
- On-screen display for: brightness, contrast, back light, hue, volume
- Composite, S-Video, component, and PC capability
- Case made of durable ABS plastic
- Built-in removable desk stand included
- Response Time: 30mS/20mS (rising/falling)

Optional Accessories

DC-1500	Factory approved car cord
HM-1215	Under-cabinet hinge mount bracket
HM-400	Under-cabinet hinge mount
LM-1510V	Flush mount kit, Black metal 17" (W) x 15"(H) x 2.4"(D) Installer's Cut-out: 15.5"(W) x 14.8"(H)
PLT-1000	VESA compliant plate (75mm) FPMPMI
WM-30	Wall mount bracket (fixed) (order w/ PLT-1000)
WM-302	Wall mount with swing arm & 4-way adjustable (order w/ PLT-1000)
WM-1000	2-way adjustable wall mount bracket



HM-400



WM-302

Touch screen not available for the LCD-1510V.

Display: 15.1" TFT LCD active matrix

Back Light: Built-in (CCFT)

Input Signal: Composite NTSC/PAL (auto switching),
S-Video, Analog RGB

Resolution: XGA 1024 (H) x 768 (V)dots

PC compatibility: XGA, SVGA, VGA, MAC II

Dot Pitch: 0.297 (H) x 0.297(V)mm

Brightness rating: LCD-1510V: 500 cd/m² (Nit)

Colors: 16.7M

Contrast Ratio: 400:1

Number of Pixels: 786,432 dots

Viewing angle L/R/T/B: LCD-1510V: 60/60/60/60 degrees

Pixel Configuration: Stripe

Input Signal Level: 1.0V P-P (positive) 75 Ohm

Speakers: 8 ohms, 2 W, 28 x 40mm oval type x 2

Speaker Amplifier: 2 W x 2 @ 10% THD, 100 mV

Dimensions w/o desk stand (WHD): 378 x 322 x 60mm / 14.9" x 12.7" x 2.4"

Dimensions w/ desk stand (WHD): 378 x 355 x 162mm / 14.9" x 14" x 6.4"

Actual visible screen size (WH): 309 x 232mm / 12.1" x 9.1"

Operating temperature: 32~122°F or 0~50°C

Power Requirement: Regulated 12VDC, 3500mA, negative ground

Part No. DC-1500 required for use in vehicles

Power Consumption: 35 W (max)

Includes switching power supply: 100 ~ 240VAC, 1A/47 ~63Hz

Rear Terminal Connections: BNC video IN/OUT, S-Video jack

3 RCA IN jacks (composite, audio L/R),

3.5 stereo audio OUT jack, 2.1mm DC IN jack

15-pin mini D-sub (female), 9-pin Component IN jack,

RS-232, DVI

Weight: Net: 4.82 kg. / 10.62 lbs. Gross: 6.72 kg. / 14.82 lbs.

1319 Dexter Ave. N. • Ste. 020 • Seattle, WA 98109

Tel: 206-623-6000 • FAX: 206-623-6609

E-mail: sales@totevision.com

http://www.totevision.com

