

# The Biggest Thing in Big LCD Monitors

# LCD-2003 LCD-2002V Series

Perfect for behind-the-mirror applications.



Side View

## Active Matrix 20.1" Color LCD Monitor

- Hot key and remote control allow toggeling between video input signals
- Component input capability provides superior viewing pleasure
- Aspect ratio: 4:3
- Anti-glare hard coating covers glass surface
- Zoom function
- Wireless remote control
- Handle (removeable) for easy portability
- Dual built-in front speakers for easy listening
- For color and B&W applications
- Low power consumption
- Case made of durable black ABS plastic
- Active matrix technology allows wide viewing angle
- Active matrix technology eliminates distortion
- Switching power supply (AC 90~240V, 50 ~ 60Hz) included
- Built-in removable desk stand included
- Built-in interface and proper cable exiting for wall or arm mounting VESA 100mm FPMPMI compliant
- Response Time: 16ms/16ms (rising/falling)

For unit with cable ready TV tuner order model LCD-2002VT or model LCD-2002TL.

### LCD-2002TL Flush Mount Unit (shown above)

Dimension (WHD): 24" x 16.5" x 2.75"  
 Installer's Cut-Out (WH): 21.75" x 15"  
 Weight: 26 lbs.

### Optional Accessories

- HM-400 Under-cabinet hinge mount (shown below)
- WM-30 Wall mount bracket (fixed)
- WM-302 Wall mount with swing arm & 4-way (shown below)



HM-400



WM-302

- Display: 20.1" TFT LCD active matrix
- Back Light: 4 Built-in CCFTs
- Input Signal: Composite NTSC/PAL (auto sensing for video)  
 S-Video, component,  
 Analog RGB (only for LCD-2002V/VT/TL)
- LCD-2002VT/2002TL RF TV Tuner: Cable ready (NTSC only). channels 1-125
- Resolution: 800(H) x 600(V) dots @ 75 Hz
- Brightness rating: 500 cd/m<sup>2</sup> (Nit)
- Colors: 16.7 M
- Number of Pixels: 480,000 dots
- Contrast Ratio: 500:1
- Viewing angle L/R/T/B: 80/8060/60
- Pixel Configuration: Stripe
- Video Input Level: 1.0V p-p at 75 Ohm
- Audio Input: 400 ± 50mV (rms) at 1 KHz Stereo
- Audio Output: 1V P-P
- Built-in Speakers: 3 W/ channel x 2
- Dimensions w/ desk stand (WHD): 554.8 x 433 x 160mm / 21.8" x 17" x 6.3"
- Dimensions w/o desk stand (WHD): 554.8 x 401 x 80mm / 21.8" x 15" x 2.75"
- Actual visible screen size (WH): 408 x 306mm / 16" x 12"
- Operating temperature: 50 ~ 104°F or 10 ~ 40°C
- Storage temperature: -4 ~ 140°F or -20 ~ 60°C
- Power Requirement: 100 ~ 240VAC, 50/60Hz, 12 VDC, 7A, negative ground
- Power Consumption: 80 W (max)

- LCD-2002V: Rear Down-facing Connectors: 9-pin component IN jack, RCA A/V IN jacks, S-VHS 4-Pin Mini Din IN jack, Audio OUT 3.5 stereo headphone jack, 2.1mm DC IN jack, 24-pin DVI-D (cable for PC connection included), TV Coaxial (threaded F type) for LCD-2002VT and LCD-2002TL

- LCD-2003: Rear Down-facing Connectors: 9-pin component IN jack, RCA A/V IN jacks, BNC composite IN/OUT, S-VHS 4-Pin Mini Din IN jack, Audio OUT 3.5 stereo headphone jack, 2.1mm DC IN jack

Net weight: 5 kg. / 11 lbs.

Gross weight: 6.4 kg. / 14 lbs.

1319 Dexter Ave. N. • Ste. 020 • Seattle, WA 98109  
 Tel: 206-623-6000 • FAX: 206-623-6609  
 E-mail: sales@totevision.com  
 http://www.totevision.com



Specifications subject to change without notice

©2007 ToteVision

60K

Available through: