

The Biggest Thing in Rack Mounted Monitors

LCD-400X4



Back View



Side View

4" LCD in Quad Rack Mount Kit

NEW • LED backlight provides longer life, uses less power and provides better color saturation

- Broadcast quality display
- Space saving design - occupies only 2 RU
- Tilts 90° in the rack for optimum viewing
- Front controls for power, contrast, tint, color, brightness and NTSC/PAL selection
- Composite video loop through capability for all 4 monitors (always active regardless of power). Loop out termination is provided by auto termination switch in the BNC connector
- Self-powered 3 color tally system
- For color and B&W applications
- Low power consumption
- Case made of durable aluminum & steel
- Active matrix technology allows wide viewing angle
- Active matrix technology eliminates distortion
- Single A/C adaptor power supply provides power for all 4 monitors (included)
- Response Time: 10ms/10ms (Rising/Falling)

Display: 4" TFT LCD active matrix

Back Light: Built-in LED

Input Signal: NTSC/PAL Switchable

Resolution: 480(H) x 234(V) dots

Dot Pitch: 0.171(H) x 0.264(V)

Brightness: 250 cd/m² (Nit)

Contrast Ratio: 150:1

Viewing angle L/R/T/B: 45/45/30/10

Power Requirements: 12VDC, 1.5A, + pin

Power Consumption: 60 W

Dimensions (WHD): 482 x 89 x 50mm / 19" x 3.5" x 2"

Actual visible screen size (WH): 82.1 x 61.8mm / 3.2" x 2.4"

Operating temperature: 50 ~ 104°F or 10 ~ 40°C

Storage temperature: -13 ~ 140°F or -25 ~ 60°C

Connectons: BNC video IN jack x 4

BNC video OUT jack x 4

2.1mm DC IN jack

Net Weight: Est. 2.3 kg. / 5 lbs.

Gross Weight: Est. 2.4 kg. / 5.2 lbs.

GSA Schedule

GS-07F-0069L, SIN: 246-42(1), 246-50

Specifications subject to change without notice

©2007 ToteVision

30K

Available through: