The Biggest Thing in LCD TV Monitors




Active Matrix 10.4" Color LCD TV Monitor

- · Cable ready TV tuner
- Built-in AC power contributes to esthetic apperance (electrician required for connection).
- · Custom 4-way mount allows user to position unit for maximum viewing pleasure.
 - LCD-1044TC Pan/Tilt 30°/30°/60°/0° (L/R/T/B)
- LCD-1044TU Pan/Tilt 30°/30°/0°/60° (L/R/T/B)
- LCD-1044TW Pan / Tilt 30°/30°/30°/30° (L/R/T/B)
- · Wall mount and ceiling mount versions attach to double gang electrical box.
- · Wireless remote control
- Dual front speakers for easy listening
- Front controls for power, menu, channel/volume up/down, mode, mute
- On-screen display for : brightness, contrast, tint, H/V position, saturation, sharpness
- Case made of durable black ABS plastic
- · LCD-1044TC is water tight for protection of cabinetry.
- Response time: 20mS (rising), 40mS (falling)

LCD-1044T Stand Alone Model

- · Built-in removeable desk stand included.
- · VESA conversion plat makes this unit 75mm compliant.
- · Powered by external AC adapter
- Optional Accessories for LCD-1044T:
- DC-1500 Factory approved car cord
- HM-400 Under-cabinet hinge mount
- WM-302 Wall mount with swing arm & 4-way adjustable



LCD-1044TW


all cables concealed

HM-400



Schedule For model LCD-1044TC, LCD-1044TU, & LCD-1044TW only. GS-07F-0069L, SIN: 246-42(1), 246-50

LCD-1044T **LCD-1044TC LCD-1044TU LCD-1044TW**



all cables concealed

Display: 10.4" TFT LCD active matrix Back Light: Built-in (CCFT) Input Signal: Composite NTSC/PAL (auto sensing), NTSC CATV (1-181) Resolution: VGA 640 (H) x 480 (V)dots Dot Pitch: 0.4425 (H) x 0.4425(V)mm Brightness rating: 350 cd/m² (Nit) Colors: 16.7M Contrast Ratio: 300:1 Number of Pixels: 307,200 dots Viewing angle L/R/T/B: 70/70/70/40 degrees Pixel Configuration: RGB Vertical Stripe Input Signal Level: 1.0V P-P (positive) 75 Ohm Speakers: 4 ohms, 1 W x 2 LCD-1044T: Dimensions w/o desk stand(WHD): 277 x 245 x 73 mm / 10.9" x 9.6" x 2.9" LCD-1044T: Dimensions w/ desk stand (WHD): 277 x 245 x 93 mm / 10.9" x 9.6" x 3.7" LCD-1044TC: Dimensions (WHD): TBD LCD-1044TU: Dimensions (WHD): TBD LCD-1044TW: Dimensions (WHD): 307 x 342 x 178mm / 12.1" x 13.5" x 7" Actual visible screen size (WH): 201 x 153mm / 7.9" x 6" Operating temperature: 50~104°F or 10~40°C Power Requirement: Regulated 12VDC, 4A, negative ground Power Consumption: 60 W (max) Includes switching power supply: 100 ~ 240VAC, 1A/47 ~ 63Hz Rear Terminal Connections: RCA video IN/OUT jacks, RCA R/L audio IN/OUT jacks, headphone jack x 2 "F" connector for CATV, 2.1mm DC IN jack for LCD-1044T LCD-1044T: Weight: Net: 1.6 kg./3.5 lbs. Gross: 3.3 kg./7.3 lbs. LCD-1044TC: Weight Net: TBD / Gross: TBD LCD-1044TU:Weight: Net: TBD / Gross: TBD

> 1319 Dexter Ave. N. • Ste. 020 • Seattle, WA 98109 Tel: 206-623-6000 • FAX: 206- 623-6609 E-mail: sales@totevision.com http://www.totevision.com

