

The Biggest Thing in Small LCD Monitors

LCD-560 LCD-560L LCD-560LX



LCD-560



LCD-560L



LCD-560LX



LCD-560 Back View



LCD-560L Back View



Video Cable

5.6" LCD in Flush Mount Kit

NEW • LED backlight provides longer life, uses less power and provides better color saturation

- LCD-560 and LCD-560L features 2 composite video inputs with front controls for channels A & B, contrast, tint, color, brightness, and power
- Broadcast quality display
- LCD-560LX: Rear controls: contrast, tint, color, brightness
Front control for power can be disabled by DIP switch
- For color and B&W applications
- DIP switches allow user to select mirror image or Up/Down image for both channels A and B, and "auto ON with power" feature
- Low power consumption
- Case made of durable steel
- Active matrix technology allows wide viewing angle
- Active matrix technology eliminates distortion
- Response Time: 22ms
- 1/4-20 mounting pad included for LCD-560
- VESA 75mm compliant

Display: 5.6" TFT LCD active matrix

Back Light: LED

Input Signal: NTSC/PAL (auto sensing)

Resolution: 960(H) x 234(V) dots

Dot Pitch: 0.118(H) x 0.362(V)

Brightness: 350 cd/m² (Nit)

Contrast Ratio: 300:1

Viewing angle L/R/T/B: 65/65/55/55

Power Requirements: 10 ~ 15 VDC, 0.4 A @ 12 VDC

Power Consumption: 5 W

LCD-560: Dimensions (WHD): 134 x 134 x 21mm / 5.3" x 5.3" x 0.8"

LCD-560L / LCD-560LX: Dimensions (WHD): 174 x 175 x 22mm / 6.8" x 6.8" x 0.9"

Actual visible screen size (WH): 114 x 87mm / 4.5" x 3.4"

Operating temperature: 50 ~ 104°F or 10 ~ 40°C

Storage temperature: -13 ~ 140°F or -25 ~ 60°C

Connectors: Cable w/ 2 female BNC and one 2.1mm DC inputs

Net Weight: LCD-560: 400g

LCD-560L/LX: 700g

GSA Schedule

GS-07F-0069L, SIN: 246-42(1), 246-50

Specifications subject to change without notice

©2007 ToteVision

20K ~ 30K

Available through:

1319 Dexter Ave. N. • Ste. 020 • Seattle, WA 98109

Tel: 206-623-6000 • FAX: 206-623-6609

E-mail: sales@totevision.com

http://www.totevision.com

