



# PRISMA PAR 20

## SPECIFICATIONS / TECHNICAL DATA REV A

### KEY FEATURES

IP65 Rated Exterior High-Power UV Wash Par Luminaire  
20 Degree Narrow Beam Angle  
365nm Peak True UV Wavelength  
Zero Visible Light Output

### SPECIFICATIONS

#### Dynamic Effects

- . 20° Beam Angle
- . Variable Dimming Curve Modes
- . High Speed Electronic Strobe
- . Beam Uniformity
- . LCD Display
- . (12) 2W High Power UV Diode Led's
- . 20,000 Hour Average Led Life

#### Control

- . DMX Modes: 4
- . DMX Channels: 1, 2, 3, and 6
- . RDM (Remote Device Management)
- . Art-Net Protocol Support
- . Primary/Secondary Modes
- . Onboard 4 Button Touch Control Panel

#### Connections

- . Data Connectors: 5-pin XLR In/Out
- . Locking Power Connector

#### Construction / Physical / Performance

- . Dimensions (LxWxH): 8.58 x 5.90 x 9.72 in. / 218 x 150.6 x 246.6mm
- . Weight: 5.29 lbs. / 2.40kg
- . DB Rating: 41DN (@1m)

#### Electrical

- . Input Voltage: AC 100-240V, 50/60Hz
- . Amperage: 110v/0.47A, 240V/0.23A
- . Power Consumption: 27W
- . Fuse: T2A/250V





# PRISMA PAR 20

## SPECIFICATIONS / TECHNICAL DATA REV A

### Certifications / Qualifications / Thermal

- . IP Rating: IP65 Rating
- . Approvals: ROHS, CE Approved
- . Cooling: Air Cooled
- . Maximum Temperature (Ambient): 113° F (45° C)
- . Minimum Temperature (Ambient): 14° F (-10° C)
- . ETL Approved

### What's Included

- . Twist Locking Power Cable

### Optional Accessories

- . Prisma Par Black Glass (PSG852)



218 mm  
(8.58 in.)



150 mm  
(5.90 in.)

247 mm  
(9.72 in.)

MAGMATIC