



Absenicon C Series

C Standard | C Slim

Absenicon C Series is a revolutionary all-in-one LED screen, including standard and slim versions. It helps users to better facilitate presentations, brainstorming and decision-making. Delivering effective, convenient, comfortable, smart meeting/education experience.



Native 16:9 Size
Diagonal 110" 138" 165"



High Brightness
0~600nits adjustable*



Precise Alignment
Seamless visual experience



Remote Control
User-friendly interface



Screen Mirroring
Phone, Computer, Pad



Intelligent OS
Android 8.0/Windows 10*(Optional)

Application



Meeting Room



Lecture Hall



Others

*0~600nits adjustable: C Standard is 350nits standard brightness, 600nits brightness adjustable

*Supporting for Windows system is optional. External OPS PC and the supporting structural parts are required

Features

Stunning Visuals

High refresh rate, high gray scale, wide color gamut

- 110% NTSC color gamut
- 1920 x 1080p
- 160° wide viewing angle
- Bezel-free



All-in-One Design

- Integrated display with LED cabinets, controller, wall mounts and all necessary display elements
- No external equipment required



Easy to Operate

- User-friendly interface and remote-control design
- Plug and play
- One click casting
- Free App download



Ultra-slim Trim Piece

- 28.5mm depth*
- 5mm ultra-slim trim piece



*The thinnest part of the screen body is only 28.5mm

Product specification

Product	C Standard			C Slim		
	C110	C138	C165	C110S	C138S	C165S
Model	C110	C138	C165	C110S	C138S	C165S
Diagonal size (inch)	110	138	165	110	138	165
Display area (H x V) (mm)	2440*1372	3050*1715	3660*2058	2440*1372	3050*1715	3660*2058
Resolution	1920x1080	1920x1080	1920x1080	1920x1080	1920x1080	1920x1080
Screen body size (mm)	2450x1487x28.5	3060x1830x28.5	3670x2173x28.5	2450x1400x28.5	3060x1743x28.5	3670x2086x28.5
Weight (kg) (wall mounting)	92	135	198	117	175	247
Brightness* (nits)	350	350	350	600	600	600
Contrast ratio	4000:1	5000:1	4000:1	4000:1	5000:1	4000:1
View angle (°)	160/140	160/140	160/140	160/140	160/140	160/140
Input power	AC 100-240V	AC 100-240V	AC 100-240V	AC 100-240V	AC 100-240V	AC 100-240V
Avg. power (w)	400	500	600	584	667	800
Max. power (w)	1200	1500	1800	1750	2000	2400
Android system	Android 8.0	Android 8.0	Android 8.0	Android 8.0	Android 8.0	Android 8.0
Windows system	Optional	Optional	Optional	Optional	Optional	Optional
System memory	4GB	4GB	4GB	4GB	4GB	4GB
Storage	16GB	16GB	16GB	16GB	16GB	16GB
Operating temperature	-10°C~40°C	-10°C~40°C	-10°C~40°C	-10°C~40°C	-10°C~40°C	-10°C~40°C
Operating humidity	10~80%RH	10~80%RH	10~80%RH	10~80%RH	10~80%RH	10~80%RH
Storage temperature	-40°C~60°C	-40°C~60°C	-40°C~60°C	-40°C~60°C	-40°C~60°C	-40°C~60°C
Storage humidity	10%~85%	10%~85%	10%~85%	10%~85%	10%~85%	10%~85%

*Shenzhen Absen Optoelectronic Co., Ltd. reserves the right to modify product design, specifications, and parameters without further notice

*The thinnest part of the screen body is only 28.5mm



HQ Office
7120 Lake Ellenor Dr Orlando, FL 32809
407.203.8870 info@usabsen.com
www.usabsen.com

East Service Center&Warehouse
7307 Presidents Drive, Orlando, FL 32809
West Service Center & Showroom
20311 Valley Blvd Suite J, Walnut, CA 91789

Twitter: @Absen_Inc
Facebook: @AbsenInc
LinkedIn: @AbsenInc
IG: @absen_inc