



ANCHORLINK

Wireless Platform



TECH SPECS

- Operates in the 1.9 GHz license free wireless frequency range
- Automatic Channel Switching
- 300'+ line of sight wireless range

FEATURES

- Mute and volume controls on the belt pack and handheld
- Microphone one time pairing function
- Each built-in dual wireless mic receiver handles two wireless microphones



WH-LINK Technical Specifications

Wireless Frequency	1.9 GHz DECT US: 1921 Hz - 1928 Hz Japan: 1895 Hz - 1902 Hz Europe: 1881 Hz - 1897 Hz
Wireless Range	300'+ line of sight
RF Output Power	23 dBm
Frequency Response	60 Hz – 11.3 kHz ± 3 dB
Microphone Type (Sensitivity)	Dynamic; -52 ± 3 dB @ 1 kHz
Pick Up Pattern	Cardioid
Power Supply	Two 'AA' batteries (LR6)
Dimensions (HW)	9.81" x 2.25" (24.9 x 5.7 cm)
Weight	0.6 lb / 0.27 kg
Warranty	2 years

WB-LINK Technical Specifications

Wireless Frequency	1.9 GHz DECT US: 1921 Hz - 1928 Hz Japan: 1895 Hz - 1902 Hz Europe: 1881 Hz - 1897 Hz
Wireless Range	300'+ line of sight
RF Output Power	23 dBm
Frequency Response	60 Hz – 11.4 kHz ± 3 dB
Input	3.5 mm
Dimensions (HWD)	3.93" x 2.66" x 1" (10 x 6.8 x 2.5 cm)
Weight	0.3 lb / 0.14 kg
Warranty	2 years

Microphone Elements

HBM-LINK - Headband Mic

Microphone Type	Electret Condenser
Pick Up Pattern	Unidirectional
Connector	3.5 mm

CM-LINK - Collar Mic

Microphone Type	Electret Condenser
Pick Up Pattern	Unidirectional
Connector	3.5 mm

EM-LINK - UltraLite Mic

Microphone Type	Electret Condenser
Pick Up Pattern	Unidirectional
Connector	3.5 mm

LM-LINK - Lapel Mic

Microphone Type	Electret Condenser
Pick Up Pattern	Unidirectional
Connector	3.5 mm



(Features & Specifications Subject to Change Without Notice)