



## LED-1906HDMTR

Full HD resolution, rack mount, LED-backlit, mid-size monitor with TV tuner housed in a durable metal case with a front control membrane. Built for active use in public spaces, this monitor is versatile and effective for any commercial video application.

### Benefits

Displays Full HD (1920 x 1080) signals (1080i/p) with no downscaling

3D + 3D image processing with digital noise reduction

Built-in ATSC / Clear QAM Tuner

Durable metal rack mount and housing

Built-in speakers

IR remote control

Includes Hospitality Features: Maximum volume, Key Lock, Scan Lock, and Auto Reset which maintains Startup Channel, Power On Volume, and Power On Source

### Related Products

LED-1906HDMT: Wall mount version with removable deskstand

LED-1906HDMTL: Flush mount version of the LED-1906HDT



Specifications	
Mount	Rack (7RU)
Screen Panel	18.5" TFT Active Matrix
HD Compatible	Yes
Anti Glare Coating	Yes
Case	Metal
IR Remote Control	Yes
Native Aspect Ratio	16:9
Visible Screen Size (WH)	16.1" x 9.1" / 409.8 x 230.4mm
Resolution	1920(H) x 1080(V)
Brightness Rating	250 cd/m <sup>2</sup> (Nit)
Contrast Ratio	1200:1
Back Light	LED (30K)
Dot Pitch	0.30(H) x 0.30(V)mm
Color Depth	16.7M
Number of Pixels	1,049,088
Response Time	5ms (Rising/Falling)
Audio Power / Speakers	8 Ohm, 2 Speakers x 2 Watts
Viewing Angle (L/R/T/B)	89/89/89/89 degrees
3D Comb Filter	Yes
Operating Temp	6 ~ 104°F / -14 ~ 40°C
Humidity	10% - 90%
Power Requirements	100 ~ 240 VAC; 50/60Hz
Power Consumption	<25 Watts (Max); <= 0.5 Watts (Stand-by)
TV (ATSC/QAM Digital Tuner)	x1 F (Coax) Input
HDMI	x2 Inputs
VGA (RGB)	x1 15-pin mini D-sub Input
Component	x1 RCA YPbPr Input
Composite	x2 RCA Inputs; x1 RCA Output
Audio	x2 L/R RCA Inputs; x1 RCA L/R Output; x1 3.5mm PC Stereo Input; x1 3.5mm earphone Output; x1 Coaxial Output
USB	x1 Input for firmware updates only
Weight	Net: 8.8 lbs / 4 kg; Gross: 11 lbs / 5 kg

Specifications subject to change.