RDNET CONTROL 2
2 OUTPUT MASTER UNIT

Description

The RDNet Control 2 is an hardware interface to connect RCF RDNet compatible devices (TTL55-A, TTL33-A II, TTL31-A II, etc.) to a Personal Computer (PC) by means of an USB connection. The RDNet system was purposely developed to create a data network for monitoring and command of more systems. The RDNet Control 2 unit can manage up to 2 subnets. Up to 32 devices can be connected to each subnet (2 subnets x 32 = total 64 devices).

The addressing of the various devices is handled automatically by RDNet Control 2 interface. Each device is assigned a unique address during the power on procedure of network. For the RDNET network operating, it is necessary to install the appropriate Software on PC, on Microsoft Windows® environment. From PC it is possible to check the operating of each single device connected to the network and edit its parameters output level, mute, equalization, delay, etc. The network and devices configuration can be saved as file in the PC and later reloaded. RDNET is a "real-time" system: Information relating to the functioning of the devices is acquired in real-time, a feature that allows a global view of connected devices.

Features

› Real-time USB device monitoring and control
› Control up to 2 sub-nets of up to 32 slave devices
› All devices are cyclically scanned ("POLLING") 10 times a second
› Auto detect device placement
› Connected devices are automatically added to the software synoptic

Part Number

17170163   RDNET CONTROL 2   Black   EAN 8024530010041

RDNET CONTROL 2

2 OUTPUT MASTER UNIT

TECHNICAL SPECIFICATIONS

General specifications

Number of subnets:	2
Connectors:	RJ 45, XLR
Max number of devices (for each subnet)	32
Configuration:	PC software
PC connection:	USB (typeB)
Power supply:	Powered by USB socket
RDNet	Yes

Standard compliance

Safety agency	CE compliant

Physical specifications

Color	Black

Size

Height	41 mm / 1.61 inches
Width	111 mm / 4.37 inches
Depth	90 mm / 3.54 inches
Weight	0.17 kg / 0.37 lbs