













-  6,500 Watts
-  Aluminum Face
-  Amp
-  Bridge Mode
-  Carry Handle
-  Fan
-  LED Meter
-  RCA Input
-  Steel Construction
-  XLR Inputs

## PRICING

MSRP \$219.00

## SPECIFICATIONS

Carton Size: 39.5 L x 54.0 W x 50.5 H(cm)

15.6" L x 21.3" W x 19.9" H

Pcs/Carton: 3

Unit Weight(lbs): 18 Unit Cbm: 0.0359

Product Size: 11.14 L x 19.02 W x 3.94 H

Giftbox: L x W x H

Voltage: 110v

## UPC

UPC: 817802017842

## PLACING ORDER

Technical Pro  
9 Kilmer Ct. Edison NJ 08817  
1-888-842-6277 Ext. 7  
Info@tpro.com www.tpro.com

## DESCRIPTION

6000 watts peak power

Inputs: XLR, 1/4", RCA

Outputs: Banana binding post, Speakon, 1/4"

Spectrum LED Display

Bridge / stereo

Dual cooling speed fans

Precise LED meters signal and clip and protect indicators to monitor performance

"CAF" (Complete Air Flow) ventilation system with automatic variable-speed fan for smooth and quiet operation

High-quality components and exceptionally rugged construction ensure long life and quality performance

Frequency Response: 20Hz-20kHz  $\pm 1$  dB

Damping factor: >200 @ 8 ohm

Signal to Noise Ratio: -105 dB unweighted 20Hz-20kHz

Total Harmonic Distortion: <0.02%

Input Impedance: 20 kohm balanced/ 10 kohm unbalanced

Input Sensitivity: .775V (0dBu)