



Super CAT Sound

Entertainment Grade Shielded Cat Cable

CAT5e AWG26/19 U/FTP

Durable

Professional

Flexible

High performance category 5e cable for professional touring and portable applications

Super Cat Sound combines Cat5e/6/7 cable technologies with the wisdom of conventional audio snake construction to create a product that exceeds several Cat 7 specifications and has the durability and flexibility of premium pro audio cable

12 wire cable consisting of: four foil-shielded twisted pairs, each with a dedicated ground drain wire

SuperCat Sound can be terminated to RJ45, etherCON or directly to tails

Conductor	26/19
Jacket	Halogen free polyurethane
Capacitance	48 pF/m
Impedance	100Ω
Prop velocity	68%
Prop delay	4.85 ns/m
Delay skew	15 ns/100m

Temp	-40°C/+80°C
Max pull	300 N
Att¹	27.7 dB/100m
Ps Next¹	90dB
Ps El-Fext¹	81dB dB/100M
Ps Acr¹	67.7 dB/100M
Rtn Loss¹	28 dB/100m

¹100MHz

Compliant:
Fire: EN 50267-2-1, IEC 60754-1, EN 50267-2-2, IEC 60754-2
Reference: IEC 61156-6, EN 50288-4-2, AES/EBU
Oil: IEC60811-2-1, ICEA S-82-552
UV: UL 1581 §1200 **Mud:** NEK 606 **Ozone:** EN 50396
Microbe: VDE 0282/10
Saturated carbon resistance: good