











## AUDIO – MICROPHONE CABLE, 2-CONDUCTOR SHIELDED

ITEM			GAUGE	STRANDING	O.D.	PF/FT	SHIELD	JACKET
Belden	8412		20	26 x 34	.262"	30	85% Braid	EDPM Rubber
Gepco	MP1022		24	41 x 40	.195"		95% Braid Synth	Rubber
Liberty	22-1P-EZ-BLK		22	7 x 30	.155"		100% Alum/Poly Foil	PVC
Mogami	W2549		22	30 x 37	.236"	23		Super Flexible PVC
Whirlwind	WMKPVC		22	26 x 36		35	78% BC Braid	Flexible PVC, black

## AUDIO – ANALOG MIC CABLE: 4-CONDUCTOR STAR-QUAD, LOW NOISE, FOR PORTABLE USE



ITEM			GAUGE	STRANDING	O.D.	PF/FT	SHIELD	JACKET
Canare	L4E6S		24	40	.237"	46	95% Braid	PVC
Liberty	24-2P-STAR-BLK		24	41 x 40	.24"		96%	PVC
Mogami	W2534		24	20 x 37		20	Spiral	Super Flexible PVC

## AUDIO – ANALOG MIC/LINE PERMANENT INSTALL, 2-CONDUCTOR, FOIL SHIELD WITH DRAIN WIRE



ITEM			GAUGE	STRANDING	O.D.	PF/FT	SHIELD	JACKET	NEC
Belden	1503A		22	7 x 30	.142"	53	100% Foil	PVC	CM
Belden	8450		22	Solid	.118"	40	100% Foil	PVC	CM
Belden	9451		22	7 x 30	.135"	34	100% Foil	PVC *	CMR
Canare	L4E6AT		20		.244"	46	100% Alum. Tape	PVC	
Gepco	61801EZ		22	7 x 30	.140"	34	100% Foil	PVC	CMR
Liberty	22-1P-CMP-EZ-BLK		22	7 x 30	.13"		100% Alum/Poly Foil	PVC	CMP
West Penn	291		22	7 x 30	.165"		100% Foil	PVC	CL2
West Penn	292		20	7 x 28	.184"		100% Foil	PVC	CL2
West Penn	293		18	7 x 26	.208"		100% Foil	PVC	CL2
West Penn	25291B		22	7 x 30	.165"		100% Foil	PVC	CMP
West Penn	25292B		20	7 x 28	.143"		100% Foil	PVC	CMP

\* Features self-stripping foil and BananaPeel- no jacket, just pull and peel.

## AUDIO – DIGITAL MIC CABLE: AES/EBU 2-CONDUCTOR SHIELDED, 110 OHMS, LOW CAPACITANCE

ITEM			GAUGE	STRANDING	O.D.	PF/FT	SHIELD	JACKET
Cable Up	AES7-500		24	7 x 30	.198"	14.5	95% Braid	Non-plen PVC
Canare	DA206		20		.287"	14.6	95% Braid	Non-plen PVC, blue

## AUDIO – ANALOG MIC/LINE MULTIPAIR (SNAKE), FOIL SHIELD, COMMON JACKET

ITEM			GAUGE	PAIRS	O.D.	PF/FT	SHIELD	JACKET	NEC
Gepco	6604HS		22	4	.285"	52	100% Foil/mylar side out	Plenum PVC	CMP
Gepco	6608HS		22	8	.385"	52	100% Foil/mylar side out	Plenum PVC	CMP

Bulk wire is available in standard spool lengths, and some can be cut to your requirements. Please call for specifics.

## BULK WIRE NEC RATINGS

CMP – Rated for all in-wall, plenum and riser applications. • CMR, CL3R, CL2R – Rated for all in-wall and riser applications, not permitted in plenums.  
CM, CMG, CL2 – In-wall rated; permitted in 1-2 family residential riser applications, or in riser with raceway/fireproof shaft; not permitted in plenums.



**AUDIO – ANALOG MIC/LINE MULTIPAIR (SNAKE) WITH INDIVIDUAL JACKETS PER PAIR**

ITEM			GAUGE	PAIRS	O.D.	PF/FT	SHIELD	JACKET	NEC
<b>Gepco</b> - Call for Length information, some available by the foot (varies).									
Gepco	<b>GA61804GFC</b>		22	4	.40"	60		PVC	CMR
Gepco	<b>GA61806GFC</b>		22	6	.475"	60		PVC	CMR
Gepco	<b>GA61812GFC</b>		22	12	.635"	60		PVC	CMR
Gepco	<b>GA61820GFC</b>		22	20	.800"	60		PVC	CMR
Gepco	<b>GA61826GFC</b>		22	26	.840"	60		PVC	CMR
Gepco	<b>GA61832GFC</b>		22	32	.935"	60		PVC	CMR
<b>Gepco</b> - Direct Burial series - for permanent underground installs, incl. water blocking tape that is wrapped around cable core, difficult to puncture.									
Gepco	<b>GA61806PEF</b>		22	6	.475"	48	100% Foil	PVC/Base10	
Gepco	<b>GA61812PEF</b>		22	12	.635"	48	100% Foil	PVC/Base10	
<b>Mogami</b> - Super flexible down to -2° C, channel #s printed & underlined on jacket to ensure correct ID. Ideal for soldering or crimping to connectors.									
Mogami	<b>W2932</b>		25	8	.453"	40		PVC	
Mogami	<b>W2934</b>		25	16	.622"	40		PVC	
Mogami	<b>W2936</b>		25	24	.787"	40		PVC	
Mogami	<b>W2938</b>		25	32	.854"	40		PVC	
Pro Co	<b>AC4</b>		24	4	.425"	21		PVC	
Pro Co	<b>AC8</b>		24	8	.550"	21		PVC	

**AUDIO – SPEAKER CABLE, PORTABLE HIGH FLEXIBILITY, HEAVY DUTY JACKET**

ITEM			GAUGE	COND.	O.D.	JACKET	NEC	DESCRIPTION
<b>Belden</b> - 2 Conductor, ultra flexible, ideal for home theater installs, jackets marked at 2' intervals. Black, white, gray blue or green jackets.								
Belden	<b>5000UP</b>		12	2	.302"	PVC	CL3	
Belden	<b>5200UP</b>		16	2	.208"	PVC	CM	
Canare	<b>4S8</b>		16	4	.327"	PVC		General purpose, biamp rigs
Canare	<b>4S11</b>		11	4	.421"	PVC		Long runs, subwoofers, gray only
<b>Gepco</b> - All-weather TPE outer jacket, round construction, ideal for Speakon.								
Gepco	<b>GSC132</b>		13	2	.350"	TPE, black		
Gepco	<b>GSC134</b>		13	4	.420"	TPE, black		
Gepco	<b>GSC138</b>		13	8	.580"	TPE, black		
Pro Co	<b>11-4</b>		11	4		PVC		
Pro Co	<b>14-4</b>		14	4		PVC		
Pro Co	<b>13-8</b>		13	8		PVC		
Pro Co	<b>14-2</b>		14	2		PVC		

*Bulk wire is available in standard spool lengths, and some can be cut to your requirements. Please call for specifics.*

Visit [fullcompass.com](http://fullcompass.com) today!

For expert advice - call: 800-356-5844

M-F: 9:00-5:30 Central



AUDIO



MUSIC



COMPUTER AV



VIDEO






LIGHTS










ACCESSORIES









## AUDIO – GUITAR / KEYBOARD / INSTRUMENT CABLE

ITEM	GAUGE	COND.	O.D.	PF/FT	SHIELD	JACKET
<b>Cable Up</b> - Guitar cable, low noise, low capacitance.						
Cable Up <b>M54C-500</b> 	20	1	.236"	37.2	PVC	Conductive PVC Layer
<b>Canare</b> - For electronic instruments, test probes, audio patch, and amp to cabinet leads.						
Canare <b>GS6</b> 	18	1	.228"	49	OFC >92% Braid	Carbon Sleeve
<b>Gepco</b> - Data-grade, foam dielectric (drastically reduces capacitance), abrasion resistant PVC.						
Gepco <b>XB20UB</b> 	20	1	.228"	22.3	Double 95% TC Braid	PVC





## AUDIO – UNSHIELDED CABLE: FOR SPEAKER AND CONTROL APPLICATIONS

ITEM	GAUGE	COND.	O.D.	STRANDING	JACKET	NEC
Belden <b>8471</b> 	16	2	.274"	19 x 29	PVC	CMG
Belden <b>8477</b> 	22	2	.386"	65 x 30	PVC	CL3R
Coleman <b>23288</b> 	12	2	.41"	65 x 30	T*Prene	
Gepco <b>GSC134</b> 	13	4		52 x 30	PVC	
Liberty <b>22-2P-SHEX-YEL</b> 	22	2	.186"	16 x 34	PVC	CL3
Pro Co <b>14-2</b> 	14	2	.325"	41 x 30	PVC	
Pro Co <b>12-2</b> 	12	2	.365"	65 x 30	PVC	
West Penn <b>224</b> 	18	2	.186"	7 x 26	PVC	CL2, CMR
West Penn <b>226</b> 	14	2	.24"	19 x 27	PVC	CL2, CMR
West Penn <b>227</b> 	12	2	.278"	19 x 25	PVC	CL2, CMR
West Penn <b>25224B</b> 	18	2	.138"	7 x 26	Plenum	CMP

## AUDIO – S/PDIF DIGITAL AUDIO CABLE – 75 OHM

ITEM	GAUGE	STRANDING	O.D.	PF/FT	JACKET	NEC
Belden <b>1505F</b> 	22	7 x 29	.242"	17	PVC Black	CM
Gepco <b>VDM230</b> 	Mini23	Solid	.164"	16.5	PVC, Multiple Colors	CMR
Gepco <b>VHD1100</b> 	RG11/14	Solid	.405"	16.2	PVC, Multiple Colors	CMR
Gepco <b>VHD2000M</b> 	21	19 x 34	.242"	17	Flexible PVC	
Gepco <b>VSD2001</b> 	RG6/18	Solid	.272"	16.3	PVC, Multiple Colors	CMR
Gepco <b>VPM2000</b> 	RG59/20	Solid	.272"	16.3	PVC, Multiple Colors	CMR

## AC – POWER CABLE FOR PORTABLE USE

ITEM	GAUGE	COND.	JACKET
Coleman <b>22327</b> 	14	3	TPE Seoprene
Coleman <b>22328</b> 	12	3	TPE Seoprene
Coleman <b>22329</b> 	10	3	TPE Seoprene
Coleman <b>23388</b> 	12	3	T*Prene SJEW






*Bulk wire is available in standard spool lengths, and some can be cut to your requirements. Please call for specifics.*

## BULK WIRE NEC RATINGS








**CMP** – Rated for all in-wall, plenum and riser applications. • **CMR, CL3R, CL2R** – Rated for all in-wall and riser applications, not permitted in plenums.  
**CM, CMG, CL2** – In-wall rated; permitted in 1-2 family residential riser applications, or in riser with raceway/fireproof shaft; not permitted in plenums.







LIGHTING – DMX CABLE – BULK

ITEM			GAUGE	COND.	STRANDING	O.D.	SHIELD	JACKET	NEC
Belden	9729		24	4	7 x 32	.024"	100% Foil	PVC	CM
Belden	9841		24	4	7 x 32	.232"	100% Foil + 90% TC Braid	PVC	CM
Belden	9842		24	4	7 x 32	.34"	100% Foil + 90% TC Braid	PVC	CM
Gepco	DLC124		24	2	7 x 32	.024"	100% Foil + 90% TC Braid	PVC	
Gepco	DLC224		24	4	7 x 32	.27"	100% Foil + 90% TC Braid	PVC	






DATA – CAT5E AND CAT6 BULK CABLE

ITEM		TYPE	GAUGE	COND.	PAIRS	O.D.	PF/FT	STRANDING	JACKET	NEC	
Belden	1583A-1000		CAT5e	24	8	4	.214"	15	Solid	PVC	CMR
Belden	1585A-1000		CAT5e	24	8	4	.2"	15	Solid	Plenum	CMP
Belden	10GX12		CAT6	23	8	4	.295"	17	Solid	PO	CMR
Belden	10GX13		CAT6	23	8	4	.295"	17	Solid	Plenum	CMP
Gepco	CT504HD		CAT5e	24		4	.26"	17	41 x 40	TPE, black	
Liberty	24-4P-L5SH-EN-BLU		Shielded CAT5	24	8	4	.237"	17.0	Solid	FR-PVC	CMR
Liberty	24-4P-L6SH-BLK		Shielded CAT6	24	8	4	.270"	17.0	Solid	FR-PVC	CMR



DIGITAL/ANALOG VIDEO – 75 OHM SDI/HDSDI COAXIAL CABLE – RG6

ITEM		GAUGE	STRAND	O.D.	PF/FT	VEL-PROP	SHIELD	JACKET	NEC	
Belden	WV-1694D		2 x 18	Solid	.334" x .618"	16.2	82%	100% Duofoil+95%TCBraid	Non-plenum	CMR
Belden	1694A		RG6/18	Solid	.275"	16.2	82%	100% DuoFoil+95%TCBraid	Non-plen PVC	CMR
Belden	1695A		RG6/18	Solid	.234"	16.2	82%	100% DuoFoil+95%TCBraid	Plenum	CMP
Liberty	18-CMR-SD-BLK		18	Solid	.27"	16.2	82%	100% Alum/Poly+95%TCBraid	PVC	CMP

DIGITAL/ANALOG VIDEO – 75 OHM SDI/HDSDI COAXIAL CABLE – RG59

ITEM		GAUGE	STRAND	O.D.	PF/FT	VEL-PROP	SHIELD	JACKET	NEC	
Belden	1505A		RG59/20	Solid	.233"	16.3	83%	100% DuoFoil+95%TCBraid	Non-plen PVC	CMR
Cable Up	RG59ST-500		RG59/22	7 x 29	.242"	17	80%	Double TC Braid 95%	Non-plen PVC	CM
Gepco	VPM2000		RG59/20	Solid	.242"	16.3	83%	100%Foil/95%TCBraid	Non-plen PVC	CMR
Gepco	VPM2000TS		RG59/20	Solid	.2"	16	84%	100%Foil/95%TCBraid	Plen PVC	CMP
Liberty	20-CMR-VIDEO-BLK		20	Solid	.24"			100%Alum/Poly+95%TCBraid	PVC	CMR

VIDEO – RG-59/8281F TYPE (STANDARD & PLENUM) SINGLE CHANNEL

ITEM		GAUGE	STRANDING	O.D.	PF/FT	VEL-PROP	SHIELD	JACKET	NEC	
Belden	8241		RG59/23	Solid	.242"	21	66%	95%Braid	PVC	CM
<b>Canare</b> - Highly flexible, copper braid shield polyethylene dielectric										
Canare	LV61S		RG59/24	7/7.88	.24"	21	66%	95% Braid	Poly	

Bulk wire is available in standard spool lengths, and some can be cut to your requirements. Please call for specifics.

Visit [fullcompass.com](http://fullcompass.com) today!

For expert advice - call: 800-356-5844

M-F: 9:00-5:30 Central

